

Radio Editors of magazines and newspapers are hereby given permission to reprint in whole or in part, with proper credit to the Aerovox Corporation, the contents of this issue of the Aerovox Research Worker.

The AEROVOX

Research Worker

The Aerovox Research Worker is a monthly house organ of the Aerovox Corporation. It is published to bring to the Radio Experimenter and Engineer authoritative, first hand information on capacitors and resistances for radio work.

VOL. 18, NO. 8

AUGUST, 1946

50c per year in U.S.A.
60c per year in Canada

V. H. F. PRIMER

PART 6. WAVE GUIDE TABLES

By the Engineering Department, Aerovox Corporation

Accompanying this paper are two tables of wave guide data; one a chart showing cut-off wavelengths and corresponding frequencies for common sizes of square wave guides, and the other a chart giving similar data for common sizes of circular wave guides. The Editors believe that square and circular pipes will be the types most commonly employed by amateurs and experimenters, and have set up the tables for these two cross sections only. The prospective user of wave guides may consult these tables to save himself the labor of calculation when seeking cut-off values for common pipe dimensions.

In the first column of each table, common standard pipe sizes are listed every one-sixteenth of an inch apart from $\frac{1}{8}$ inch (diameter of circular type or per-side measurement of square type) to 2 inches. These

sizes will be entirely useful in the majority of cases.

The wavelength and frequency values given in each table are those corresponding to the three simplest modes, which very likely will be the principal ones in which amateurs and experimenters will be interested. These are TE_{01} ; TE_{11} ; and TM_{11} , for square wave guides and TE_{02} ; TE_{11} ; and TM_{01} for circular wave guides. The frequencies listed in several instances exceed the present 30,000-Mc. limit of allocated super-high-frequency spectrum. However, the Editors feel that this particular data will be useful in appraising available pipes and tubes of very small cross section.

All dimensions are in inches, wavelengths in centimeters, and frequencies in megacycles per second. If it is desired to determine the size of

pipe required for a cut-off wavelength not listed in the tables, one of the following equations, corresponding to the cross section and mode concerned, may be employed.

A. SQUARE WAVE GUIDES

- (1) TE_{01} $a = \lambda/5.08$
- (2) TE_{11} $a = \lambda/3.592$
- (3) TE_{11} $a = \lambda/3.592$

B. CIRCULAR WAVE GUIDES

- (4) TE_{02} $d = \lambda/2.083$
- (5) TE_{11} $d = \lambda/4.394$
- (6) TM_{01} $d = \lambda/3.327$

In each equation:

λ = cut-off wavelength in centimeters.

a = one side of square in inches


d = diameter of circle in inches

(a and d are inside dimensions)

AEROVOX PRODUCTS ARE BUILT BETTER




TABLE 1. Square Types



INSIDE DIMENSIONS (inches)	CUT-OFF WAVELENGTH (cms.)			CUT-OFF FREQUENCY (Mc.)		
	TE _{0,1}	TE _{1,1}	TM _{1,1}	TE _{0,1}	TE _{1,1}	TM _{1,1}
1/8 x 1/8	0.635	0.449	0.449	47,244.1	56,815.1	56,815.1
3/16 x 3/16	0.953	0.674	0.674	31,479.5	44,543.4	44,543.4
1/4 x 1/4	1.270	0.898	0.898	23,622	33,407.6	33,407.6
5/16 x 5/16	1.588	1.123	1.123	18,887.7	26,726	26,726
3/8 x 3/8	1.905	1.348	1.348	15,748	22,271.7	22,271.7
7/16 x 7/16	2.223	1.572	1.572	13,491.2	19,090	19,090
1/2 x 1/2	2.540	1.796	1.796	11,811	16,703.8	16,703.8
9/16 x 9/16	2.856	2.021	2.021	10,493.2	14,958.9	14,958.9
5/8 x 5/8	3.175	2.245	2.245	9448.8	13,363	13,363
11/16 x 11/16	3.493	2.470	2.470	8585.3	12,139.1	12,139.1
3/4 x 3/4	3.810	2.694	2.694	7874	11,135.8	11,135.8
13/16 x 13/16	4.128	2.919	2.919	7264.5	10,279.2	10,279.2
7/8 x 7/8	4.445	3.143	3.143	6749.2	9545	9545
15/16 x 15/16	4.763	3.368	3.368	6295.9	8908.7	8908.7
1 x 1	5.080	3.592	3.592	5905.5	8351.8	8351.8
1 1/16 x 1 1/16	5.398	3.817	3.817	5555.2	7860.6	7860.6
1 1/8 x 1 1/8	5.715	4.041	4.041	5249.3	7423.9	7423.9
1 3/16 x 1 3/16	6.033	4.266	4.266	4970.4	7033.1	7033.1
1 1/4 x 1 1/4	6.350	4.490	4.490	4724.1	6681.5	6681.5
1 5/16 x 1 5/16	6.670	4.715	4.715	4497.1	6363.6	6363.6
1 3/8 x 1 3/8	6.985	4.939	4.939	4294.9	6074.1	6074.1
1 7/16 x 1 7/16	7.303	5.164	5.164	4106	5810	5810
1 1/2 x 1 1/2	7.620	5.388	5.388	3937	5567.9	5567.9
1 9/16 x 1 9/16	7.938	5.613	5.613	3777.5	5345.2	5345.2
1 5/8 x 1 5/8	8.255	5.837	5.837	3634.2	5139.6	5139.6
1 11/16 x 1 11/16	8.573	6.062	6.062	3497.7	4949.3	4949.3
1 3/4 x 1 3/4	8.890	6.286	6.286	3374.6	4772.5	4772.5
1 13/16 x 1 13/16	9.208	6.511	6.511	3256.5	4607.9	4607.9
1 7/8 x 1 7/8	9.525	6.735	6.735	3149.6	4454.3	4454.3
1 15/16 x 1 15/16	9.843	6.960	6.960	3046.4	4310.6	4310.6
2 x 2	10.160	7.184	7.184	2952.8	4175.9	4175.9



TABLE 2. Circular Types



INSIDE DIAMETER (inches)	CUT-OFF WAVELENGTH (cms.)			CUT-OFF FREQUENCY (Mc.)		
	TE _{0,2}	TE _{1,1}	TM _{0,1}	TE _{0,2}	TE _{1,1}	TM _{0,1}
1/8	0.260	0.549	0.416	115,300	54,650	72,250
3/16	0.390	0.824	0.624	76,900	36,400	48,100
1/4	0.521	1.098	0.832	57,700	25,739	36,300
5/16	0.651	1.373	1.040	46,250	21,850	28,850
3/8	0.710	1.648	1.248	42,300	18,210	24,250
7/16	0.911	1.925	1.456	32,950	15,590	20,640
1/2	1.041	2.197	1.664	28,800	13,660	18,000
9/16	1.172	2.472	1.872	25,600	12,120	16,030
5/8	1.302	2.746	2.080	25,100	10,900	14,420
11/16	1.432	3.021	2.287	20,950	9,940	13,100
3/4	1.562	3.296	2.496	19,200	9,110	12,020
13/16	1.692	3.570	2.703	17,750	8,410	11,100
7/8	1.823	3.845	2.991	16,460	7,810	10,025
15/16	1.953	4.119	3.119	15,380	7,280	9,640
1	2.083	4.394	3.327	14,390	6,835	9,010
1 1/16	2.213	4.669	3.535	13,550	6,438	8,485
1 1/8	2.343	4.944	3.743	12,790	6,075	8,010
1 3/16	2.473	5.218	3.951	12,130	5,760	7,595
1 1/4	2.603	5.493	4.159	11,530	5,469	7,230
1 5/16	2.734	5.767	4.367	10,950	5,200	6,875
1 3/8	2.864	6.042	4.575	10,480	4,971	6,565
1 7/16	2.994	6.327	4.783	10,010	4,740	6,270
1 1/2	3.124	6.591	4.991	9,610	4,550	6,017
1 9/16	3.254	6.866	5.199	9,230	4,370	5,775
1 5/8	3.384	7.141	5.407	8,860	4,200	5,450
1 11/16	3.514	7.415	5.615	8,540	4,045	5,349
1 3/4	3.645	7.690	5.823	8,235	3,900	5,150
1 13/16	3.775	7.965	6.031	7,945	3,765	4,975
1 7/8	3.905	8.239	6.239	7,690	3,640	4,810
1 15/16	4.035	8.514	6.447	7,475	3,525	4,660
2	4.165	8.788	6.655	7,225	3,439	4,505

Introducing... the new **Aerovox Series 83**

PLASTIC-CASE PAPER TUBULAR

that withstands

HEAT and **HUMIDITY**



Combination of special plastic casing and special sealing compounds for ends, insures immunity to moisture.

Already rated for operation at maximum temperature of 95° C. (203° F.).

Will not deteriorate under normal storage conditions.

Overall dimensions identical with those of Aerovox paper tubulars of corresponding voltages and capacitance values.

Somewhat higher in cost than corresponding paper tubulars.



"Slick as a Seal"

● Forget about that melting and dripping wax when it comes to tubular capacitors operating at elevated temperatures. Especially in auto radios. Also forget about humidity; capacitors sticking together and picking up dirt; premature breakdown.

The new Aerovox plastic-case bonded-seal tubulars (Series -83) now protect your good name with performance insurance. Slick as a seal, these clean, bright, handy tubulars are immune to temperatures ranging from sub-zero cold up to sizzling heat, and

impervious to moisture penetration.

This latest Aerovox development (patents pending) overcomes usual objections to paper tubulars for the *more critical* applications. The rigid plastic case with bonded-seal ends, provides real protection for the capacitor section. Overall wax dip becomes a thing of the past, while rigid humidity tests are readily met.

Simply install them—forget them—and be insured!

● Write for further details...



FOR RADIO-ELECTRONIC AND INDUSTRIAL APPLICATIONS

AEROVOX CORPORATION, NEW BEDFORD, MASS., U.S.A.

SALES OFFICES IN ALL PRINCIPAL CITIES • Export: 13 E. 40th St., NEW YORK 16, N. Y.

Cable: 'ARLAB' • In Canada: AEROVOX CANADA LTD., HAMILTON, ONT.