BROadcas Figneering


March, 1976/75 cents

NAB Convention Preview Page 24

Film vs. Electronic News

Random Access To Film

Small Market Workshop



www.americanradiohistory.com

Just add four walls and you're on the air.

Presenting Collins' full line of broadcast equipment.

Whether you have 10 watts or 100,000 watts behind your signal, Collins has everything you need. From towers and transmission line to transmitters and test gear to turntables and tone arms... and all the other items in between.

Including the modular, flexible AutoPro program automation line. And featuring the Generation 4¹⁸⁶ series of transmitters — with the exciter that has set new standards for FM broadcasting. Plus AM transmitters that our customers say sound like FM . . . and consoles with plug-in flexibility to meet your changing format requirements.

But there's much more to Collins than just breadth of line.

Every item we make is the result of an uncompromising dedication to technical superiority. The result is a difference that some customers say they can "feel". They call this difference "the Collins presence". Your listeners will notice the difference, too.

And Collins believes in aftersale support to keep you on the air. Our Product Support Staff is at your service 24 hours a day, 365 days a year. And our Service Parts Department is just a phone call away, even on weekends and holidays at 214/690-5000. Support is not just lip service at Collins, either. Our transmitters are backed up with a full two-year warranty, twice as long as the other majors.

Our quality line of broadcast products and prompt service add up to still another benefit to Collins customers — longer operating life and lower cost of ownership. We're

ready to demonstrate this with action, too.

For those four walls, see a general contractor.

For everything else, see Collins, the *radio specialists*. Contact your local Collins salesman, or Broadcast Marketing, M.S. 406-240, Collins Radio Group, Rockwell International, Dallas, Texas 75207. Phone 214/690-5574 or -5424.



..where science gets down to business





BROADCASTENGINEERING.

The journal of the broadcast-communications industry

March, 1976 Volume 18, No. 3

- 24 NAB Docks In Muddy Waters. The annual convention will be held in Chicago from March 21 to 24. Article covers points likely to be hot topics at the convention. Ron Merrell.
- 33 Convention Exhibit Floor Plan. BE divides the exhibit area into four sections and shows booth placement as a guide to convention attendees.
- 40 NAB Product Review. A roundup of new products that will be introduced at the convention. This feature will be continued in the May convention wrapup issue.
- 48 NAB Exhibitor List. These are the manufacturers who answered our pre-show questionnaire with information on products to be featured and those on display for the first time.
- 70 Film vs. ENG: A State Of The Art Comparison. The author compares operating flexibility and costs of news film and the new ENG equipment, another high interest issue at NAB this year. Ron Whittaker.
- 82 Cutting Into Random Film Handling Costs. WBRE-TV uses a cartridge film machine to solve their film handling costs. George Andresky.
- 90 A New Approach To FM Peak Control. Our Audio Editor tests and reviews the new Thomson CSF Volumax. Includes spec comparison and on air tests. Dennis Ciapura.

About the Cover

Gary Moore and production assistant Juliet Wybrants during taping session of "To Tell The Truth" at NBC-TV studios in New York. Cover supplied courtesy of RCA.

Departments

Direct Current4
Industry News8
SBE Journal12
New Products40
Globecasting132
People In The News 141
Ad Index
Classified Ads169

EDITORIAL

Ronald N. Merrell, Director Carl Babcoke, Technical Pat Finnegan, Maintenance Howard T. Head, FCC Rules Robert A. Jones, Facilities Walter Jung, Solid State

CIRCULATION

Evelyn Rogers, Manager

Rainelle Harris, Editorial Assistant H. G. Roesler, Cartoonist Dudley Rose, Graphic Designer Joe Roizen, Video Archer Taylor, CATV Dennis Ciapura, Audio Editor

ADVERTISING

Mike Kreiter, Director Gloria Parmenter, Production Regional Advertising Sales Offices on Advertisers' Index page.





Telephone: (913) 888-4664 Broadcast Engineering is mailed free to qualified persons engaged in commercial and educational

Broadcast Engineering is published monthly by

Intertec Publishing Corp., 1014 Wyandotte Street,

Kansas City, Missouri 64105.

radio and television broadcasting. Non-qualified subscriptions in the U.S. are \$6.00 one year, \$10.00 two years, \$13.00 three years. Outside the USA add \$1.00 per year to cover postage. Single copy rate 75 cents. Back issues rate \$1.00. Adjustments necessitated by subscription termination at single copy rate.

Controlled Circulation postage paid at Indianapolis, Indiana.




Robert E. Hertel, Publisher

INTERTEC PUBLISHING CORP. Subsidiary of HOWARD W. SAMS & CO., INC.

Copyright, 1976, Intertec Publishing Corp. All Rights Reserved: Material may not be reproduced or photocopied in any form without written permission of Publisher.

Introducing MODEL 1600-7R MASTER CONTROL SWITCHING SYSTEM





FEATURES

- 24 Video inputs
- 32 Audio inputs (22 AFV, 10 unmarried)
- Exclusive GVG linear mix-wipe-fade system
- Separate video keyer in PGM bus
- PVW/BYPASS system
- Separate audio-over bus with remote ratio control
- Program and Preview remotely controlled audio line amplifiers with VU meters
- Interface for automation control
- Auto black system


OPTIONS

- Borderline generators
- Downstream keyer system
- Chroma keyer
- Audio cart start system
- Pre-roll system
- APC-2000 Series automation systems
- Auxiliary switching buses
- Audio-only tally system

THE GRASS VALLEY GROUP, INC. AA

A TEKTRONIX COMPANY

Station Plaza East GREAT NECK, NY 11021 (516) 487-1311 4419 Van Nuys Blvd, Ste 307 SHERMAN OAKS, CA 91403 (213) 990-6172 1644 Tullie Cir, NE ATLANTA, GA 30329 (404) 634-0521 P.O. Box 482 MABANK, TX 75147 (214) 887-1181 810 W Bristol Street ELKHART, IN 46514 (219) 264-0931



FROM D.C.

March, 1976/By Howard T. Head and Harold L. Kassens

NAB time has rolled around once again and as we prepare to stand shoulder-to-shoulder with all our industry colleagues, we realize they expect us to cast a spell like a modern necromancer and fore-tell the shape of the future for a year to come. With this poetic (if slightly inaccurate and ungrammatical) prelude, we cast our magic dust into the Bicentennial fire and bring you our 1976 . . .

POMPOUS PREDICTIONS

VHF TV Drop-Ins

The FCC is barely starting to recover from a deluge of thousands of pieces of paper filed by over 150 well-divided partisans, those favoring VHF TV channel drop-ins and those equally opposed. At stake is a fundamental change in the way that VHF TV channel assignments are made. Commission will reach a decision in the coming year because of high industry interest.

ENG Congestion

Electronic News Gathering (ENG) is still one of the hottest new things on the TV horizon today. Its successful use, however, depends on liberal access to the frequency bands necessary for relaying purposes. These are becoming crowded in the larger markets, and it is only a matter of time until interference complaints will multiply. This is likely to lead to the setting up of industry frequency coordinating committees for the auxiliary bands.

AM Stereo


The new industry committee to standardize a system of AM stereo broadcasting is already hard at work, and three competing systems are presently under study. In addition, a fourth system not submitted to the committee for consideration is under test and will be actively promoted. The committee is working hard to complete its report by the end of the year and may have this report in the Commission's hands by next year's NAB convention. However, don't look for early Commission action, since the Commission will have many other problems confronting it.

(Continued on page 6)

HORSEPOWER!



It brought news and entertainment to the early West. Today's broadcaster doesn't rely on Pony Express, but the "horsepower" of Sparta transmitters.



The DUAL REDUNDANCY built into Sparta medium and high power models is an added convenience not available in most others'. OUTSTANDING SPECIFICATIONS of Sparta FM transmitters show 0.4% or less distortion at all frequencies...FM noise 70 dB below 100% modulation...AM noise at least 55 dB below carrier level. All have intermodulation specifications of 0.5% or better! And for stereo stations, a clean and crisp 45 dB or better separation across the audio band!

Where TRANSMITTER "HORSEPOWER" of ANY power is needed, think FİRST of Sparta.

Satisfaction GUARANTEED!



5851 Florin-Perkins Road. Sacramento. Ca. 95828 (916) 383-5353

For More Details Circle (22) on Reply Card

DIRECT CURRENT FROM D. C.

(Continued from page 4)

Expansion of FM Broadcast Band

Various schemes will be considered for adding additional FM broad-cast channels to the present 100 channels each 200 kHz wide in the 88-108 MHz region. These will include proposals for narrowing the bandwidth from 200 to 150 kHz (already in use in Europe) and the establishment of additional FM broadcast channels in the UHF band in the general vicinity of 500 MHz.

TV "Receiver of Tomorrow"

The Commission will let a research contract for the design of a prototype TV receiver exhibiting improved performance over today's typical receiver. Primary emphasis will be on UHF performance—higher sensitivity, lower noise figure, greater linearity, improved tuning, better antenna performance, and other goodies. The Commission will also be urged to have the receiver include extras such as automatic channel identification and captioning for the deaf.

AM Clear Channels

The Commission has launched its Notice of Inquiry as to what to do with the remaining dozen Class I-A AM clear channel channels which have not yet been duplicated. The clear channel licensees would like to keep the channels intact, while new applicants would like to build secondary stations on the clear channels. Nobody is pressing this real hard so look for things to simply drift along during the coming year.


Land Mobile Grabs of TV Spectrum Space

The land mobile people are already sharing UHF TV Channels 14-20 in some markets, and a few years ago were handed the top 14 UHF channels outright. They will continue to press their demands for access to more TV broadcast spectrum space. They have already asked for outright allocation of over 200 MHz in the middle of the existing UHF TV band, increased sharing or outright reallocation of the lower portion of the UHF band, and even sharing of the VHF TV band or outright reallocation of VHF TV spectrum space for TV and land mobile.

Circular Polarization for TV Broadcasting

The Commission has pending a petition to authorize circular polarization for TV transmissions on a regular basis. Some work has been done at VHF in Chicago, and further work is under way on UHF at Modesto, California. The UHF work will be reported to the Commission within the coming year, but the findings will be inconclusive. Further work is needed at VHF and some additional testing has been undertaken at Chicago. However, it isn't likely that definitive results of the further VHF testing will be completed in the months to come. Look for little forward action on this topic between now and this time next year.

WE OFFER MORE



WITH THE AMERICAN DATA 558

- (*) WHICH FEATURES THE ONLY FOUR CHANNEL MIX EFFECTS SYSTEM AVAILABLE — ALLOWING ALL OF THESE PRODUCTION FUNCTIONS TO BE DONE ON A SINGLE MIX EFFECTS AMPLIFIER.
- A-B Mix or Dissolve
- A-B Wipe
- A-B Wipe with Border

- Wipe to a Preset Wipe
- - Mix or Dissolve to a Key
 - Wipe to a Key or Wipe Key
 - Mix to a Bordered Key

- A-B Mix Behind a Chroma Key
- A-B Wipe Behind a Chroma Key
- A-B Wipe with Borders Behind a Chroma Key
- A-B Wipe through 100% Border Mix-Wipe or Bordered Wipe to a Preset Wipe Behind a Chroma Key
- Mix or Dissolve to a Preset Wipe
 Mix or Dissolve to a Luminance Key Over a Chroma Key
 - Wipe to a Luminance Key over a Chroma Key
 - Bordered Wipe to a Preset Wipe Mix, Wipe or Dissolve to an Electronic Spotlight Behind a Chroma Key
 - Mix or Wipe to a Quad Split, with or without Borders, Behind a Chroma Key
 - Luminance Key over a Quad Split behind a Chroma Key
 - And More —

SEE FOR YOURSELF NAB BOOTH 403

AND JUST THINK — THE 558 HAS TWO!



AMERICAN DATA DIVISION

AIRPAX ELECTRONICS, INC.

401 WYNN DRIVE • P. O. BOX 5228 • HUNTSVILLE, ALABAMA 35805 USA • TELEPHONE 205 837-5180 • TWX 810 726-2125

For More Details Circle (23) on Reply Card

INDUSTRY NEWS

Canadian Broadcasters Set May Convention Dates

The Western Association of Broadcast Engineers has announced their 1976 dates and location for the 26th Annual WABE Conference.

The 1976 Western Association of Broadcast Engineers Conference will be held May 3rd, 4th and 5th at the Hotel Bessborough, Saskatoon, Saskatchewan. This year's conference will open May 3rd with two three-hour seminars on digital electronics. The seminar will be in conjunction with the Southern Alberta Institute of Technology, Calgary. Senior Instructor, Wayne Gedlaman will teach the course and there will be a forty-page handout which will cover all phases of the

The Western Association of seminar and will be of use for roadcast Engineers has an future reference.

The seminar and handouts are open to all registered delegates and there is no extra charge.

May 4th and 5th will be regular WABE Conference days with two full days of technical papers presented by experts in their field from Canada, U.S.A. and Europe. The exhibitor's rooms will occupy at least three floors of the Hotel and will be open from the evening of May 3rd through May 4th and 5th.

Registration fees before April 15th are \$25.00 per person, \$30.00 per person after April 15th. There is no fee for exhibiting except the normal hotel room costs. All at-

tending the Conference must register.

For further information in regard to exhibiting, accommodation or presenting a paper, please contact General Chairman, Alex White, W.A.B.E., Box 412, Regina, Saskatchewan, Canada S4P 3A2.

ITVA Will Meet In Anaheim


"Effective Programming—The Next Step" will be the theme of the 8th Annual International Conference of the International Industrial Television Association (ITVA), March 27-30, 1976, Anaheim, California.

At the conference, industrial and instructional production and management people will hear from many of the leading authorities and innovaters in visual communications today. "Video communications

(Continued on page 10)

MASTER GART

For your AM Station TODAY . . . For your AM Stereo Station TOMORROW!



In stereo broadcasting, phasing problems make tape cartridge quality a factor of prime importance. Upgrade your AM sound and be stereo ready with Master Cart from Fidelipac. Master Cart assures you of the superior on-air sound, negligible high frequency cancellation and clean, crisp, undistorted reproduction conventional tape cartridges can't deliver. In fact, Master Cart is guaranteed to perform to within 60° of 0 phase at 12,500 Hz, repeatable with each use and with each Master Cart you purchase.

AM or Fm... Top 40 or Classical... Mono, Stereo or Encoded Quad, Master Cart is your sound buy in broadcast tape cartridges today and in the future.

For technical information contact your Fidelipac Distributor or




FIDELPAC®
109 Gaither Drive • Mt. Laurel, NJ 08057

(609) 235-3511

See us at Booth #405. NAB

For More Details Circle (24) on Reply Card



VIDEOMAX NOW REFURBISHES MORE KINDS OF QUAD HEADS THAN ANY OTHER COMPANY IN THE WORLD.

You now have a single source for refurbishing RCA High Band and Low Band video heads and the Ampex Mark III, Mark X and Mark XV heads. No other refurbisher works harder at satisfying a broader range of customer services than Videomax.

Visit us at booth 606 during the N.A.B. convention.



Videomax Corporation, An Orrox Company 3303 Scott Boulevard, Santa Clara, CA 95050 Phone: (408) 988-2000 Telex: 910-338-0554

SALES & SERVICE - New York: (212)947-8031, Los Angeles: (213)980-7927, Washington: (301)384-41733

For More Details Circle (25) on Reply Card

News (Continued from page 8)

passed the 'survival' stage some time ago," said Herb Wolff, conference chairperson. "Now we must focus on effective **programming**—in terms of both instructional impact and dollar cost."

The ITVA Conference dates coincide with those of the national convention of the Association for Educational Communications and Technology (AECT). Attendees of the ITVA Conference will have an opportunity to attend sessions of AECT as well as view more than 500 audio-visual exhibits at the Anaheim Convention Center.

Keynoter for the ITVA Conference will be Dr. Robert F. Mager of Mager Associates, Inc., well-known author and consultant on the subject of setting and achieving instructional objectives. Mager will examine effective use of video in the craft of instruction.

The influence of television on human behavior will be discussed by George Comstock, head of a Rand Corporation research team which recently completed an extensive study of the phenomenon. Dr. Richard Lamberski, Senior Production Specialist at Pennsylvania State University, will show attendees how to evaluate audience response to visual stimuli. Other speakers will demonstrate the impact of computerized animation and three-dimensional television on non-broadcast programming; the use of satellite transmissions for video distribution; recent developments in electronic news gathering (ENG) techniques and systems; and effective use of low cost sets for television.

Winners of the 8th Annual ITVA Videotape Competition will be announced at a special Awards Banquet March 28th; regional and international winners will be available for private viewing throughout the Conference.

The highly popular Breakfast Workshops featuring discussions of production and programming problems; job descriptions and salary levels, etc. will again be offered.

Further information on the ITVA Conference can be obtained by contacting Herb Wolff, Conference Chairperson, New England Video Services, 501 Boyston Street, Boston, Ma. 02117.

Three Stations Share New FM Antenna

Three FM radio stations in Miami, Fla., will begin broadcasting early this year from a new multiple-channel broadcast antenna custom-designed by RCA Broadcast Systems.

The Miami installation marks the first time three FM broadcasters have used a common antenna designed with ring radiators for pole or tower-leg mounting, according to R. L. Rocamora, Manager, Antenna Engineering and Product Management, for the RCA activity.

The eight-bay BFL unit will radiate circularly polarized signals for stations WINZ-FM, WYOR-FM and WBUS-FM.


Rocamora noted that the new design provides a multiple-station antenna at a lower cost than for an equivalent panel-type unit. Low wind-loading of the new antenna also permits mounting on a less expensive tower, he added.



For More Details Circle (26) on Reply Card

A second SECRET


has been uncovered!



We tried to keep the door slammed on a second new x-pandable system under development. But the word is out.

Would you believe a fast, flexible,

accurate time code ENG system for under \$20K? And the 34X is x-pandable, too!





As you know, we were going to surprise you in March with two new systems. Now you know.

Nobody can keep a secret in this business.

3303 Scott Boulevard, Santa Clara, CA 95050 Phone: (408)988-2000 Telex: 910-338-0554

For More Details Circle (27) on Reply Card



See You At The Convention!

The Society of Broadcast Engineers will meet Sunday, March 21, at the Hyatt Regency Chicago, 151 Wacker Drive. At 12:30, the Board of Directors will meet in the Atlanta Room. The Annual Membership Meeting will be held in Regency Room A from 3:00 until 5:00. Finally, from 5:00 to 7:00 that evening, there will be a reception in the Toronto and Hong Kong Rooms.

Billing Schedule for SBE Dues

The December issue of **The Signal** stated that all members whose numbers are below 3299 will be billed during March, 1975, and

members holding numbers higher than 3298 will not receive notices until 1976. Please don't think you're home free if you have a membership number below 3299... the notice should have read March, 1976, in the first instance and 1977 in the second.

Tid Bits

Vince Flanders, assistant secretary of SBE, reports that he's still having trouble mailing newsletters. Apparently, many addresses are incorrect, since the post office returns nearly 130 copies after each mailing. If you're one of those still not receiving a **Signal**, please notify him as soon as possible.

Josh Socolof [see address below] is looking for more people to join him in the formation of a Chapter in the Oklahoma City area. If you are interested in what an SBE Chapter can do for you, please call him at (405) 525-5595.


Chapter 2: Northeastern Penn.

Chapter 2 met Monday evening, February 2, to hear Ed Karl, engineering representative for Gates-Harris Intertype, speak on their recently announced one-kilowatt, all solid-state AM transmitter. Karl, a National Director for SBE and a member of the Certification Committee, also held a question/answer session on the Certification proposal, of which Chapter 2 had recently voted total endorsement.

Chapter 9: Phoenix, Arizona


January's program, on the FCC's new Rules regarding the two-tone EBS system, featured representatives from TFT. TFT, who worked with the FCC in defining the new two-tone equipment specifications prior to last August's announcement, reviewed the system with members and reported on the new

(Continued on page 14)



Beaucart is is here.

The hottest, coolest cart machine you can use!




The long wait for a superior broadcast audio cart machine is over. We've built all the most wanted features into our complete new line of mono and stereo A, B, and C-size cartridge tape recorders and reproducers. Compact size, reduced flutter and wow, and lowest operating temperatures are just some of the many advantages. And Beaucart meets the new NAB standards, too.

What makes this hot new machine the coolest cart machine you can buy? Beaucart was designed by the manufacturer of the quality BEAU motor and incorporates our low profile, patented pancake hysteresis synchronous direct drive motor. You've never seen anything like it. And you've never seen a cartridge machine like Beaucart either.

For complete information and pricing, write or call today. And look for us at Booth No. 712 at the Chicago NAB Convention.

UMCBEAUCART DIVISION UMC ELECTRONICS CO.

460 Sackett Point Rd. North Haven. CT 06473 (203) 288-7731



Model VL-1 Video Line Isolator

With VACc's new video line isolator, you can stop worrying about using differential amplifiers and humbucking coils to clean up that 60Hz hum in your video signal. VACc's self-contained electro-optical isolator passes 1Hz to 8MHz yet rejects hum levels up to 70 Vrm's at 60Hz. Now you can route video signals from building to building where your equipment is connected to different a-c line sources—and forget about differential voltage and interference.

\$250 list

2 week delivery

See this and other VACc products at NAB Booth 142



VIDEO AIDS Corp. of Colo.

112 West 4th St. Loveland, Colorado 80537 (303 667-3301)

For More Details Circle (8) on Reply Card

SBE (Continued from page 12)

In response to requests for a complete Chapter listing, we include the following:

CHAPTER 1—BINGHAMTON, NEW YORK. Bill Sitzman, Jr., Chairman, Independent Broadcast Consultants, Inc., Box R-181, Freeville, New York 13068, (607) 273-2970.

CHAPTER 2—NORTHEASTERN PENNSYLVANIA. John Kowalchik, Chairman, RCA Solid State Division, Crestwood Road, Mountaintop, Pennsylvania 18707, (717) 474-6761, ext. 635.

CHAPTER 9—PHOENIX, ARIZONA. Leon Anglin, Chairman, SBE, P.O. Box 615, Phoenix, Arizona 85001, (602) 285-7333.

CHAPTER 11—BOSTON, MASSACHUSETTS. Bob Molloy, Chairman, 66 Bellevue Street, Manchester, New Hampshire 03103, (603) 669-1250.

CHAPTER 15—NEW YORK, NEW YORK. John Lyons, Chairman, WWRL, 41-30 58th Street, Woodside, New York 11377, (212) 335-1600.

CHAPTER 16—SEATTLE, WASHINGTON. Bob Ingalls, Chairman, 5441-187th Avenue, N.E., Redmond, Washington 98052, (206) 543-7774.

CHAPTER 17—MINNEAPOLIS/ST. PAUL. Lance Raygor, Chairman, Route 1, Box 337, Chisago City, Minnesota 55013, (612) 373-4807.

CHAPTER 20—PITTSBURGH, PENNSYLVANIA. Jim Hurley, Chairman, WTAE-TV, 400 Ardmore Blvd., Pittsburgh, Pennsylvania 15230, (412) 242-4300.

CHAPTER 21—SPOKANE, WASHINGTON. T. O. Jorgenson, Chairman, Technical Director, KXLY, W. 500 Boone Avenue, Spokane, Washington 99201, (509) 328-9084.

CHAPTER 22—CENTRAL NEW YORK. Gary Hartman, Chairman, WSYR, 1030 James Street, Syracuse, New York 13203, (315) 474-3911.

CHAPTER 25—INDIANAPOLIS, INDIANA. Donald Morgan, Chairman, WTTV, 3490 S. Bluff Road, Indianapolis, Indiana 46217, (317) 787-2211.

CHAPTER 26—CHICAGO, ILLINOIS. Bob Churchill, Chairman, SBE, 121 W. Wacker Drive, Chicago, Illinois 60601, (312) 729-5215.

CHAPTER 28—MILWAUKEE, WISCONSIN. Dave Dezurick, Chairman, WRJN, 4201 Victory Avenue, Racine, Wisconsin 53405, (414) 634-3311.

CHAPTER 32—TUCSON, ARIZONA. H. J. "Bart" Paine, Chairman, Chief Television Engineer, University of Arizona, College of Medicine, Tucson, Arizona 85724, (602) 882-6644.

CHAPTER 33—CINCINNATI, OHIO. Louis A. Williams, Chairman, 2092 Arrowwood Place, Cincinnati, Ohio 45231, (513) 851-4964.

CHAPTER 34—ALBUQUERQUE, NEW MEXICO. Fern A. Bibeau, Chairman, KOB, P.O. Box 1351, Albuquerque, New Mexico 87103, (505) 243-4411.

(Continued on page 21)

BROADCAST ENGINEERING



SS 3159

The SS3159 stereo disc. reproducer provides complete facilities for professional stereo reproduction of disc. recordings. It is completely self-contained with SP10D turntable, tone arm, plug-in pickup cartridge, equalized preamplifiers, audio cue switching, power supply and pedestal assembly.

The turntable offers the highest quality, lowest noise operation available. It adds virtually nothing to the original sound as recorded on the disc. And with the advent of quadrophonic discs, it's imperative that vertical as well as horizontal "rumble" be reduced to a minimum.



FOR FURTHER INFORMATION CONTACT:

McCURDY RADIO INDUSTRIES INCORPORATED

1051 CLINTON STREET, BUFFALO, N.Y. 14206 (716) 854-6700, TWX 610-492-3219

EASTERN SALES OFFICE: P.O. BOX 86 SADDLE RIVER N.J., 07458, (201) 327-0750 TWX 610-492-3219

IN CANADA: McCURDY RADIO INDUSTRIES LIMITED


108 CARNFORTH ROAD, TORONTO, ONTARIO M4A 2L4 (416) 751-6262 TELEX: 06-963533

SS 7800


The SS7800 Series of modular audio consoles provides complete professional facilities for mixing and shaping today's complex audio material.

In addition to complete program mixing, monitoring and control, SS7800 Series consoles provide PA feeds and comprehensive Solo/Cue, Echo-Send/Receive, Foldback and talkback system facilities. A full range of options is also available including Equalizers, Compressors, Program Assign with Pan, and Remote Controls.





For More Details Circle (6) on Reply Card



On March 21, Sony will reveal a major commitment to the broadcast industry.

That date is the opening of the 1976 National Association of Broadcasters convention in Chicago.

At the show, Sony will exhibit eight new video products specially designed for the broadcast industry. They represent the largest investment in broadcast equipment ever made by Sony.

But the new products are only part of the important things we will introduce at N.A.B.

A new organization. Formed specifically by Sony to serve the broadcast industry and headed by Dave MacDonald, our team of broadcast specialists is knowledgeable, experienced and eager to apply our technological leadership to your problems.

A new service policy. Sony recognizes that the broadcast industry cannot afford "downtime." At the show, we'll explain how we plan to service our equipment quickly and efficiently.

A new name. Sony Broadcast will begin to appear in many places. It's there to assure you that we're dedicated to the product and service standards necessary for the broadcast industry.


What this all adds up to, of course, is a major commitment on the part of Sony to the broadcast industry.

Sony Broadcast

A division of Sony Corporation of America. 9 West 57th Street, New York, New York 10019

For More Details Circle (76) on Reply Card For Demonstration Only Circle (77) on Reply Card

Studio Lighting. We supply everything but the electricity.



STRAND CENTURY presents four complete lighting and control system packages for television studios. Our studio package literature provides you with a wealth of information.

It's the easy way to light your studios with great STRAND CENTURY products at a very affordable price. Send for our data: Strand Century Inc., 20 Bushes Lane, Elmwood Park, NJ 07407. 5432 West 102nd St., Los Angeles, Calif. 90045.



Renewal Legislation

NAB Still Shoots for

The Board of Directors of the National Association of Broadcasters has reaffirmed its objective to obtain license renewal legislation that provides stability and a license term of more than three years.

The Radio Board and the Television Board adopted this resolution:

"The National Association of Broadcasters reaffirms its commitment to licensee stability and a lengthened license term for all broadcasters. However, should the Congress decide first to direct its attention to renewal relief for the radio industry, NAB would support such appropriate legislation."

The Board expressed its continuing concern over the advertising of personal products and adopted a resolution directing the Television Code Board to keep the matter under close review. It said such advertising should be handled in good taste and must be limited to specified hours—from 9 a.m. to 4 p.m. and after 10 p.m. on weekdays and after 10 p.m. on weekends, local time, and from 8 a.m. to 3 p.m. and after 9 on weekdays and after 9 a.m. on weekends in the central time zone.

The Board endorsed broadened guidelines for children's advertising that incorporate under one umbrella various Code Authority rules on the subject. Included is a stipulation that feature films not suitable for family viewing can not be advertised in or adjacent to programs designed primarily for children under 12.


In another action, the Board chose Robert D. Gordon of WCPO-TV, Cincinnati, O., as its chairman to succeed Walter E. Bartlett of AVCO Broadcasting Co., Cincinnati, who is scheduled to resign from the Board on March 1. Kathryn F. Broman, Springfield (Mass.) Television, was chosen to replace Mr. Gordon as vice chairman on that date.

Bartlett's resignation became necessary because of the purchase of AVCO's Cincinnati station, WLWT, by Multimedia Broadcasting Co., Greenville, S.C. NAB Board Chairman Wilson Wearn is president of Multimedia and NAB By-Laws provide that only one representative from the same station or group may serve on the Board. FCC approved WLWT's acquisition as of March 1.

The Board revised its method of computing the dues of NAB's TV members.

It dropped the old hourly program rate schedule in favor of a formula based on market size and the nature of operations. A network affiliated VHF station in the number one market would pay the highest dues while an independent UHF in the smallest market would pay the lowest. An escalator clause tied to industry revenue increases over a three-year period would be used to adjust the dues annually.

smart switcher



CDL has just raised the standard for video production switchers. Again.

The CD-480 is the first totally new full scale production switcher from CDL in 7 years. It offers every wanted feature, from superb Chroma Keying to Rotating Wipes with Colored Borders and Soft Edges.

We applied unique technology to create an operator's "dream". A single CD-480 Effects Amplifier can perform production sequences that are not possible even on a conventional triple M/E switcher.

The CD-480 is not just a new switcher, but a completely modular production system.

Call us!

CD-480 gives you the competitive advantage!



CENTRAL DYNAMICS LTD

Canada: 147 Hymus Blvd., Montreal, Que., H9R-1G1 ■ 514-697-0811 U.S.A. 230 Livingston Street, Northvale, N.J. 07647 ■ 201-767-1300 Chicago: 312-991-4720 ■ Los Angeles: 213-789-0574



...A year of pioneers and pioneering

For more than a decade and a half, Moseley Associates, Inc., has pioneered many advances in aural studio-transmitter link (STL) and transmitter remote control equipment. Some of these innovations are —

MOSELEY - PIONEERS OF:

All Solid-State Aural STL and Remote Pickup Systems
Dual and Composite STL's for FM Stereo
AM and FM Wireless Remote Control with Subaudible Metering
Computer-Assisted Transmitter Remote Control

First STL Capable of Transmitting Quad Stereo — and Used in Quad Field Tests Digital Transmitter Remote Control and Logging

AND FOR '76-MOSELEY PRESENTS

First 950 MHz STL Transmitter with ON-FREQUENCY ALL SOLID-STATE RF POWER AMPLIFIER Full COLOR CRT Display of Transmitter Remote Telemetry Information

See these and other Moseley innovations in Booth 505 during 1976 NAB Convention...or contact us directly for full details of a Moseley innovation to meet your requirement.



111 CASTILIAN DRIVE GOLETA, CALIFORNIA 93017 TELEPHONE (805) 968-9621 TELEX 658448 CABLE: MOSELEY

SBE

(Continued from page 14)

equipment specifications that will go into effect this April.

Chapter 11: Boston, Mass.

Members of Chapter 11 met January 27 at the American Telephone facility in Boston for an informative tour of A. T. & T.'s radio and TV division. A business meeting was held in one of the conference rooms that evening.

Chapter 16: Seattle, Wash.

On January 14, Chapter 16 met to hear Barry Lloyd from RCA give a report on circular polarization of TV antennas. The presentation included slides which were taken at the WLS-TV site in Chicago.

Chapter 20: Pittsburgh, Penn.

Chapter 20 welcomed Mr. Bill Bannow, director of commercial marketing for the Duquesne Light Company, at their regular noon meeting on January 15. Mr. Bannow included a twenty-minute film on "The Critical Choices Ahead" in his speech on the uses and production of energy. A question-and-answer period followed.

Chapter 26: Chicago, Illinois

The Chicago Chapter invited local SBE members Fred Rodey and Ken Steininger to present the program on January 20. Mr. Rodey, manager of TV technical operations, discussed video signal standards. These represent a tightening of the allowable parameters within the FCC specifications so that there will be less chance of a station receiving a citation for violating the technical standards. The inherent problems in this procedure were discussed, and copies of the specifications as published by NBC were passed out to the group. (NOTE: NBC has published the tightened specs for its own internal use and, in the interest of maintaining better

(Continued on page 102)


SBE Chapters

CHAPTER 35—LOUISVILLE, KENTUCKY. Robert J. Kline, Chairman, WKLE(TV), 600 Cooper Drive, Lexington, Kentucky 40502, (606) 233-0666.

CHAPTER 36—SAN DIEGO, CALIFORNIA. Bill Montgomery, Secretary/Treasurer, SBE, 6841 Convoy Court, San Diego, California 92111, (714) 556-8080.

CHAPTER 37—WASHINGTON, D.C./NORTHERN VIRGINIA. Charles F. Riley, Chairman, Tele-Color Productions, 708 N. West Street, Alexandria, Virginia 22314, (703) 683-3203.

(List continues on page 102)



For More Details Circle (11) on Reply Card

40 MARBLEDALE ROAD/TUCKAHOE, NEW YORK 10707/(914) SW 3-5000/TWX 710-562-0110/TELEX 1-37449

ELECTRONICS COMPANY, INC.

ITS DECADE

...and another giant step forward in camera technology from the makers of the most wanted, most used and most imitated cameras in the world.

most complete family of cameras available today. Cameras designed to meet every requirement and budget. *Plus* an expanded national sales and service organization ready to serve you.

The LDK 25. Unquestionably, the state of the art multicore studio and field camera system on the market.

Incomparable Philips stability through its exclusive combination of advanced modular circuitry, beam-splitting prism and famous rugged, low profile head casting. Uses 1" Anti-Comet-Tail Plumbicon tubes that allow highlights of up to 32 times normal peak white level without

blooming or streaking...and still providing famous
Philips color rendition and resolution.

Has unique CLUE (Color
Line Up Equipment) at
viewfinder and CCU
for very rapid and
highly accurate color
balance under any lighting condition using only
a monochrome monitor

or the camera viewfinder itself. Plus electronic color temperature control, auto white balance, highly flexible auto iris and contrast compression to enhance detail in blacks. The LDK 25...the camera for new studios, replacement or adding to existing equipment.

15,

Since 1965, when color television leaped into practicality with the introduction of the Plumbicon* tube and the Norelco PC-60 to U.S. broadcasters, the succession of Philips design innovations during the past 10 years has been industry-boggling.

The dramatic improvement of home screen pictures and the equally dramatic simplification and reliability of color production techniques brought on by such exclusive Philips advancements as its 3-Plumbicon tube design and beam-splitter prism, had all 3 networks and most groups and independents using PC-60's and 70's. In a few years, over 1,000 cameras were in use. And over the past 10 years, as one important technical advancement followed another, Philips cameras have become the accepted leader in the U.S. and throughout the world.

Building on these major breakthroughs, Philips now has taken the industry into DECADE TWO—with the LDK and LDH series—the finest, most advanced and

The LDK 5. A uniquely flexible, digitally controlled Triax field and studio camera system with many features to minimize installation and operating costs for both studio and field operation...plus the advantages of Triax to make it ideal for remote situations. Has a built-in memory system that maintains settings for up to a week and automatic cable compensation that eliminates timing and power supply problems even beyond a mile. And much, much more.





The LDK 11. At last...a camera totally designed for full broadcast quality ENG and production applications. All without compromise of quality or operational features. This remarkable battery or AC powered 15 lb. camera has full production control either remotely or at the backpack and all the key Philips engineering features. Famed 3 Plumbicon tube picture with bias light, beam-split prism, linear matrix for superb colorimetry, H and V contours, auto iris, auto white balance, genlock sync generator, switchable gain and gamma, built-in color bars. Also, remote VTR and zoom controls and 2 microphone channels. All this and more provide the utmost flexibility and economy for ENG, remote and studio production... and, we repeat, without compromise.

able production camera. Actually an LDK 5 in a portable package. Use it inside, outside, wherever.

Operates in a self con-

The LDK 15. The ultimate port-

tained mode or interfaces with either the LDK 5 or the LDK 25 CCU in system configurations with absolutely no compromise in performance. Triax, wireless and standard cable modes of operation.

The LDH 20S. The recognized leader in 3-tube economy cameras. Now with increased sensitivity and a greater selection of performance-oriented field interchangeable zoom lenses. The Philips patented prism beam-split optics and contours-out-of-green enhancement are included. Plus a new CLUE



For more information or to arrange a demonstration, call your local Philips representative or contact:
Broadcast Products, Philips Audio Video Systems Corp., 91 McKee Drive, Mahwah, N.J. 07430. (201) 529-3800.



For More Details Circle (12) on Reply Card

The attendance at this year's NAB convention will probably be the largest ever. Exhibitors won't like the union's way of doing business, but the aisles will be crowded.



Docks In Muddy Waters For '76 Convention

It's back to the Windy City, and the portents are for a stormy convention. The question is whether or not the Association will broaden its battle lines.



BY RON MERRELL

You Can't Please 'em All

Some years ago a group of prominent engineers decided that it might be beneficial for their kind if a professional society could be formed that would focus on the needs of the professional broadcast engineer. Through their efforts, they formed what became known as the Society of Broadcast Engineers (SBE). And it has grown into just about what the charter members wanted.

Who did they pull away from? The IEEE, NAEB, or NAB? While it might be true that they pulled away from some association, it is more true to say that no association

has or is paying more attention to their everyday problems than the SBE.

But the hills and valleys of broadcasting have many special interest groups, and more crop up all the time. It follows that no one association could blanket the countryside and give equal time.

What about the FM segment. Once the weak sisters of radio, they've come into their own. So much so that today they represent the greatest growth area in overthe-air broadcasting. So they started the National Association of FM Broadcasters (NAFMB). Annually, they met immediately before, during, or after the NAB convention....and, in the same city. In the past year, that organization has become totally independent. They recently changed their name

to the National Radio Broadcasters Association (NRBA).

Now this caused more than a ripple among the NAB ranks. They got the spotlight when they planned a national convention at great distance in time and space from the NAB. Attendance was good and exhibitors cooperated.

But if the people who set up the NAEB, the NRBA, the SBE and other special interest groups were pulling away, wouldn't this weaken the NAB? And if the NAB were but a mere shadow of its former self, wouldn't that cause the industry to lose its bargaining and lobbying strength? The answers might seem to be, Yes, Yes!

Fortunately, that's not really what we're seeing. If these special interest groups threw out their memberships to NAB, it would be a



problem. But if you notice what's been happening, you see that the NAEB, SBE, and NRBA people still have memberships in the NAB, accept the Code, and attend conventions. And speaking of conventions, they attend in greater numbers now than they ever did before! What has happened is that these associations have gotten more people into the act, and as a result, they start attending one convention, then two. Ironic, isn't it.

Now the worst thing that could happen would be for the NAB to deny that special interest associations are needed and that their existence threatens the major umbrella association, the NAB. That, in itself, would open a chasm that might never be closed, with the greatest crunch falling on the NAB itself.

More Services For Radio Members

In late January, president Vincent T. Wasilewski outlined to the Radio Board of Directors of the National Association of Broadcasters a multifaceted program designed to provide additional services for its radio members.

He told the Board the new measures are part of an ongoing program that already has resulted in NAB "doing more for radio than any other organization by a margin of about 1,000 per cent."

Wasilewski announced the promotion of Charles T. Jones, Jr., NAB vice president and director of its Radio Information Office, to the newly-created post of vice president for radio affairs. He said Jones will act as NAB's radio ombudsman—the staffer who will serve as the

contact point for all radio members and who will devote full time and attention to all radio issues.

The president said the Radio Information Office also will be expanded and the Legal and Government Relations Departments will each designate a staff member as, respectively, radio legal affairs and radio government relations specialists. Valerie Waddelove was promoted to administrative assistant for RIO.

Wasilewski said NAB cooperation with the Radio Advertising Bureau during last year's Fall meetings proved very successful and plans now are well underway for broader participation by RAB and the Television Bureau of Advertising at the forthcoming NAB Convention in Chicago.

He also reported that feedback



NAB president Vincent Wasilewski...."doing more for radio than any other organization by a margin of about 1,000 percent."

from radio members shows they are "extremely pleased" with RADIO-active, NAB's new monthly publication for radio members.

Measures also are underway, he said, to improve communications and "work more closely" with state broadcaster associations. Among other things, state presidents and executive directors will be invited to fall meetings and conventions as NAB guests.

All-Radio Legislation

At the meeting, the Radio Board adopted a resolution reaffirming its support on legislation requiring that all radio sets costing more than \$15 be equipped to receive both AM and FM signals.

The resolution said that "the Radio Board of Directors reaffirms its endorsement of all-channel radio legislation and urges that strong efforts continue to effect the passage of such legislation. In addition, the Board recognizes and commends the free-enterprise programs in response to the urging of NAB made by such companies as the Chrysler Corp., Hertz, and others in providing all-channel receivers."

The Radio Board also urged NAB's Engineering Department to look into the possibility of establishing standards for radio receivers and urged the Federal Communications Commission to broaden its inquiry into television receivers to include radio sets as well.

In other actions, the Radio Board:

- Authorized establishment of a Radio Hall of Fame honoring individuals who have made outstanding contributions to the sound media. A four-member committee was appointed to carry the project forward. Members are Robert Hilker, Suburban Radio Group, Belmont, N.C.; Donald Jones, PSB Radio Group, Fond du Lac, Wis.; Len Hensel, WSM, Nashville, Tenn., and Sherril Taylor, CBS Radio, New York, N.Y.
- Authorized a \$30,000 study of the Future of Radio under the supervision of a committee to be named later.
- Returned to the Radio Code Board for further study a Code Board recommendation for a ban on advertising of fireworks for sale to the public.
- Heard a report by Bill Sims, Wycon Corp., Laramie, Wyo., chairman of NAB's new cable radio committee, on degradation and elimination of radio signals on cable systems, possible non-duplication protection, and the need for BMI and ASCAP fees on programs cable originates.
- Heard Taylor emphasize the importance of radio members supporting NAB's drive to prevent cable siphoning of free TV's programs.

The Joint Radio-Television Board, at an earlier meeting, adopted two new categories for associate members—attorneys and consulting engineers. The dues structure provided calls for annual dues of \$250 for firms with from one to five persons; \$500 for those with six to 10, and \$750 for those with more than 10.

The Board also provided graduated increases for associate member equipment manufacturers with gross receipts of more than \$1 million annually. Those grossing between one and five million would pay \$1,250 a year; those grossing between five and 10 million would pay \$1,500, and those grossing over \$10 million would pay \$2,000.

Headliners

Richard E. Wiley, chairman of the Federal Communications Commission, and noted commentator Paul Harvey, will address the annual convention.

Wiley will address the joint radio-television luncheon Tuesday, March 23, and Harvey will speak at the radio luncheon on Monday, March 22.

Pay TV Panel

The NAB has announced the participants for the panel discussion "Pay TV: Will it Supplement or Supplant?" during a television session at its annual convention.

The panel at the Monday (March 22) afternoon session will be moderated by CBS newsman Mike Wallace.

Panelists will be Everett H. Erlick, senior vice president and general counsel, ABC, New York; William Carlisle, NAB vice president for government relations, and former chairman of the Federal Communications Commission Frederick W. Ford. Ford is with the Washington, D.C. law firm of Pittman, Lovett, Ford and Hennessey. A fourth panelist will be announced later.

Congress, Too


A member of the Senate Commerce Committee and two members of the House Committee on Interstate and Foreign Commerce, also will participate in the convention.

Speaking at Monday's (March

Two Of Our Cameras Are Covering The News.



Hitachi FP3030



Hitachi SK-70

The Third One Is News.

You're invited to the unveiling of our new Hitachi SK-80 portable ENG color camera at the NAB Show. The SK-80 is a totally self-contained camera whose exceptional design and features are sure to be appreciated by broadcasters.

While you're at our booth, also check out our existing SK-70 and FP3030 portable color cameras. The SK-70 is a modular system which can be converted easily from studio to field use, with superior performance in either mode. And the FP3030 is a light weight and low cost completely self-contained camera which is ideal for mobile video capability in ENG, as well as a variety of educational and industrial applications.




Hitachi SK-80

Come get the scoop on ENG cameras at the Hitachi booth.



Exec. Offices: 58-25 Brooklyn-Queens Expressway, Woodside, New York 11377 Offices in Chicago, Los Angeles, Dallas, Atlanta. Toronto

CANON ANNOUNCES DIOL



The new Canon 18x series for major broadcast cameras. With the best relative aperture, superior wide angle and shorter M.O.D. Choice of manual or servo focus and zoom. Built-in servo/manual operated 1.5x and 2x extenders. And interchangeable, plug-in servo modules, for easier service. All at a competitive price.

Judge for yourself. Compare the specifications below. Factor in Canon's nationwide service and comprehensive loaner program. And see a demonstration.

For more information, please write or call:

Canon U.S.A. Inc. Head Office. 10 Nevada Drive. Lake Success, N.Y. 11040 (516) 488-6700 ◆ 140 Industrial Drive. Elmhurst. III 60126 (312) 833-3070 ◆ 123 Paularino Avenue East, Costa Mesa. Ca 92626 (714) 979-6000

Canon Optics & Business Machines, Canada, Ltd., 3245 American Drive, Mississauga, Ontario L4V 1B8. Can. Canon Amsterdam N.V., Industrial Products Division De Boelelaan 8, Amsterdam, Netherlands

© 1975 Canon U.S.A. Inc.

For More Details Circle (134) on Reply Card



NAB '76 should see the largest number of exhibitors ever scheduled for the annual convention. Hot items will be the EBS equipment and ENG key and support equipment.

22) afternoon television session will be Senator Vance Hartke (D-Ind.), who also is on the Communications Subcommittee.

Scheduled for Tuesday morning's radio session is Torbert H. Macdonald (D-Mass.), chairman of the House Communications Subcommittee. Broadcasters attending that morning's television session will hear Lionel Van Deerlin (D-Calif.).

The Union of '76

The convention site is Chicago, and what's going to happen to exhibitors there may well go down in history as the great American ripoff. I mean, can you believe that the exhibitor will have to pay for a carpenter to uncrate his exhibit equipment? That he must have an electrician to hook up all connections (even though he won't have the

foggiest notion of what he's doing)? Or that it may take someone from the upholsterer's union and the carpenter's union to get a curtain stapled back or a sign put up?

Now while the NAB is running, Chicago will be flooded by attendees of the Chicago Flower and Garden Show. And their numbers will make the NAB look mighty small. Chances are mighty small that the manufacturers will stand for a repeat of NAB-Chicago!

Despite the predictions of even more innovative and exciting new products coming from the horn of plenty at NAB convention time, the star in the spotlight will be the latest version of two-tone Emergency Broadcast System (EBS) equipment.

As everyone admits, there has been some confusion about who must have what. More importantly, when. Well, the deadline stands at April 15. If it's fair game to second-guess the FCC, you'll have to admit that it's hard to imagine the entire industry having bought and installed the new equipment in time to meet the deadline. With this in mind, the FCC may allow—in some districts—an extra week or so.

Admittedly, second-guessing the FCC is risky, at best. Inspection interpretations are not always consistent. They never have been and they probably never will be. So while some RI's may turn their backs today, they'll be back tomorrow. If you haven't already made the purchase, it's time to get moving. And the NAB convention will be a great place to shop and compare. (Continued on page 32)

Ampex, the first word in VTRs, announces the last word in cameras.

Overnight, BCC-1 made your camera obsolete.

BCC-1 is a new state-of-the-art in color cameras.

We predict it will become the new standard of the world, because it was designed from the floor up to be the **now** camera. To fill the **now** needs of working broadcasters.

Now the director can count on superb, unsurpassed picture quality. Operational flexibility lets him set up and shoot, in the studio or in the field, in minutes. New convenience features give him better creative control

of his cameraman and his picture.

Now the cameraman can claim a camera for his own—"the cameraman's camera." Because the BCC-1's maneuverability makes his work faster, easier, more efficient. Like a tiltable, rotatable viewfinder. A return viewfinder feed. New digitized intercom.

And now the engineer can smile again. About picture quality from 1" Plumbicon* tubes. 1000 hour reliability.

Ruggedized construction throughout. Modular design for accessibility and easy maintenance. Computer-matched yokes. Automatic centering. And more.

And now, finally, the manager gets what **he** really wants: cost efficiency. A camera unprecedented for rugged, stable, efficient, reliable performance, and a better on-air look. A camera on which all of his key people can agree. A **new** camera that, in today's economy, adds up to the **only** choice for investment value. Now and for the future.

See why. See it for yourself. For a demonstration, call your local Ampex Broadcast Sales Engineer, or write: Ampex Corporation, Audio-Video Systems Division, 401 Broadway, Redwood City, CA 94063.

AMPEX



www.americanradiohistory.com



FCC Chairman Wiley will be on hand, along with other Commission members. As usual, there will be fire and counter fire.

A Plea From NAB

The NAB did ask the Commission to delay their deadline date by at least six months. Meanwhile, of course, a goodly number of stations already had purchased the new EBS equipment.

From the manufacturer's point of view, they had pushed to design and build the new EBS equipment to meet the deadlines. And one of their major objections to delaying the deadline (after all they would sell their units anyway) was that if the deadline weren't firm, the industry would maybe be only half ready to handle an EBS problem should it occur on April 15 or any other day shortly thereafter. Then too, from their point of view, it would have been a lot easier to promote their equipment over time, as well as to run it down the line, wring it out, and deliver.

In its filing, NAB said that since the system was adopted on December 5, 1974, stations have been asking what the cost of new equipment would be. Answers ranged from \$100-\$700, and also that the government would issue a schematic which would enable station engineering personnel to build the required units for as little as \$50.

"As a result," NAB said, "most stations chose to ignore the initial commercial units which were placed on the market in the \$300-\$700 range."

Finally, in August of this year, the Commission decided to require type acceptance of encoders and the idea of do-it-yourself units was no longer a practical consideration.

Questions were raised as to why all stations should be required to install the transmitting equipment, rather than just a few. Commission personnel conceded the merit in such questions and suggested the real possibility of a further extension of the effective date.

NAB also said "it is an industry composed of hundreds and possibly thousands of radio stations whose role as transmitters of the two-tone signal would be redundant to the point of absurdity. These latter stations should not be required to purchase equipment only to find later that their role as transmitters is superfluous."

Plan Your Time And Interest

You'll notice that on page 33 we included a four-section map of the convention exhibit area. Also, on page 48 we have included a list of manufacturers, their booth numbers, new products, and their hotel.

The key to using your convention time wisely is to mark the maps to indicate (from these special sections) those manufacturers you'll want to be sure to visit.

The FCC's View

Meanwhile, the Commission said NAB failed to provide supporting data for its claim that stations, on notice for more than eight years of impending changes, would be affected adversely by the new system. In addition it said the EBS twotone system's primary purpose is for inter-station signalling between broadcast stations rather than as home warnings, all references to which were deleted in 1972 when any use of inter-station signalling by the general public was put on a secondary basis.

The FCC said that while it did not wish to discourage public monitoring, it was imperative that the two-tone system become operational to improve inter-station signalling.

More On Home Brew

The Commission pointed out that a station licensee who constructed not more than five encoders or decoders for his use at one station location and did not offer them for sale need not submit the fees required with certification and type acceptance applications but still must obtain formal type acceptance and certification from the FCC.

Since a conscientious licensee would assure that the station-built equipment was thoroughly tested before installation and use, the Commission said the only additional requirement was that they submit test results to the FCC.

The Commission said the requirement that all broadcast stations, with the exception of noncommercial educational FM's with 10 watts or less power, be equipped with the two-tone system was intended to ensure adequate interstation signalling under the most adverse national, regional or local

(Continued on page 38)

BROADCAST engineering.

McCormick Place Locator Guide

Section 1 Exhibitors
Andrew Corp.-510
Angenieux Corp.-304
Ball Bros.-308
Berkey Colortran-107
Boston Wire-204
Cohu-302
Colorado Video Inc.-105
Conrac-102
Data Communications (BIAS)-104 104 GTE Sylvania-206


Hitachi-Shibaden-200 International Video Corp. (IVC)-514 Kliegl Bros.-508 Listec TV Equipment-306 Marconi-301 Mohawk Wire-212 Power Optics-103 Q-TV/Telesync-208 RCA-502 & 504 RCA-502 & 504 RCA/Commercial Communica-tions Systems Div.-500 RCA Solid State-506
Recortec, Inc.-101
Richmond Hill Labs-100
Teledyne-210
Telemet-300
Telex Communications-512
Varian Assoc., Eimac Div.-310
Vital Industries-106
World Video-214

Section 2 Exhibitors AEL-601

Alford Mtg.-503 Ampex-513 Ampro Corp.-812 Audio Designs-511 Barco US Div., Kallman Assoc.-600 Belar Electronics Lab.-509 Bird Electronics-705A Broadcast Electronics Inc.-507 Broadcast Programming Intl.-803 CCA-602



Entrance




Micro-Trak Corp.-815
Moseley Assoc. Inc.-505
Nortronics-801
QRK-702
Scully/Metrotech-817
Stanton Magnetics-811
Storeel-700
Systems Marketing Corp.
(Sonomag)-709A
Thomson Elec. Tube-814

Section 3 Exhibitors
Akai America-545
Alan Gordon Enterprises-925
Amco Engineering-827
Army Recruiting-721
Asaca-614
Audi-Cord-922
Audio Services Inc.-821
Auditronics Inc.-804
Automated Processes-711
Beston Electronics-616
Beta Technology-629
Cablewave Systems Inc.-710
Camera Mart-935
Camex-714
Ceco-555


Cetec Corp. (Sparta Corp., Jampro Antenna, Cetec Audio, Vega, Schafer Electronics)-615
Cetec Audio (Cetec)-615
CMX Systems (Orrox Corp.)-606
Commercial Electronics Inc. (CEI)-519
Computer Image-627
Computer Magnetics
Corp.-543
Comrex Corp.-831
Consolidated Video Systems (CVS)-547
Control Design Corp.-706
Cox Data-604
Dielectric
Communications-808
Dipol-835
Drake-Chenault-806
Eastman Kodak Co.-521
Edutron-928-30
Electron-Voice Inc.-802

Fernseh Group, Robert
Bosch-610
Film Treat-924
Fujinon Optical-541
Grass Valley Group-517
Industrial Sciences Inc.-539
Jampro Antenna (Cetec)-615
McCurdy Radio-704
Memorex-537
Charles Michelson-923
Micmix-829
Micro-Consultants-926
Micro-Probe-918
Mingom Div., 3-M-529
Minneapolis Magnetics-825
Nagra Magnetics-708
National Guard-819
O'Connor Engineering-916
Orrox Corp. (Videomax and
CMX Systems)-606
Pacific Recorders-717
Pentagon Industries-621
Phelps Dodge-625
Potomac Instruments Inc.-523
Q.E. I.-943
Radio Programming-927
Revox Corp.-549



AISLE

500





Rhode & Schwarz-533
Robins-Fairchild-553
Rosco Labs-929
Rupert Neve-715
Russco Electronics-551
Sansui-525
Schafer Electronics
(Cetec)-615
Sintronic-713
Sparta (Cetec)-615
Spectra Automation
Systems-839
Studio Tape Exchange-810
Taber Mfg.-623
Tektronix Inc.-515

Television Research Int'l.
(TRI)-612
Tepco-934
Terracomm-931
3-M-527
Time & Frequency
Technology-619
UMC Electronics-712
US Air Force-800
US Army Reserve-535
U.S. Pioneer Electronics-837
United Research-823
Utility Tower-531
Vega (Cetec)-615
Videomax (Orrox Corp.)-606

Section 4 Exhibitors
Acrodyne Industries-109
American Data Corp.-403
Anixter Mark-130
Arvin Echo-316A
Atwood Richards-915
Central Dynamics Corp.-518
Cine Co.-913
Cinema Products-406
Communications
Technology-232
Comquip-226

Wilkinson Electronics-617 Willi Studer-833 Convergence Corp.-317
Corning Glass-116
Data Disc-112
Datatek Corp.-313
Datatron-409
Digital Video Labs-305
Dynasciences-400
E & O-315
Eigen Video-906
Electrohome Ltd.-311
Electronics, Missiles & Comm.-314
ESE-122
Farinon Electric-110
Fidelipac/Telepro-405







Flash Technology-322
Fuji Film-411
Ikegami-522
Innovative TV Equip.-111
International Tapetronics-307
Jefferson Data-222
JVC Industries-413
Kansas State Network
(KSN)-402
Key Mktg.-911
Kings Electronics-921
Laird Telemedia-113
Lightning Elim.-115
Lint Assoc.-903
L-W Int'l.136

Merlin Engineering-140
Micro Communications-118
Microwave Assoc.-309
Mole-Richardson-114
Nat'l. Cine-117
Nurad-320
Optek-902
Orban-909
Otari Corp.-209
Panasonic-Matshushita-524
Philips Broadcast
Equipment-516
PSI-108
Quick-Set. Inc.-312 Quick-Set, Inc.-312 Ramko Research-919

Rank Industries-201
Scientific Atlanta-132
Sescom-119
Shure Bros.-324
SMPTE-128
Soll Inc.-120
Sonex-224
Sony Corp. of America-303
Sound Tech-123
Strand Century-401
Tele-Cine, Inc.-216
Telecommunications Ind.
Ltd.-205
Teledata-126
Telemation/NEC America-31 Telemation/NEC America-316 Telescript-207
TV Equipment Assoc.-203
Tentel-228
Thomson CSF-520
Townsend Assoc.-901
Unarco/Rohn-905
US Coast Guard-914
US Marines-318
US Navy Recruiting-910
Vedco-138
Video Aids Corp. of
Colorado-142
Video Tape Co.-404
Ward Beck-407
Winsted-230






D

1

A I S L E



REDUCED OPERATOR ERROR

Here's something you'll like — Sound Tech's new distortion measuring instrument for use in balanced work.

The new 1710A is much more than just a distortion analyzer. It's a system.

It contains its own ultra-low-distortion generator tracked with the analyzer. It's a system that greatly simplifies measuring — gives you fast measuring with simple operation that reduces operator error.

For example, push the frequency buttons and you set both generator and analyzer. Push "Distortion" and you have your reading. Automatically. No slow, tedious manual null-searching.

Features in the new 1710A include:

- a balanced, floating output (600/
- a balanced (bridging) input
- a high-level +26 dBm signal

- +26 to -90 dBm attenuator
- distortion measurements to .002%
- fast 5-second measuring speed
- automatic nulling, optional automatic set level.
- both harmonic and optional intermodulation distortion measurements.

SPECIAL OUTPUT CIRCUIT

In the 1710A you get a transformerless audio generator output that's balanced and floating. No transformer means no transformer distortion. Floating and balanced means you can connect to virtually any audio circuit regardless of configuration. And you can set the output from +26 to -90 dBm in 0.1 dB steps.

FAST, SIMPLE MEASURING

Automatic nulling and the automatic set level option (ASL) give you ex-

tremely fast measuring and little chance for operator error. You can measure in 5 or 6 seconds. With ASL you can measure distortion vs. frequency, and distortion vs. voltage or power without resetting level.

IM OPTION

An additional optional bonus is that the 1710A also measures intermodulation distortion. After you've made a harmonic measurement, just push the "IMD" button. In 3 seconds you'll have the IM reading. With this option you'll be ready for future IM requirements.

CALL/SEND NOW FOR LITERATURE

It's worth while getting the information on this major new distortion measuring system. Call Larry Maguire or Bob Andersen now and get our new product brochure. It's ready and waiting.

5 SOUND TECHNOLOGY

CAMPBELL, CALIFORNIA 95008 (408) 378-6540

For More Details Circle (14) on Reply Card

(Continued from page 32)

emergency conditions. It said to restrict the two-tone transmission capability, as suggested by the NAB, would leave the EBS vulnerable and diminish its flexibility and diversity.

In November 1974, the Commission amended its rules to substitute a two-tone signalling system (a transmission with two audio tones) for the carrier-break (two five-second breaks followed by a 1000 Hz tone for 15 seconds) attention system then in use.

In an order released August 11, 1975, the rules were amended to provide type acceptance and certification parameters that the new EBS attention signal equipment must satisfy before it could be used at broadcast stations. The same order extended the original starting date of January 15, 1976, through April 15, and exempted noncommercial educational FM stations with power of 10 watts or less from installing the encoder.

(Type acceptance and certification are two of three equipment approval procedures used by the FCC. Type acceptance is granted after a review of data submitted to the FCC by an applicant. Certification means that the manufacturer or user has filed a report of measurements to show that the equipment complies with FCC technical rules.)

In seeking a delay of at least one year, the Louisiana Broadcasters said the required equipment was in short supply, the cost of purchase would be burdensome to many small market stations, and insufficient time had been spent in studying the actual need and effectiveness of the new devices.

The FCC replied that 14 equipment suppliers had received equipment type acceptance or certification for EBS attention signal encoders and decoders. It said these suppliers had a combined capability to manufacture and deliver an adequate supply of encoders or decoders by April 15 and, therefore, it could not foresee any problems regarding availability of equipment by that date.

The Commission said one factor that delayed earlier implementation of the two-tone signal was the high costs of the then-available equipment. However, it said, advances in solid state technology had made it possible to produce acceptable equipment at lower costs.


The FCC said manufacturers now indicated prices ranging as low as \$195 for a combination encoder/decoder and therefore, the cost now was neither exorbitant nor prohibitive.

The Commission noted that in 1967 it issued two public notices that emergency broadcast receivers then in operation might become obsolete when a new, improved alerting signal went into operation.

It said equipment then being supplied to public institutions such as schools and hospitals was designed to respond to the carrier-break attention signal which then, as now, was used primarily for inter-station signalling purposes, and such equipment carried no official approval.

The Commission noted that the notices stressed that a two-toned signal technique was being developed and was expected to prove superior to the two-tone signal.





Programmer/Comparators and Controllers

Whether your station is based in New York, Honolulu or anywhere in between, perfect timing of programs, station breaks and commercials is essential. To meet your exacting timing requirements ESE now offers two precision timing systems. For flexibility and economy with up to ten events, ESE has de-

signed the 750 Series of Programmer/Comparators. Rugged thumbwheel programmers coupled with an ESE clock or timer to provide a single pole contact closure (1 Amp contact rating) for the length of time program matches display. Low on cost, the reliable Programmer/Comparators start at \$305.


Write, Wire or Call Today: 5051/2 Centinela Avenue

When you want to program more than ten events, consider the ES 780 Series of Programmer/Controllers: A Solid State Random Access Memory united with an ESE clock or timer to provide 32 user-programmed outputs. Ten minutes is all you need to program all 32 events. Manual override and ten sec-

ond re-programming provide maximum flexibility. All this in $5\frac{1}{4}$ inches of rack space! Internal crystal time-base and battery pack are standard features. Four digit, 32 event units are \$1,200. and Eight digit, 32 event units are \$1,500. Custom options and special orders are available.

Inglewood, California 90302 • (213) 674-3021






And if it's Memorex Chroma 90, it is.

In fact, Memorex Chroma 90 Broadcast Video Tape has an image quality so crisp and clear, we dared test it against a live picture on a closed circuit TV monitor. Even the Broadcast Engineer we challenged couldn't tell if the picture he was watching

was live or on Memorex Chroma 90. That's the kind of consistency you need

in a tape today. And every day.



EMOREX CHROMA 90

Reproduction so true, we can ask, "Is it live, or is it Memorex?"

©1976, Memorex Corporation, Santa Clara, California 95052

NAB product review

Since the flood of new products often is the biggest story coming out of the NAB convention, we're kicking off our products section up front. You'll see here a sampling of products that will be on display in the exhibit area, mostly for the first time.

And, you'll note that we are including a circle number with each item. In this way, you can circle the appropriate number on our Reader Service Card and get further information. So even if you don't make it to the convention, you can have about all the information you will need for your own product files.

As expected, the halls will be crowded with two hot items: emergency broadcast equipment and ENG packages. And speaking of EBS, Broadcast Engineering Techniques now has type approval by the FCC. Since the April 15 deadline for installation of the EBS equipment still stands, buying should be brisk.

But it's the ENG and LIVE areas that will show most of the new equipment. There will be new cameras, maybe even a few new recorders. The approach will be to make the equipment lighter, easier to operate, and editing equipment even more practical. There should be a lot of new support equipment.

Even if your interest doesn't lie in EBS or ENG equipment, there will be plenty new to see. Antennas continue to change, as well as transmitters. Even automation will have some new, interesting wrinkles.

Hand-held Color Camera

A versatile "take-it-anywhere" hand-held camera for professional quality video productions is now available from the Broadcast Equipment Division of **Philips Audio Video Systems Corp.** Known as the Philips LDK-11, the camera has many features which make it ideal for a wide variety of on-site television assignments, such as electronic news gathering, local station commercial productions, documentaries and special events.

For maximum flexibility, the LDK-11 may be either battery or

AC powered. The system design permits operation of the camera either as a fully self-contained portable unit, or as a cable-connected, remote-controlled camera when integrated with additional cameras in a multi-unit studio or field pickup.

Compactly constructed, the LDK-11 camera head with lens weighs only 15 pounds. It contains three ²/₃-inch Plumbicon pickup tubes and intégral bias light to minimize lag at low light levels. Augmenting pickup quality is a patented beam splitting prism which Philips claims provides high quality pictures compatible in colorimetry with studio cameras. For added operating efficiency, it is equipped with automatic white balance and automatic iris.

Equally lightweight, the 19-pound backpack not only has been designed for wearer comfort, but also to give the cameraman immediate and easy access to all necessary operational controls. The pack produces a fully processed encoded signal, including contour enhancement. It contains provisions for connection of two commentator microphones and a composite interface connector to connect all necessary signals to the remote control unit or an associated VTR.

In all modes of operation, the camera system can be genlocked to an external signal either at the backpack or the remote control unit.

To provide the cameraman with maximum accessibility to key controls, the LDK-11 camera contains fingertip controls for VTR stop/start, motorized zoom and servo iris, auto/manual exposure, auto/manual white balance, external viewfinder video monitoring, and a four-position filter wheel.


For More Details Circle (151) on Reply Card

Pro Recorders

OTARI Corporation will introduce several improved models of its professional recorder line. These



Regardless of who made your 2/3-inch Plumbicon* TV camera, or where it was made— Amperex has the exact replacement for the tube that came with the camera.



We know this tube as only its originator can know it. You can take our word for it...there is only one Plumbicon. And no matter where your Plumbicon camera comes from, whether it's a full-sized studio camera or one of the new hand-held portables... Amperex has the replacements for your equipment that will give you equal or better per-

formance compared to any tube that came with the camera.


There is this difference. Amperex replacement tubes are immediately available, off-the-shelf,

for delivery within 24 hours through local distributors and Amperex factory sales representatives. And Amperex tube distributors (your own local businessmen), are carefully selected for their ability to support Plumbicon TV camera systems with on-the-spot customer support and on-the-spot customer service.

For more information on Plumbicon TV camera tubes, write or phone: Electro-Optical Devices Division, Amperex Electronic Corporation, Slatersville, Rhode Island 02876. Telephone: 401-762-3800.



★Trademark of N.V. Philips of the Netherlands



Recorder/Reproducer \$775 (Reproducer \$550)

So Much For So Little

PD-II SERIES

A machine that records and plays mono tapes in the "A" size cartridge, stops automatically on the 1 kHz cue tone and offers you longer life, less maintenance and better performance than any other cartridge machine at an economy price.

Compare For Yourself

- Quiet air-damped solenoid
- Flat, stable ½ inch solid aluminum deck
- Micro-adjustable head assembly
- Direct-drive capstan motor
- Trim design 3 units fit side-by-side in a 19 inch equipment rack
- Latest solid state components
- Plug-in circuit cards
- No relays

CALL US AND WE'LL PROVE IT TO YOU

For complete information call us collect at 309/828-1381. You'll be talking to experienced broadcasters who not only know what ITC can do—but know what you want it to do.



INTERNATIONAL TAPETRONICS CORPORATION

P.O. Box 241•2425 South Main Street Bloomington, IL. 61701 Marked Exclusively in Canada by McCurdy Radio Industries Ltd.

For More Details Circle (18) on Reply Card

NAB Products (Continued from page 40)

include the production version of the ARS-1000 automated radio station reporducer, the eight channel MX-5050 with variable speed (±10% DC capstan servo as standard, plus the two and four channel versions with and without optional DC capstan servo, and the MX-7308 one-inch eight channel recorder.

ARS-1000 Automated Radio Station Reproducer: The production version of this machine, already in wide use in automation systems, will be demonstrated for the first time at NAB 76. The ARS-1000 is a ruggedly built rack mounted reproduce machine designed to meet the special needs of the automated radio broadcaster for long term reliability under continuous operation.

Its features include two speeds—7½ and 3¾ ips, two channel stereo (half track) head stacks (full track heads optionally available), recessed front adjustable output level and head azimuth, plug in professional

grade PC boards and relays, IC preamp in head assembly for improved S/N, simple operation plus remotable Play and Stop, ready light to indicate proper tape threading, special long-life polypropylene pinch roller and ball bearings.

MX-5050 Compact Recorder: A full capability professional recorder, with $10^{1/2}$ inch reels, three motors, and two or four channels in 1/4 inch tape. New at NAB will be the first showing of the variable speed DC capstan servo, a new dual case for the four channel, and portable cases for all models. MX-5050 professional features include front panel edit and cue controls, motion sensing, precision mounted splicing block on head cover, synchronous reproduce, professional XLR connectors for line in and 600 ohm line output, variable or fixed outputs (at +4 dBm or -10 dBm), front adjustable bias and equalization, built-in test and cue oscillator.

For More Details Circle (150) on Reply Card

EBS-100 Encoder-Decoder

Broadcast Engineering Techniques has received FCC Type Acceptance and Certification for its Model EBS-100 Emergency Broadcast System Encoder-Decoder.

The EBS-100 employs digital techniques in frequency generating, decoding, and timing functions. Two temperature-compensated precision audio oscillators generate the attention signal frequencies; the Decoder uses CMOS digital comparators which match incoming material against the generator section's accurate reference for identification of the EBS signal. The digital approach provides the reliability and accuracy of integrated circuitry.

In addition to its state-of-the-art design, the EBS-100 features three transformer-isolated Encoder outputs (two switched for stereo stations, one always on for test); a built-in speaker amplifier and speaker; both normally open and normally closed contacts for external decode alarms; and the convenience of a single 3½-inch rack chassis. The optional fixed-tuned AM Receiver comes mounted in the

same enclosure.

The equipment is now in production, and orders are still being assigned shipping dates before the April re-regulation deadline. Production includes a two-day burn-in for component testing. The unit is covered by a five year parts, one year labor warranty.

For More Details Circle (149) on Reply Card

In-line Linear Chroma Keyer

A new in-line linear chroma keyer will be introduced at the National Association of Broadcasters convention, March 21, by **DYNAIR Electronics, Inc.** Incorporating proportional keying techniques, the new SE-362A Chromatech makes possible soft combining of two NTSC encoded color video sources into a single composite picture.


One and two tube color cameras, which do not usually provide RGB outputs, can now be utilized as a video source in post production applications with or without the use of a production switcher.

According to Bob Vendeland, VP
(Continued on page 45)

BROADCAST ENGINEERING

In Seattle it's Mark VIII. Automatically.

KCTS-TV, Seattle, recently purchased six Marconi Mark VIII-B cameras, after careful evaluation of every known top quality camera. We welcome Public Broadcasting Station KCTS-TV to the ranks of commercial, educational, and specialist users of the Mark VIII-B camera in the U.S. and around the world.



Mark VIII-B. A well-proven, reliable production tool.

- World's first fully automatic color camera
- Super-sensitive. Saving studio energy by operating at f/4.0 in 75 f.c. Or operating on remotes when others guit.
- Small and lightweight, using 1/2-inch cable.
- Always making "Big-Picture" pictures AUTOMATICALLY.

Marconi Electronics, Inc.

National Sales: 4785 Lake Forrest Drive, N.E. Atlanta, Georgia 30342 (404) 252-7842

Executive Office / N.Y. Area Sales: 100 Stonehurst Court, Northvale, New Jersey 07647 (201) 767-7250

See us at NAB Booth 301

Quality, Reliability, Service...

Excellent Reasons for Choosing ADM®



Audio Designs® has consistently been a leader in innovative design concepts and "state-of-the-art" techniques. Our principals have worked on the studio side of consoles—they know what professionals want and need to do their demanding jobs faster and easier. And customers know that ADM Consoles are engineered for consistent high performance. That is one reason why our customer list reads like a "Who's Who" of the industry.

Our consoles are manufactured with the finest components for long life and trouble-free operation. Hopefully you will never need service, but if you do, we will provide assistance promptly and without question. Our five-year warranty is the most liberal in the industry. Before you buy any console—standard or custom—let us give you some more reasons why an ADM Console is your best buy. Call or write us soon.



AUDIO DESIGNS AND MANUFACTURING, INC. 16005 Sturgeon, Roseville, Michigan 48066 Phone: (313) 778-8400, Cable: AUDEX TLX-23-1114 AMPEX, DISTRIBUTED OUTSIDE U.S.A. BY AMPEX INTERNATIONAL OPERATIONS, INC.

See us at the show-Booth 511

For More Details Circle (20) on Reply Card

NAB Products

(Continued from page 42)

Marketing of the San Diego based DYNAIR, who claims delivery of the keyer is from stock, "the introduction of the SE-362A Chromatech as well as a completely new line of broadcast video, pulse, pulse delay, and subcarrier distribution equipment to DYNAIR's broadcast distribution switchers will allow our specialized dealers to provide an integrated package backed by one of the most experienced switching and distribution manufacturers in the field."

For More Details Circle (142) on Reply Card

Video Line Isolator

Video Aids Corporation of Colorado will be in booth 142 with their new video line isolator called the VL-1. This self-contained electro-optical unit passes 1 Hz to 8 MHz yet it will reject hum levels up to 70 V rms at 60 Hz.

When using the VL-1, video signals can be routed from building to building or between complexes where equipment is connected to different AC line sources. Listed at \$250, the VL-1 is available on two weeks delivery.

For More Details Circle (143) on Reply Card

FM Transmitting Antenna

CCA Electronics will introduce a new FM transmitting antenna at NAB. This new antenna comes in a low power and a high power version.

The low power version will handle up to 10 kW, while the high power model will take up to 50kW (single bay). These antennas feature a 700 kHz bandwidth with the SWR under 1.1:1. All elements are 50 ohm to assure lowest Q. Large gap form factor of the antenna eliminates feed point straps and insulators.

Its integral radome is designed to offer no increase in wind load.

For More Details Circle (144) on Reply Card

High Speed Color And B/W Video Duplicator

Panasonic has introduced the world's first cartridge VTP system for EIAJ standard color and black-

Practical Tests & Measurements

Tektronix will do something new and interesting in their booth at NAB. The company will feature a tests and measurements theater that will give practical "how to" demonstrations for making measurements in AM, FM and TV

and-white video cartridges. This mass printing system makes possible duplication of a 30-minute video cartridge in less than three

minutes.

In introducing this new product, Mr. Irwin Tarr, General Manager of Panasonic's Video Systems Division, noted that this cartridge VTP will make it possible to print video tapes almost as easily as one makes duplicates of documents on an office copying machine.

The Panasonic cartridge VTP system, VTP-1000, consists of two compact machines: master cartridge recorder NV-5180 with controller NV-5181, and tape printer NV-5182.

The master cartridge recorder records the video signal from a camera monitor, VTR or VCR in a pattern that is a mirror-image of the EIAJ standard color or #1 black-and-white signal. This master can be used to make 1,000 precise duplicates. The master tape is recorded on a video cartridge—all tape threading, duplicating, and rewind functions are thus performed automatically.

For More Details Circle (145) on Reply Card

Triaxial Connectors

Kings Electronics Co., Inc., Tuckahoe, New York has developed Tri-Loc®, a new connector series for the television broadcast industry. This series is designed for triaxial cable.

The Tri-Loc® connector is designed to fulfill the interconnect requirements of triaxial color cameras for the telecast industry. This unique quick disconnect RF connector terminates 3/8" and ½" diameter triaxial cables.

When mated, the connectors are completely weatherproof. This rugged mechanical construction, with Kings' durable TR-5 weatherresistant finish, makes the connectors ideally suited for outdoor use.

operations.

The basic elements of these sessions will be proof of performance, monitoring requirements, and day-to-day maintenance. The AM and FM sessions will focus on audio systems tests and measurements.

The connectors have an interface retention greater than 100 pounds and cable retention greater than 200 pounds.

The contacts can be either crimped or soldered. The inner braid is crimped and the outer braid is of the conventional combout type, thus assuring quick, reliable termination.

The use of triaxial cable with its inherent low capacitance enables the camera crew to use the triax camera at distances 20 to 30 times further from the van than had been possible with the old multicable multiconductor system.

For More Details Circle (146) on Reply Card

EBS Decoder

Bryant Electronics has introduced an EBS decoder that they've dubbed the Model EBSD-1. Bryant is specializing in decoders only.

The EBSD-1 is an all solid state design, with TTL and PPL circuitry in a broadcast equipment configuration. The power supply is IC regulated.

This decoder can be driven by any receiver capable of 100 mw output into an 8 ohm load. The unit includes 8 and 600 ohm inputs.

The front panel includes two control switches that are tied to color coded status lights to show switch position. Also, a digital timer is used with the alarm.

For More Details Circle (147) on Reply Card

Live Color TV Camera

The 1976 Harris NAB exhibit will feature the new top-of-the-line TC-80 live color television camera with optional Triax, which will be introduced at the convention.

The TC-80 uses three normal lead oxide or anti-comet tail tubes, interchangeable by the customer as desired, and employs a full range of automatic features. The camera

stresses extremely stable operation, matchless color integrity and fast, easy setup and control.

Harris will also introduce its new circularly polarized television antenna at the NAB. The CP antenna has excellent specs for axial ratio, horizontal circularity, and maximum antenna bandwidth. The horizontal circularity may be custom tailored to fit the user's requirements. A model antenna will be on display at the show.

For More Details Circle (148) on Reply Card

Microwave **Transmitters**

The new all solid state TEM-7 and TEM-13 microwave transmitters for television broadcast have been announced by Tepco Corporation, Rapid City, South Dakota. The TEM-7 is 7 GHz and the TEM-13 is 13 GHz.

Both have digital frequency control, continuously variable frequency adjustment and micrometer frequency dials. Companion receivers have automatic frequency control.

Applications are STL, inter-city relay for fixed installations, portable for electronic news gathering and remote pickup for temporary installations.

A company spokesman said the new designs are based on manufacturing and field experience the company has gained since it was founded in 1961.

For More Details Circle (152) on Reply Card

Field Strength Meter

The FIM-71 Field Strength Meter by Potomac Instruments is a truly portable test instrument of laboratory quality, covering the frequency spectrum between 47 MHz and 225MHz.

This unit contains an accurate internal calibration oscillator and may be used as a tuned voltmeter or, when used with the associated antenna assembly, a highly accurate field strength meter. Intended primarily for measurement of commercial TV and FM broadcast signals and harmonics, the FIM-71 has

switchable IF bandwidth and switchable AM/FM demodulators which make it suitable for practically all types of radio frequency emission measurements within its frequency range. Either average or peak values of TV sync signals may

The receiver operates as a linear voltmeter having a 120 dB range in 20 dB steps. The 5-inch taut band meter has a logarithmic (approximate) scale calibrated between 1 and 10. A dB scale is also provided for signal ratio measurements. A dynamic range of 60 dB, without attenuator switching, is provided in the LOG mode of operation.

For More Details Circle (153) on Reply Card

Video Spot Assembler

The Recortec Video Spot Assembler (VSA) is a microprocessor based system designed to provide the convenience and versatility of a cartridge system at a fraction of its cost. The VSA uses the same two VTRs used for A-B rolls for (Continued on page 145)

PROFESSIO OTARI MX-5050

What does a professional recording or broadcast engineer demand in a tape recorder? Above all, he wants consistently high performance, production and editing features, ease of operation and set up, and a reliable mechanism that won't let him down when the schedule gets tight.


If that's what you want too, then take a close look at the Otari MX-5050. It's a full capability professional machine in a compact package. This new recorder is the end result of Otari's ten years of leadership in producing Japan's finest professional recorders and high speed duplicators.

Check these features: gentle, positive tape handling; front panel edit and cue; built-in precision-aligned splicing block; front adjustable bias and equalization; synchronous reproduce for overdubbing; professional connectors, levels, and impedances; 68 dB S/N, 19 dB headroom, 60 dB crosstalk; optional variable speed dc capstan servo; motion sensing; plus many others. And if you need more than two channels, the MX-5050 is also available in four channel (1/4 inch) and eight channel (1/2 inch), the eight channel with dc capstan servo as standard.

See Otari at NAB Booth 209.



Otari Corporation 981 Industrial Road, San Carlos, Calif. 94070 (415) 593-1648 TWX: 910-376-4890 In Canada: Noresco Mfg., Toronto (416) 249-7316



For More Details Circle (132) on Reply Card

This is all you need to get moving with Dolby FM



Remember the first time you came across Dolbyized cassettes? And how surprised you were that music could sound so good in such a convenient form?

Well, now the same principles are being used to improve FM broadcasting. The audible effect of the Dolby system as used in FM is a bit more subtle than with

cassettes. But the overall results are just as important. Dolby FM is cleaner, with sparkling high frequencies free of limiting. And, of course, noise is reduced, which often increases the area of good reception.

As of August 1975, over 100 US stations have purchased the Dolby Model 324 or

334 FM Broadcast Unit. The unit accurately compresses the signal in accordance with the Dolby B-Type characteristics and changes the effective transmission time-constant to 25 microseconds. This allows the station to reduce or eliminate any high frequency limiting required previously.

Akron OH Albany NY Allentown PA Alta Vista VA Arlington TX Balkmore MD Birmingham MI Boston MA	WHNE WROR	106.5 94.7 98.5	Cincinnati OH Collegeville MN Columbus GA Columbus OH Columbus OH Dayton OH Dallas TX Dallas TX	WGUC KSJR WEIZ WCOL WOSU WTUE KCHU KTLC	90.9 90.1 100.1 92.3 98.7 104.7 90.9 100.3	Edmond OK Fairmont NC Flint MI Fort Wayne IN Fort Worth TX Fresno CA Gainesville GA Grand Rapids MI	KWHP WFMO WGMZ WMEF KWXI KPHD WDUN WZZM	107.9 97.3 97.1 95.5 106.7 95.7	Los Angeles CA Los Angeles CA Los Angeles CA Lancaster PA Lexington VA Louisville KY Madison WI	KGBS KIOO KPFK WDAC WLUR WCSN WLRS WYXE	91.5 99.7 102.3 92.1	New York NY New York NY Normai IL Opportunity WA Paterson NJ Philadelphia PA Portland ME Richmond VA	WOXR WRFM WGLT KZUN WPAT WMMR WDCS WEZS	97.9 103.7	Seattle WA Skokie IL St. George SC St. Louis MO Stevens Point WI Sylvania OH Topeka KS Tuscaloosa AL	KIXI WCLR WPWR KCFM WSPT WXEZ KTPK WUOA	95.7 101.9 95.9 93.7 97.9 105.5 106.9 95.7
Boston MA	WVBF	105.7	Dallas TX	KVIL	103.7	Hanover NH	WDCR	99.3	Maine FL	WAIA	97.3	Rochester NY	WCMF	96.5	Utica NY	WOUR	96.9
Buffalo NY Buffalo NY	WDCX WBEN	99.5 102.5	Dallas TX Denver CO	KZEW KBPI	97.9 105.9	Hartford CT Henrietta NY	WTIC	96.5 89.7	Manassas VA Memphis TN	WEZR WKNO	106.7 91.1	Rochester NY Saline MI	WEZO WIOB	101.3 102.9	Washington DC Washington DC	WAMU	88.5 97.1
CarbondaleIL	WSIU	91.9	Denver CO	KLZ	106 7	Houston TX	KILT	100.3	Miami FL	WAIA	97.3	Salt Lake City UT	KDAB	101.1	Washington DC	WGMS	
Charlotte NC	WEZC	104.7	Detroit MI	WABX	99.5	Houston TX	KRLY	93.7	Minneapolis MN	KSJN	91.1		KSL	100.3	Washington DC	WHUR	96.3
Charlotte NC	WROO	95.1	Detroit MI	WOMC		Indianapolis IN	WNAP	93.1	Morgantown WV	WAJR	101.9	San Antonio TX	KEXL	104.5	Washington DC	WMAL	107.3
ChicagoIL	WFMT	98.7	Detroit MI	WJZZ	105.9	Jackson MS	WSLI	96.3	New Orleans LA	WEZB	97.1	San Diego CA	KGB	101.5	Wilkes-Barre PA	WYZZ	92.9
Chicago IL	WLOO	100.3	DetroitMI	WMUZ		Kettering OH	WVUD	99.9	New Orleans LA	MNOM		San Francisco CA	KABL	98.1	Youngstown OH	WYSU	88.5
Cinclonati OH	WEBN	102.7	Detroit MI	WQRS	105.1	Los Angeles CA	KBIG	104.3	New York NY	WNEW	102.7	SeattleWA	-KIRO	100.7			

JANUARY 1976: 30 more stations

As listeners to these stations can hear for themselves, a Dolby FM signal is compatible. In fact, most people find it a better signal even when received on their normal equipment without Dolby decoding.

However, some listeners like to take advantage of every opportunity for improvement. If they use Dolby circuitry* during reception, they can bring the signal even closer to the quality of the original source material used at the station.

Naturally, the noise is reduced. But that's not all. Dolby compression is standardized, recoverable compression. By using Dolby encoding instead of the conventional high frequency limiting normally required during transmission, the station gives the listener at home the opportunity of recovering the full frequency range and dynamics of the signal. Furthermore, depending on the amount of limiting previously used, many stations find that Dolby encoding permits them to increase their level – which is good for both the listeners and the station.

If these prospects excite you, we think you will soon be wanting to check out the new Dolby Model 334 FM Broadcast Unit. \$1,350 and 1½ inches of rack space are all you need to get moving with Dolby FM – an improvement we think both you and your listeners will appreciate.

Distributors
FTC Brewer Co, Pensacola, FL
Broadcast Communication Devices, Anaheim, CA
Broadcast Consultants Corp, Leesburg, VA
Collins Radio Group, Dallas, TX
Control Technology Inc, Fort Lauderdale, FL
HM Dyer Electronics, Farmington Hills, MI

La Salle Audio, Chicago, IL Lebow Labs Inc, Brighlon, MA Pacific Recorders and Engineering Corp, San Diego, CA Schaler Electronics Corp, Golela, CA Sparta Electronics Corp, Sacramento, CA Whalin's Pro Audio Sales, Arlington, TX Technical literature and reprints of papers describing these developments are available from our offices or distributors

*Some of the 50 Dolby licensees are already producing their new receiver models, and others have new designs in the pipeline.

Dolby Laboratories Inc

'Dolby' and the double-D symbol are trade marks of Dolby Laboratories Inc.

March, 1976

731 Sansome Street San Francisco CA 94111 Telephone (415) 392-0300 Telex 34409 Cable Dolbylabs 346 Clapham Road London SW9 Telephone 01-720 1111 Telex 919109 Cable Dolbylabs London

NAB Exhibitor List

The following is a list of NAB convention exhibitors who responded to our pre-convention survey. Of special interest, of course, is the equipment they list as NEW. This equipment will be on display at the NAB for the first time.

In another section of our pre-

convention section, you'll find maps of the exhibit area. It will help you plan your stops if you'll note the name and booth number of a company you want to visit, turn to the maps, and mark the booth there so you can easily find it when you get to the convention.

Anixter-Mark Booth 130

Microwave antennas for electronic journalism, STL and intercity systems.

NEW: Circular polarized 2.0GHZ antennas.

Suite: NA

Audio Designs & Mfg., Inc. Booth 511

Audio consoles, accessory components.

NEW: ADM DA 16/CH 20 audio distribution system, ADM 660 1/3 octave audio real time analyzer.

Suite: NA

Auditronics, Inc. Booth 804

Audio consoles.

Suite: NA

Belar Electronics Laboratory, Inc. Booth 509

Comprehensive line of AM, FM, TV modulation and frequency monitors with their respective auxiliary equipment. This includes the two new AM modulation only monitors recently introduced. Also AM stereo techniques via an active display. Silence alarms for both modulation and carrier off.

NEW: A number of different units directed to alerting the broadcaster to the moment-by-moment performance of his broadcasted signal.

Suite: None.

Bird Electronic CorporationBooth 705A

Quality instruments and components for RF power measurement; RF directional Thruline® wattmeters; RF absorption wattmeters; 2W to 50kW

(Continued on page 50)

Acrodyne Industries Inc. Booth 109

Broadcast television translators, transmitters and accessory equipment.

NEW: T-210 100% solid state UHF translator, 500-Watt television transmitter.

Suite: Conrad Hilton

American Data Division, Airpax Electronics, Inc. Booth 403

Featured, will be the all new ADC 558 production system. Also on display will be the latest version of the 900 series distribution switchers and the full line-up of related terminal equipment.

NEW: The 558 "Dual Key" production switcher and the 553 production switcher designed for remote ENG and small studio operations.

Suite: NA

American Electronic Laboratories, Inc. Booth 601

AM-5KE, AM-10KD, FM-10KE, FM-25KE, antennas, dummy loads & assorted "post transmitter" equipments.

NEW: AM-5KE and FM-10KE transmitters

Suite: NA

Ampex Corporation Booth 513

Studio and portable videotape

recorders for broadcasting, business and industry, education, and government; video disc recorders; color broadcast cameras; editing systems; broadcast automation products; digital time base correctors; professional audio recorders and accessories; time code synchronization systems; video tape in all widths and formats; audio mastering and recording tape.

NEW: To be announced.

Suite: NA

AMPRO CorporationBooth 812

Cartridge tape recorders and reproducers broadcast audio consoles; 4 to 12 channel, studio furniture & accessories, cartridge tape transport controllers.

NEW: Modular studio furniture and accessories, cartridge tape transport controller, "B" version cartridge tape equipment.

Suite: NA


Angenieux Corporation of America Booth 304

10x14E11, f/1.6, 10x14.5E11, f/2.2, 15x14E61, f/1.6, 18x20.5E61, f/1.5. Zoom and fixed focal length lenses as well as prisms, dichroics and splitting systems for the broadcast industry.

NEW: Cover all lens - 42x16E11, f/2; for ENG - 15x9.5, f/1.9, 15x12.5, f/2.5.

Suite: NA

THE ADC 900 IS



QUALITY!

RELIABILITY is the watchdog of quality management. With many 900 systems now approaching 20,000 hours of continuous operation with no significant downtime or maintenance required, we offer proven reliability.

Significant Features

- Exclusive use of high reliability standard and multi-sourced proprietary components.
- Only 10 crosspoints per crosspoint module allows in-service maintenance with minimum disruption.
- Input oriented crosspoint modules which allow the superior shielding required to maintain extremely low crosstalk specifications between either synchronus or non-synchronus inputs.
- Individual, horizontally oriented output amplifiers enable superior shielding between outputs and inservice maintenance with no disruption to other output channels.
- Externally accessable control latching and decoding which allows in-service maintenance, no interaction between matrix frames and uses no unique codes or non-compatible addressing schemes. All active control components are plug-in devices.
- External control interface to allow use of multiple control panels of different types on a single system.
- Standard LED grid matrix status display on all systems gives visual display of crosspoint status at all times.

- Control hold system available to return matrix to a last state condition in event of power failure or dip. Hold times of 20 minutes to 12 hours available.
- Fully redundant power systems with visual, aural and remote alarms available.
- · Vertical interval switching standard on all systems.
- Use of an external combining matrix on systems with more than 20 inputs allows complete isolation to the smallest matrix unit (10 x 10) for superb specifications. External matricing simplifies system timing, any input to any output, on large systems.

Customers

Alabama ETV
Bell Labs
City of Los Angeles
Editel
HCG Geneva
Jefferson Productions
KATU
KCTS
KGGM
KLAS
KOLR
Michigan State Univers

ORTQ
RCA Camden
RCA, Ltd.
RTV Belgrade
S.I.U. School of Medicine
University of Louisville
University of Michigan
USIA
U. S. Navy
Venevision
WCAU
WESH
WETA
WPBT
WTVI



AMERICAN DATA DIVISION

AIRPAX ELECTRONICS, INC.

401 WYNN DRIVE • P. O. BOX 5228 • HUNTSVILLE, ALABAMA 35805 USA • TELEPHONE 205 837-5180 • TWX 810 726-2125

1729 WILMONT DRIVE ATLANTA, GA. 30329 404-633-2100 5504 WATERWAY ROCKVILLE, MD. 20853 301-460-1454 3250 WILSHIRE BL. STE900 LOS ANGELES, CA. 90010 213-387-7756 2908 MULBERRY PASADENA, TX. 7750 713-941-7272 233 W. HILL AVE. GLENN ELLYN, IL. 60137

For More Details Circle (133) on Reply Card

Exhibitors

(Continued from page 48)

air cooled, water cooled and self-contained-heat-exchanger loads. New series of line terminations. RF power and VSWR monitors; coaxial filters, couplers and filter-couplers.

NEW: SENTRILINE® filter/couplers for FM transmitters. The Bicentennial 76,000th THRULINE® Model 43 RF wattmeter.

Suite: NA

Capitol Magnetic Products Booth 807

Audiopak A-2 broadcast cartridge, Audio tape Q19 high output, low noise, back coated mastering tape, Audiotape Q15 low noise tape, Audiofilm perforated audio film.

NEW: NA

Suite: NA

CEI (Commercial Electronics Inc.) Booth 519

CEI-290 portable production color television camera system. CEI Camera Control and Operating Control Units.

NEW: CEI-287 professional color television camera system. CEI Medical television camera.

Suite: Blackstone

Cinema Products Corporation Booth 406

16mm TV-newsfilm/documentary cameras, Aero-Kit and Cat-Kit quartz location lighting kits; the CINEVID-16 video-assist camera system; Crystalink wireless system; Sturdy-Lite focusing spot, the CPT-24 fluid head tripod, PLC-4 16mm 400 ft. magazine, J-5 zoom lens control.

NEW: CINEVID-16 video-assist camera system.

suite: NA

CMX Systems Booth 606

In addition to the 340X, the 34X video tape time code editing system. The 340X works with quad or helical or both and is compatible with all other CMX editing systems.

NEW: 34X

Collins Radio Group, Rockwell International Corp. Booth 603

Model 820D-2 1-kw AM transmitter, Model 831D-2 2.5-kw FM transmitter, Model 831G-2 20-kw FM transmitter, Model IC-6 and Model IC-10 control consoles, and Collins' new A7600 program automation system.

NEW: The A7600 program automation system.

Suite: NA

Colorado Video, Inc. Booth 105

Equipment for the transmission of compressed video signals over FM subcarrier channels.

NEW: See above.

Suite: NA

Communications Technology, Inc.

Booth 232

Complete line of video/audio routing switchers.

NEW: Small production switcher, audio switcher.

Suite: NA

Computer Image Corp. Booth 627

Video switcher equipment, R&D and manufacturing products, software production materials.

NEW: Video switcher equipment, CAESAR Electronic character/graphic animation software, large 7243-B production switcher, master control, and two computer controlled editing switchers, software products generated by the CAESAR electronic animation system.

Suite: NA

Computer Magnetics Corp. Booth 543

Auto equalizer, refurbishing Mark X, Mark XV, and Mark XX video head assemblies, refurbishing audio heads for VTR's, video discs & heads for slow-motion applications.

NEW: Auto equalizer.

Suite: NA

COMQUIP, Inc. Booth 226

Fixed lens adapter for color TV cameras.

Suite: NA

Comrex Corporation Booth 831

Introducing: The Comrex radio ENG system; studio diversity system; floor-man's wireless intercom system; 450 MHz 1-Watt hand-held wireless microphone. Also showing: Full line of receivers for ENG cueing/command/control, 450 RA/TA wireless microphone system, cue systems.

NEW: Comrex radio ENG system; studio diversity system; floor-man's wireless intercom system; 450 MHz 1-Watt hand-held wireless microphone.

Suite: NA

Conrac Division, Conrac Corp. Booth 102

Conrac will introduce four new products. The 6000, a 19-inch professional broadcast color monitor with full front access. The 5300, a 19-inch broadcast color monitor, budget priced for general purpose broadcast applications. The 5700, a 13-inch high-resolution broadcast color monitor for 10½-inch tape bridge mounting. The DZB, a 14-inch updated version of the DZA monochrome broadcast monitor for 10½-inch tape bridge mounting.

NEW: See above.

Suite: NA

Consolidated Video Systems Booth 547

Digital time base correctors and digital video synchronizer with electronic video compression.

NEW: "Low cost" digital time base corrector.

Suite: NA

Continental Electronics Mfg. Co. Booth 607


5 kW, 10 kW, and 50 kW transmitters. Also related equipment and services such as design and manufacture of antenna phasing and coupling


(Continued on page 54)

PLANNING FOR 40 KW FM? 4" HELIAX® CABLE WAS DESIGNED FOR YOUR SYSTEM

Designed specifically for use with 40 KW FM transmitters, our new 4" HELIAX flexible coaxial cable handles this power level very comfortably, providing good efficiency, low VSWR and the convenience and economy of continuous lengths.

Broadcasters have been using Andrew antenna system products for 38 years, with complete satisfaction Our present line includes HELIAX flexible coaxial cables, phase stabilized sampling lines for AM rigid line component arrays, pressurization equipment, coaxial switches and a complete line of STL microwave antenna equipment. Most items are available off-the shelf. Ask for Bulletin 1123





ANDREW CORPORATION 10500 W. 153rd St., Orland Park, IL., U.S.A. 60462 Telephone: (312) 349-3300


ANDREW ANTENNA COMPANY LTD. 606 Beech St., Whitby, Ontario, Canada L1N 5S2 Tel: (416) 668-3348

ANDREW ANTENNA SYSTEMS Lochgelly, Fife, Great Britain KY5 9HG Telephone: (0592) 780561

ANDREW ANTENNAS 171 Henty St., Reservoir, Victoria, Australia 3073 Telephone: (03) 460.1544


ANDREW ANTENAS LIMITADA Av. Brigadeiro Faria Lima, 830s/64 Caixa Postal 22.252, 01452 São Paulo, Brasil Tels: 210-2808, 211-5132

IKEGAMI. The Depe



IKEGAMI ENG Systems...over 300 cameras in service


More broadcast-quality ENG Systems by Ikegami are in the field than all other makes combined. Reason: one user tells another they're the "Dependables". They're super-rugged, light, and deliver superb colorimetry. You can get great low-light pictures . . . right down to 15 ft.-candles.



IKEGAMI HK-312 . . . ultra-high performance camera


After putting the cameras of top makers through the wringer, ABC chose the Ikegami HK-312. Besides outstanding colorimetry, stability, and engineering, it offers many more functions than competing cameras. "It's the latest state-of-the-art camera," says Julius Barnathan, V.P. in Charge of Broadcast and Engineering at ABC. An exclusive feature is its push-button minicomputer. In 15 seconds per camera, it will cycle many remote cameras through all adjustment parameters . . . white balance, black balance, flare correction, gamma correction, and 9 registration functions.

nccbbbes



IKEGAMI TKC-950 ... the ultimate film chain

High quality film chain that automatically achieves highest fidelity color reproduction. Built-in test pattern slide. Built-in ALC with ND disk to instantly compensate for all light variations. Unique optical system cuts lens dust out of the picture.



IKEGAMI TM14-1RHP... 600-line resolution NTSC color monitor

This compact 14" color monitor offers the most precise picture reproduction in broadcasting. All key sections have IC circuitry for stable operation, minimum size, long life. Solid state throughout. Adjustment controls are up front for convenience. Exceptionally rugged, rigid construction.

Convenient distributors offer full stocks of parts and quick service nationwide.

LANDY ASSOCIATES

12 Buston Road Cherry Hill, New Jersey 08003 609-424-4660

TRI TRONICS, INC. (TTI)

4019 Tujunga Avenue North Hollywood, California 91604 213-985-6616

TECHNICAL VIDEO SYSTEMS

1148 Burke Street Winston-Salem, North Carolina 27101 919-722-6181

BENNETT ASSOCIATES, INC.

P.O. Box 23 Mercer Island, Washington 98040 206-232-3550

CAMERA MART

456 West 55 Street New York, New York 10019 212-757-6977

ELECTRONICS PRODUCTS CORP.

16006 Waterloo Road Cleveland, Ohio 44110 216-692-3050

ROSCOR, INC.

6160 W. Oakton Street Morton Grove, Illinois 60053 312-539-7700

GRAY COMMUNICATIONS

1709 Stuart Avenue Albany, Georgia 31707 912-439-7610

MARTIN, ZIENKOSKY & BROWNE

13731 Omega Road Dallas, Texas 75240 214-233-5535

Call or write for a demonstration.



Depend on it

Ikegami Electronics (USA) Inc., 29-19 39th Avenue Long Island City, New York 11101 (212) 932-2577

For More Details Circle (137) on Reply Card

Exhibitors

(Continued from page 50)

equipment, diplexers, filters, combiners, and all special requirements related to AM transmitting systems.

NEW: NA

Suite: NA

Data Communications Corp. (BIAS)

Booth 104

BIAS (Broadcast Industry Automation System), a real time sales, traffic, accounting and engineering automation system.

NEW: The BIAS standard interface for linking-up with technical automation systems.

Suite: Continental Plaza

Datatek Corp. Booth 313

TV transmitter color phase equalizer

and waveform corrector, video-audio routing switchers, video sweep generators, differential phase & gain measuring sets, video, audio and pulse D.A.'s.

NEW: Video sweep generators.

Suite: NA

DYNAIR Electronics, Inc. Booth 701

Featuring new line of linear chroma-keyers and color distribution amplifiers. Also on display: audio switching, video switching, digital control modulators, demodulators.

NEW: linear chroma-keyers and color distribution amplifiers.

Suite: NA

Dynasciences Video Products Booth 400

Image enhancers, video processing system, distribution amplifiers, routing & production switchers.

NEW: Model 7200 downstream chroma keyer vibra stop low-cost motion-stabilized lens.

Suite: NA

Electro Home (USA) Limited Booth 311

Monitors.

NEW: 17V, 25V professional color monitors.

Suite: NA

EIMAC Division of Varian Booth 310

X-2159, X-2170 plus tubes for AM-FM-TV service.

NEW: NA

Suite: NA

Electro Impulse Booth 121

AM/FM/TV loads, attenuators, baluns, power meters.

NEW: 40kw self-cooled load.

Suite: NA


(Continued on page 56)

Built for Professionals



ITC's 750 Series Reproducer

1/2 Track Stereo \$1150



Check with any leading automation company for more information or call ITC collect (309-828-1381).




INTERNATIONAL TAPETRONICS CORPORATION

2425 SOUTH MAIN STREET • BLOOMINGTON, ILLINOIS 61701 Marketed in Canada exclusively by McCurdy Radio Industries Ltd • Toronto

© 1975 by ITC

For More Details Circle (174) on Reply Card





This 3½" air dielectric Wellflex consists of a corrugated tubular copper center conductor, unique polyethylene locked vertebrae helix dielectric, copper corrugated outer conductor and black polyethylene jacket. It is remarkably flexible, has excellent mechanical stability and extremely low attenuation.



Velocity of Propagation	96%
Attenuation at 100 MHz	
Average Power at 100 MHz	50.06 kW
Peak Power	

Send for our new $3\frac{1}{2}$ " Coax Data Sheet and our complete catalog.



Cablewave Systems Inc.

60 Dodge Avenue, North Haven, Connecticut 06473 203-239-3311 • TWX: 710-465-0244

Exhibitors

(Continued from page 54)

Farinon Electric Booth 110

ENG version of FV(2)P portable microwave for video and subcarrier point-to-point relay at 2 GHz, with optional 6-watt or 20-watt RF output; information on other fixed and portable microwave equipment for video and subcarrier transmission.

NEW: The above-mentioned ENG version of FV(2)P microwave.

Suite: NA

Fidelipac Booth 405

Master Cart and its stereo phase performance will be featured. Over 400 Master Carts will be available for at random selection. Also the Models 300, 350, 600, & 1200 cartridges, studio on-air light, alignment tools, labels, racks and other accessories.

NEW: Cartridges for use with delay machines, with delays of 8 and 10 seconds.

Suite: NA

Flash Technology Corp. of America Booth 322

High intensity obstruction warning lighting system.

NEW: FTB 205 electroflash beacon system.

Suite: Pick Congress

Fuji Photo Film USA, Inc. Video Tape Booth 411

H-701 broadcast video tape Beridox ¾" u-matic cassettes.

NEW: NA

Suite: Conrad Hilton

Garron ElectronicsBooth 611

RAPID-Q cartridge tape equipment, STE-100 stereo phase enhancer.

Harris Corporation Broadcast Products Division Booth 501

TV cameras, TV transmitters, AM and FM transmitters, consoles, and broadcast antennas.

NEW: TC-80 live color TV camera with optional triax; circularly polarized TV antenna; TF-100 color film camera; TE-301 live color TV camera; BT-25L1, 25-kW VHF low band color TV transmitter.

Suite: Conrad Hilton, North Imperial

Hitachi Shibaden Corp. of America Booth 200

ISK-70 w/22:1 zoom lens, digital control unit; SK-70 (portable version); FP-3030:1 tube (tri-electrode tube) fully self-contained color portable camera; FP-1212 3 1" Plumbicon camera; FP-1010:3 tube self-contained color camera.

NEW: SK-80

(Continued on page 60)


COMPARE...

CONSIDER...

does your audio console, or the one you're talking about purchasing,

have all these standard features:

CHECK...



The second secon	AMF YES	PRO NO	YOU YES	RS No
Every input channel equipped with preamp 4 transformer coupled inputs per channel Remote start contacts on all high level inputs Modular plug-in amplifiers 2 location cue/intercom system with remote				
talkback 4 selectable monitor inputs 4 programmable speaker muting outputs Step type faders with cue on all channels 15 watt rms protected monitor amp 4 selectable headphone inputs plus stereo cue + 18dBm transformer coupled outputs Telephone grade lever keys Shielded PC board mixing bus for extra RF	হাত্যবাব্যব্যব্য			
immunity Engraved panel markings Extra cost hidden options High purchase price				

Ampro audio consoles are available in 6, 8, 10 and 12 channel rotary or slide fader versions in mono, dual mono, stereo or dual stereo/simulcast configurations. Priced from \$1,995.00 to \$5,275.00.

Ampro also produces a comprehensive line of broadcast

Ampro also produces a comprehensive line of *broadcast* tape cartridge equipment. For complete details, call collect today or write.



Rep inquiries invited. See us at the Show.


AMPRO CORPORATION

850 PENNSYLVANIA BLVD., FEASTERVILLE, PA 19047 • (215) 322-5100 Professional Equipment for Broadcasting Professionals

See us at Booth #812, NAB
For More Details Circle (139) on Reply Card

(comment on page or,

BROADCAST ENGINEERING



WE INTRODUCE THE REFURBISHING SERVICE FOR MARK XV VIDEO HEAD ASSEMBLIES

Send Your Heads to CMC FOR FAST TURNAROUND

- MARK III VIDEO HEAD ASSEMBLIES
- MARK X VIDEO HEAD ASSEMBLIES
- MARK XV VIDEO HEAD ASSEMBLIES
- MARK XX VIDEO HEAD ASSEMBLIES

ONE week turn-around.

- AUDIO STACKS (FOR VTR's) ONE week turn-around.
- VIDEO DISCS & HEADS for SLO-MO . . . IMMEDIATE shipment.

We are proud to claim that in addition to our superior workmanship, our pricing and service are still unmatched in the TV industry.

For more information, please write:

COMPUTER MAGNETICS CORP.

125 W. Providencią Ave. Burbank, Calif. 91502 U.S.A. (213) 843-6674

AIR PROGRAMS INTERNATIONAL

60 Bathurst Street Sydney, N.S.W. 2000 AUSTRALIA TEL: 26-1498

GLENTRONIX, LTD.

160 Duncan Mill Road Don Mills, Ontario M3B 1Z5 CANADA (416) 444-8497

TRANS-ELECTRONIC SYSTEMS LTD.

105 - 614 6th Ave., S.W. Calgary, Alberta T2P 0S4 CANADA (403) 264-3863


For any inquiries other than Canada and Australia, please contact CMC in Burbank, California.

SEE US AT NAB BOOTH 543

For More Details Circle (140) on Reply Card

BULLETIN: The Do It Again at Booth

DON'T MISS THESE 7 GREAT NEW PRODUCTS FROM 3M . . . SEE THEM DEMONSTRATED.



5. NEWAT NAB! D-3000/ D-4000 Animation.



We've added new dimension to the D-3000 Character Generator and companion D-4000 Disc Memory. Now, you have a greater selection of videotype fonts . . . including Upper and Lower Case. Also, selected math symbols, and accented foreign language characters. PLUS, you can animate your display for action. New Animation Mode allows you to play out full frames at a rate of 6 or 12 per second from the D-4000 Memory, creating "video motion pictures".

1. NEW AT NAB! D-8000 Video Art Memory System.

Now you'll be able to present artwork in seconds on a randomselect basis. The D-8000 converts any high-contrast original art into digital format for storage on lowcost diskettes. It changes fixed-

image video inputs from a standard monochrome TV camera into black-and-white or colored video art. Cursor Re-entry Mode allows use of up to 6 different colors. Stores and displays one "full frame" presentation. Use the D-8000 now for high-impact '76 Election Coverage . . . and throughout the year for colorful station logos, repetitive titles, product art, and special graphics.

3. NEWAT NAB! D-2000 Character Generator.

Our new D-2000 Titler provides high-resolution characters at the lowest price ever. Up to

Features internal video mixing and audio interface. Internal fourpage memory. Page format has 24 characters per row, 10 rows


per page. Both 28sl and 20sl Upper Case Fonts. Lower Case Fonts optional. Automatic Centering and Character Edging optional.



"Good News" People 529, NAB '76!

2. NEW AT NAB! 1114 Production Switcher.

We are pleased to announce a broadcast Production Switcher with big unit functions . . . at a small unit price. Provides the most wanted and used features in a convenient single-unit package. Model 1114 is loaded with features. The Preview Channel allows accurate set-up of effects before actual use, including preset wipes and pattern modulation. And, the Key-Over-Effects function gives added dimension to special effects capabilities. Has 100% vertical interval switching . . . 11 inputs . . . 4 bus system . . . 14 special effects . . . many, many more features.



4. NEWAT NAB! RGB Image Enhancer.

Introducing a new, professional quality RGB Image Enhancer from 3M, featuring green-derived enhancement, 3.58 combing, and adjustable noise reduction circuitry. Also features . . . Horizontal/Vertical Enhancement Balance . . . Level Dependent Aperture Equalizer and Coring controls . . . three sets of independent outputs to drive encoder, effects generator, and monitor . . . much, much more.

6. NEW AT NAB! Video Outliner.

Now there's a Video Outliner from 3M. Add sharp, clear outlines to camera or video generated titles and artwork. Built-in video keyer. Features: Full edging; 4-position drop shadow selection; black and white outlining capability; more.

7. NEW AT NAB! Keyer/Colorizer.

New. Companion to our Video Outliner, or can be used as a stand-alone unit. Full Remote Control Panel provided. Features: 5 insert modes; Cut or selectable rate Dissolve control; accepts 3 "push-button selectable" video inputs; unique circuit minimizes "edge crawl" effect.

For complete data visit our booth, write to 15932 Shady Grove Road, Gaithersburg, MD 20760, or Phone: (301) 948-0460.

Mincom Division

3 COMPANY






COMMUNICATIONS TECHNOLOGY, INC.

ROUTING SWITCHERS FOR EVERY REQUIREMENT

THE ULTIMATE

- ★ 20x10 Matrix W/P.S.
- ★ 5 Level Switching 1-Video, 2-Audio & 2-bi-directional auxiliary
- * Breakaway Audio
- ★ Memory CMOS Logic
- * Any Type Control



15X

REPLACES PATCH PANELS VIDEO/AUDIO

- * Plug-in Construction
- * Local or Remote
- ★ 12 or 15 Inputs
- * LED Status Indicators



RX

REMOTE CONTROL FOR BROADCASTERS VIDEO/AUDIO

- * Plug-in Modular Const.
- ★ Momentary Pushbuttons
- * LED Indicators
- ★ Input-Output Amps
- * Obtional Vert. Int.



15X-2

TWO CHANNEL SWITCHER

★ Same features as 15X with one or two outputs



20X-3

THREE CHANNEL SWITCHER


* Same features as 20X with one to three outputs



AX

AUDIO SWITCHER

- ★ Two 24x10 Matrices per frame
- * All Solid State
- ★ Card frame construction
- ★ Plug-in control logic



QUALITY AT A PRICE EVERYONE CAN AFFORD!

Send For Brochures & Price List

COMMUNICATIONS TECHNOLOGY, INC.

3070 LEEMAN FERRY ROAD, S.W. ◆HUNTSVILLE, ALABAMA 35801

205-883-7370

See us at NAB Booth #232

For More Details Circle (160) on Reply Card

Exhibitors

(Continued from page 56)

IGM/Northwestern Technology, Inc. Booth 605

New live operator assist control system (MARC VII), Instacart & Go-Cart random access cartridge handling systems, automation systems, printed logging equipment, memory units, expansion equipment for existing systems, Series 700 computer automation systems.

NEW: Go-Cart cart handler, MARC VII manual assist controller, Series 700 systems.

Suite: NA

Industrial Sciences (ISI) Booth 539

Special effects generators 32 patterns routing switcher.

NEW: Custom audio console.

Suite: NA

Innovative Television Equipment Booth 111

Television camera support dollies, tripods, pedestals, pan/tilt heads, microwave support products and accessories.

NEW: Model ITE-H1 torsion head and ITE-H5 hydro head. Pan and tilt heads designed for ENG cameras for both remote and studio camera control.

Suite: NA

International Tapetronics Corp. Booth 307

ITC will display its complete line of audio tape equipment including single and multi-deck premium cartridge equipment and the PD-II Series of economy cartridge machines. Also at the NAB you will see ITC's professional audio reel-to-reel equipment—both the premium 850 Series and the new economy 750 Series.

NEW: The 750 Series of professional, economy open reel audio equipment, showing both the reproducer and the recorder/reproducer. Also new this year is a totally automatic cartridge splice locater/eraser.

Suite: NA

(Continued on page 62)

BROADCAST ENGINEERING



NAB BOOM

THE BIGGEST ADVANCE OF AUDIO CONTROL IN THE LAST 15 YEARS . . .

Noiseless input select switches. Noiseless audition/off/program select switches. Noiseless audio mixers. Noiseless cue switching. Do these things make any sound at all? You bet! Probably the cleanest sweetest low distortion sound you've heard from any audio console regardless of price. Not only that but these babies are loaded with features that: (1) you will only find in consoles selling for 5 to 10 times more; (2) you'll only find in these consoles . . . period.

From our exclusive illuminated Touch Pad audio select switching, thru our, "better

than a VU meter", solid state light emitting meters, to the highly reliable & noiseless method of audio control. That's not all. Prices that are almost unbelievably low (compared to what you're used to) and performance that takes second place to **none.**

Want more? OK, how about RAMKO's exclusive SIMUL-Q or our full range gain select on each input, or the cue and monitor mute select patch boards on each channel (except the last one). The plug in amplifier cards or the RF suppression.

For More Details Circle (164) on Reply Card

Call collect or write today. You'll find it both an exciting and profitable adventure!

MODELS & PRICES

SC-5M Single Channel, mono .	\$	605
DC-5M Dual Channel, mono .	\$	742
DC-5MS Dual Channel, stereo .	\$	979
DC-8M Dual Channel, mono .	\$	1,199
DC-8MS Dual Channel, stereo .	\$1	1.760

RAMKO RESEARCH

3516 C LaGRANDE BLVD. SACRAMENTO, CA 95823 Telephone (916) 392-2100

Exhibitors

(Continued from page 60)

International Video Corp. Booth 514

IVC-9000 broadcast videotape recorders; IVC-7000 broadcast color television cameras (studio and portable).

NEW: Expanded line of 2-inch and 1-inch broadcast recorders and color cameras. New all-purpose digital timebase correctors.

Suite: Executive House, #3812

Jampro Antenna Company Booth 615

Circularly polarized FM antennas, circularly polarized TV antennas.

NEW: Top mounted circulary polarized television antenna.

Suite: NA

Kaman Sciences Corp./BCS
Booth 809

BCS will display its complete family of computerized traffic and accounting systems for radio and television. In addition, computerized interfaces from BCS traffic systems to automated control room switchers.

NEW: BCS 1100 system which handles AM/FM/TV and automated switching simultaneously.

Suite: McCormick Inn

Kliegl Bros. Booth 508

Lighting equipment (theater, television, film)

NEW: Q-level 2000, Kliegpac 9 (6000W), lighting fixtures.

Suite: NA

KSN, Inc. Suite 402

Time base corrector and character generators.

NEW: Low cost production character generator. Model CG-410.

LENCO, INC., Electronics Division Booth 707

Video terminal and test equipment, digital genlock sync generators, NTSC color encoders, color stabilizing amplifiers, video presence detectors, video, pulse and subcarrier amplifiers, and the modular 300 system, including sync generation, video test signals, pulse and video distribution modules.

NEW: 300 System modular video test signal generators, e.g. multiburst/sweeper, stairstep/ramp generators, etc.

Suite: McCormick Inn, #601

Listec Television Equipment Corporation Booth 306

Television camera mounting equipment.

NEW: Kestrel powered camera crane.

Suite: NA

(Continued on page 64)

CLOCK SYSTEM AUTOMATICALLY SYNCHRONIZED TO NBS

Featuring The New

Illuminated Impulse Clock!

- Designed for darkened TV Studio
- Extremely silent operation, no oil bath required.
- Easy time setting from rear.
- Low voltage and current requirements: 12V at 12ma, 24V at 6ma.
- Easy to follow impulse action.
- Wall, rack and console mounted units.
- Compatible to impulse master clock systems.

Available in 5", 8", 12" and 16" models

Distributor Inquiries Invited

For Further Information Write or Call

CHRONOTRON SYSTEMS INCORPORATED

230 Mineola Blvd., Mineola, N.Y. 11501 Phone: 516-248-4858

See us at NAB Booth No. 629

CASSETTE TIMER



leader in tape timing devices. Complete, ready to plug into your **2850** Cassette machine. Timer with re-cue function standard. Presets optional for editing ease.




VAMCO ENGINEERING

Box 7512 Tulsa, Oklahoma 74105 Call Collect (918) 252-4142, 747-7812

leadership through creativity in design


For More Details Circle (154) on Reply Card



select a
ROUTING
SWITCHER!

- Select for PERFORMANCE
- Select for COST EFFECTIVENESS
- Select for RELIABILITY
- Select for EXPANDABILITY
- Select for RELIABLE SOURCE

Select DYNAIR




SERIES 8100 AUDIO SWITCHER


Frequency Response ±0.15 dB (20 Hz to 20 kHz) — Harmonic Distortion less than 0.15% — Hum and Noise 85 dB below maximum output — Crosstalk better than 70 dB




SERIES 1400 VIDEO SWITCHER

Frequency Response 8 MHz ±0.1 dB, 12 MHz ±0.5 dB — Differential Phase 0.1° — Differential Gain 0.1% — Crosstalk better than 60 dB







Pushbuttons to computers control our switches. Specify from an inventory of standard controls, describe your desired control, or invent your own. Our crosspoints are addressed discretely or with BCD so flexibility comes naturally. **DO IT YOUR WAY!**

DYNAIR ELECTRONICS, INC.

6360 FEDERAL BLVD., SAN DIEGO, CA. 92114 PHONE: (714) 582-9211; TWX: (910) 335-2040



Exhibitors

(Continued from page 62)

LPB Inc. Booth 813

Complete line of studio broadcast equipment including six consoles. One of which will be an operating unit on our DJ8 furniture system.

NEW: A 10 channel audio dual stereo console.

Suite: NA

Marconi Electronics, Inc. Booth 301

Marconi Mark VIII-B automatic studio and portable color television cameras, featuring new HOP pick-up tube; Marc VIII telecine, type B3404; D.I.C.E. all-digital NTSC/PAL/SECAM standards conversion equipment; EEV camera tubes; test equipment.

NEW: Mark VIII-B camera to be shown with new highlight overload protection (HOP) camera tubes; D.I.C.E.—Digital Inter-Continental Conversion Equipment.

Marconi Instruments Booth 301

Automatic TV quality monitor system, TV non-linear distortion analyzer, test line generator and inserter, video sweep analyzer.

NEW: All systems now compatible with NTC #7 recommendations. New data selector Model 2917 for remote interrogation and reporting of TV picture quality.

Suite: NA

McCurdy Radio Industries, Inc. Booth 704

Audio consoles, turntables, intercoms, audio distribution and speaker systems.

NEW: Modular consoles for Mono, Stereo or Quadraphonic applications, tape input switcher (SA141).

Suite: NA

MICMIX Audio Products, Inc. Booth 829

Master-Room series reverberation chambers, LED panel meter with switchable rms/peak indication and switchable dBm/top-of-equipment indication.

NEW: An improved model of the STUDIO B series Master-Room reverb and a brand new 'C' series.

Suite: NA

Micro-Trak Corp.

NEW: Audio control centers—line of four channel stereo & monaural consoles.

Suite: NA

3M Brand Video Products Datavision Video Products Mincom Division, 3M Company Booth 529

Electronic video titling system, video processing equipment, video signal & distribution equipment, video art memory system, Quad DOC, production switcher.

NEW: Model 5110 colorizer/keyer, Model 5120 outliner, D-2000 title generator, Model 1114 production switcher.

Suite: NA

(Continued on page 66)



For More Details Circle (157) on Reply Card

RCA power tubes of the future have a remarkable past: actual lifespans up to 30,000 hours.

Up to 5 kW	24,142 hrs.	21,329 hrs.		
Types 8890 & 8806	12,263 hrs.	19,200 hrs.		
Aural service	16,200 hrs.	14,000 hrs.		
Up to 12.5 kW	10,096 hrs.	10,525 hrs.		
Type 8891	9,402 hrs.			
Visual service				
——————————————————————————————————————	16,600 hrs.	18,300 hrs.		
Type 8807	29,800 hrs.	21,200 hrs.		
Visual service	30,100 hrs.	20,400 hrs.		
Up to 27.5 kW	9,778 hrs.	9,776 hrs.		
Type 8916	7,875 hrs.	13,183 hrs.		
Visual service	10,799 hrs.			

RCA power tubes are at work now in new-generation color transmitters. Proving their value with an excellent combination of high gain, high linearity, plus long operating life.

Documented long life. In the table, you can see actual operat-

ing hours reported by 20 TV stations. That reliability comes from RCA's sturdy, coaxial CERMALOX® construction and thoriated-tungsten mesh filament, which minimize inductances and feed-thru capacitances. So you can use simple, economical broadband circuitry.

In fact, RCA can supply you with the right circuit and cavity to go with the tube you select.

For high performance and proven long life in a wide range of power tubes, there's one thing to do. Contact your RCA Representative. Or, RCA Power Tube Marketing, Lancaster, PA 17604.
Telephone 717/397-7661.





For More Details Circle (158) on Reply Card

Exhibitors

(Continued from page 64)

3M Company, Magnetic Audio/ Video Products Division Booth 527

Complete line of quadruplex and helical videotape, videocassettes and video cartridges. Full line of video accessory items.

Suite: McCormick Inn

3M Company, Mincom Division Booth 529

Broadcast video products including: character generators; production switchers; video animation systems; video processing and amplifying equipment.

NEW: D-2000 high resolution; low cost character generator; Model 1114 small, full function production switcher; D-8000 video synthesized animation system; keyer/colorizer; image enhancer; video outliner and others.

Suite: NA

Microwave Associates Booth 309

STL intercity links at 2 GHz, 7 GHz, and 13 GHz. Long band intercity microwave systems. ENG microwave systems, including MA-13CP miniature camera. Bantam weight TV pickup links, 2 GHz van links and down links.

NEW: Solid State "window" microwave relay system for ENG.

Mohawk Wire & Cable Corp. Booth 212

Television color camera cables, connectors and cable assemblies for most American and European manufactured color cameras.

Suite: NA

Mole-Richardson Co. Booth 114

Studio lighting equipment.

NEW: Type 40310 Teenie-Weenie-Mole

Moseley Associates, Inc. Booth 505

Newly-revised PCL-505 series STL utilizing all solid-state on-frequency RF amplifier in transmitter; Models SCG-9 stereo generator; Series "8" subcarrier system; TRC-15A remote control system; RPL-3 and RPL-4 remote pickup links; DRS-1 digital remote system; DCS-2 digital control system with computer option.

Nagra Magnetic Recorders, Inc. Booth 708

Nagra portable audio tape recorders and accessories.

NEW: Kudelski QGB 10½ inch reel attachment and QTIM tape timer for use with nagra series IV & 4.2 tape recorders.

NEC America, Inc. Booth 316

FS-10B Frame Synchronizer with video compression; FS-12 Frame Synchronizer with video compression; and FS-12 Frame Synchronizer with time base corrector.

NEW: MNC-61 Micropower hand held color camera for ENG system; TT-3000 Helical Scan video tape recorder; NTC-4000 Time Base Corrector for U-Matic VTR.

Suite: NA

Orban/Panasound Booth 909

Spring reverb, dynamic sibilance controller, stereo synthesizer, parametric equalizer.

Suite: NA

Pacific Recorders And Engineering Booth 717

Multilimiter; Multisync.

NEW: Digiclock, Digital stopwatch in the form of a clock. Tape Velocity Indicator, variable speed for MCI recorder.

Suite: NA


Phelps Dodge Communications Company Booth 625

FM antennas, rigid coaxial transmission line, transmission line accessories.

(Continued on page 68)

image enchancer

- Up to 175% enhancement with adjustable H/V balance
- Better than 60 dB signal/noise ratio
- Comb filter provides optimum enhancement without chroma distortion or noise addition
- Models available for automatic or manual enhancement, encoded or RGB inputs, NTSC, PAL or SECAM



DYNASCIENCES

n[@|video products

Township Line Road, Blue Bell, PA. 19422 Tel.: (215) 643-0250 / Telex: 84-6358

For More Details Circle (159) on Reply Card

Our antennas make waves.

350 MHz to 13.25 GHz

At Anixter-Mark, we make a startling array of microwave antennas spanning the frequency spectrum from 350 MHz to 13.25 GHz.

All our microwave antennas are backed by over 20 years experience and innovation. Look at the two antennas featured here. You'll see what we mean.

Rugged center-fed feed antenna

5.9-13.25 GHz. High efficiency, low side lobes. Unique backframe enables this antenna to withstand 125 mph wind (200 KM per hour) with 1 inch (25mm) of radial Ice. Maintains deflection to less than 0.1° in 70 mph (110 KM per hour).


This antenna meets or exceeds EIA Standard

RS-222B and RS-195A. It features a low profile for bulk crating, continuous polarization adjustment and is pressurable to 10 PSI. Feed guy wires included on all models 4 feet and larger. High performance "Shroudome" and ultra-high performance antennas also available.

Low windload antenna

Low profile grid design cuts tower construction cost with no sacrifice in electrical performance. Three-point mounting greatly reduces path alignment and installation time.

Ringbacks further Improve already extremely low wind loading characteristics of Anixter-Mark grid antennas compared to solid dish type parabolics. Frequency range: 350-2700 MHz. Others available on special application. Nest 4 to a crate.



Visit us at the NAB · March 2I-24 · Booth I3O

ANIXIER-MARK

Manufacturers of a Full Line of Point-To-Point Antennas
Microwave ● Two-Way ● Amateur ● CB
5439 W. Fargo, Skokie, III. 60076 / (312) 675-1500
Made in the U.S.A.

For More Details Circle (162) on Reply Card



For More Details Circle (163) on Reply Card

Exhibitors

(Continued from page 66)

Philips Audio Video Systems Corp.

Booth 516

Broad line of video equipment.

NEW: ENG Camera.

Suite: Conrad Hilton, 1600.

Potomac Instruments Inc. Booth 523

AM, FM, TV field strength meters, antenna monitors, RF frequency synthesizer/detector.

NEW: FIM-71 VHF field strength meter.

Suite: NA

Quick-Set, Inc. Booth 312

Complete line of television support equipment. Products for all studio, remote, ENG and special effects requirements. Featuring newly acquired Houston Fearless product line and new line of fluid heads for all camers 5-150 lbs.

NEW: Houston Fearless support line and ENG equipment.

Suite: NA

Ramko Research Booth 919

Audio consoles, turntable preamps, mic line amps, distribution amps, power controllers (remote), studio monitor amps, automatic tape winders, mic/limiters.

NEW: Audio consoles, mic/limiters/ super power amplifiers

Suite: NA

Rank Precision Industries, Inc. Booth 201

Rank Cintel 16 and 33 mm. Flying Spot MK III Color Telecine, with vertical aperture corrector, electronic automatic color corrector, NTSC Encoder, and remote control system; Varotal 30, Varotal VRM, Varotal XX, Varotal 16:1 RM, and TV broadcast lenses.

Suite: NA

RCA Broadcast Systems Booth 500-502-504

Complete ENG systems, studio cameras, film systems, video tape systems, control equipment, audio systems, radio and TV transmitters, broadcast antennas.

NEW: Production model, TK-76 electronic news camera; small mobile TV van.

Suite: Conrad Hilton, Imperial South

Recortec, Inc. Booth 101

Video spot assembler, alternative or cartridge back-up system, VM-1000 helical video tape recorder-a broadcast quality one-inch recorder with omega format, R-MOD for quad video tape recorders-a modification package for constant tension and open the path to full automation.

NEW: Video spot assembler.

Suite: NA

Richmond Hill Laboratories Booth 100

Broadcast video production switchers, broadcast television automation, video signal test generators, video and pulse distributors, amplifiers, unipulse system, video clamping and equalizing amplifiers.

NEW: Three new video production switchers, models VPM 3112, VPM 3220 and VPM 3320. New test generator STG 700, new unipulse encoder and decoder.

Suite: Ambassador

Russco Electronics Mfg. Inc. Booth 551

Turntables, broadcast audio consoles, rack mounted audio amplifiers, phono preamps, speakers, microphones, headsets, tone arms.

NEW: Ten channel consoles-both stereo and mono.

Suite: NA

Scully/Metrotech Division of Dictaphone Booth 817


Professional audio tape recorders with AC and servo capstan drives. Mono, stereo and multitrack. Broadcast

(Continued on page 141)

FCC
 Type-Accepted
 and Certificated
 \$325 Price

\$275 Without Receiver

- Stereo or Dual Balanced-Line
 Switching Included Not Optional or Do-It-Yourself
- Complete System
 In a Single 3½ Inch
 Rack-Mount Unit
- CMOS Digital
 Comparator Decoder
 No Tuning-fork Filters
- Socket Mounting of All ICs and Relays
 - Full Testing and 2 Day Burn-in of Every Unit
 - Five Year Parts,
 One Year Labor
 Warranty




THE BET EBS-100
It's Not Too Late
To Change Your Mind
Call or Write Today



Broadcast Engineering Techniques

(401) 861-6007 206 Doyle Av. Providence RI 02906 THE LEAST **EXPENSIVE** EBS **ENCODER** -**DECODER** -RECEIVER SYSTEM INCLUDES **FEATURES** THE **EXPENSIVE SYSTEMS** DON'T.



This golf cart-like apparatus is used to transport ENG equipment from the van into the news scene. Below the camera is the CCU. The 34-inch tape machine is at the bottom.

FILM VS. ENG

A state of the art comparison



Weighing 13 pounds when fully equipped, this 16mm sound-on-film camera can produce newsfilm under low light levels and some conditions not presently recommended for ENG equipment.

By Ron Whittaker

Now that the dust has started to settle just a little on the whole film-to-ENG issue, it is a good time to do a critical examination of the ENG and film approaches to TV journalism and try to determine the relative strengths, weaknesses, problems, costs, etc. of each system.

Although the "PR value" associated with the quick change to ENG was a real competitive advantage in many markets, some stations have now found that they are suffering with some hardware-related problems that they did not expect...problems that could have been avoided if they had made some different decisions on the purchase of equipment, and problems which have resulted from trying to make ENG equipment suddenly "do everything".

What follows will be a look at ENG and film from the standpoints of (1) the relative technical quality under different conditions, (2) the strengths and weaknesses of each

approach in actual on-the-job situations, (3) the time, steps and problems involved in preparing ENG and film stories for broadcast, and (4) the total costs represented by each approach.


Relative Technical Quality

Although technical quality is very important—especially in highly competitive markets—it is certainly not THE most important consideration in TV news. (We would be hard pressed to find a TV news director that's still working who refused to run the VTR of man's first step on the moon or the film of the assasination of Robert Kennedy because the technical quality of these pieces fell short of standards.) Just getting the story is the first consideration—"something" is better than "nothing" on an important story. After you have the "something" under control, you worry about such things as how fast you can get the story on the air, the

technical quality, etc.

But, for now, let's pass up these other issues and examine the relative technical quality of the 16mm film and ENG broadcast images. It is an interesting fact that although the information-carrying capacity of a high-quality 16mm image is 50 times greater than the resolution or detail capability of video in the U.S. system of television, this same film when presented by television will appear slightly inferior to a good quality image from an electronic camera. When translated to video, film (even with image enhancement) will appear somewhat "softer" and less "crisp" than video from a high-quality news TV camera. The reasons for this are complex, but they have to do with such things as frame-by-frame image stability and light "scatter" in the telecine optics.

It is important to note that the above comparisons are based on the highest quality video cameras—



A plus for ENG is that news deadlines can be extended by about 30 minutes. Of course, if the feed is live, you're into real time coverage. This does make special demands on the newsroom team.



After returning to the newsroom, the reporter plays back
the news story and records a
time code on the tape. The time
code makes it possible to recall
important segments without again
viewing the entire tape.

ENG cameras in the \$35,000 plus price range. As the price goes down, so does the quality, and the superiority of the video cameras over enhanced 16mm film is lost with many of the less expensive portable video cameras.

Certain quality-related problems can be encountered with video cameras which do not plague the film camera image. Image "lag" and "smear" can be especially noticeable and objectionable with some video cameras when movement is combined with high subject matter brightness values and low overall illumination.

As electronic technology improves, the problems of image lag and smear will undoubtedly disappear, along with another problem associated with some ENG cameras right now—difficulties in handling low light levels. Although it is difficult to make direct comparisons between electronic and film cameras because of differences in


equipment and acceptable quality standards, the light sensitivity of film is presently recognized as being about three F-stops greater than ENG cameras. Ektachrome 7240 is commonly force-processed to an EI (ASA) of 500, which makes possible newsfilm in as little as 10 footcandles of light. Although the time will undoubtedly soon be here when ENG equipment will produce high-quality video under such low light levels, as things now stand, most ENG equipment requires more light to meet quality standards.

One of the undesirable consequences of this extra light requirement has been a return to the straight-on, single-light-beside-thecamera technique to provide an acceptable illumination level for interior shots. This has amounted to a giant step backward in news-production quality. The result is reminiscent of newspaper photography in the early '50s (and before),



www.americanradiohistorv.con

For More Details Circle (165) on Reply Card



At the ENG console, complex audio and video edits can be accomplished quickly and with single-frame accuracy. Here a reporter assists in the assembly of a news story she covered only 30 minutes before.

and the films by amateur filmmakers with their 8mm cameras mounted on light bars (which, by the way, has also become passé with the advent of existing light super 8 equipment in the early '70s). Except for emergency situations, such as an accident at night where there is no existing (natural) light, this single light approach (for reasons too numerous to go into here) just represents poor photojournalism and poor television production. This problem will undoubtedly solve itself in the coming months and years as new, more sensitive video cameras become available. Even now, some of the better video cameras will handle most brightly-lit interior situations without too many negative consequences.

One last thing should be mentioned to complete the quality comparison between film and ENG. With film—especially with the reversal film approach generally used in news work—dirt and scratches will quickly distract from quality.

With ENG, such equipment as dropout compensators and the socalled "super time-base correctors" will cover a multitude of "flaws" along the line and produce very clean, crisp video.

On-The-Job Differences

The very significant advantage that ENG equipment has over film, of course, is in its immediate VTR playback and "live" coverage capability. Unlike film, there can be an immediate confirmation of content and quality, and adjustments can be made on a moment-to-moment basis by the cameraman on the scene, or by a news director monitoring at the studio. This makes for fewer content and quality surprises all along the line.

ENG equipment is still considerably heavier and more conspicuous than film equipment, however. In sensitive news situations such as civil disturbances, the obvious presence of conspicuous TV equipment has sometimes resulted

in the creation of news, instead of just the reporting of it. Small 16mm and professional super 8 film cameras are comparatively inconspicuous and can generally shoot in existing light.

Since "top-of-the-line" 16mm sound cameras, such as the Frezzolini LW-16 and the CP-16, weigh only about 13 pounds completely equipped, they can be hand-held by one person. And ENG crew making a tape of a story (the vast majority of ENG assignments are not "live", of course) must carry something like a 13 pound camera and a 22 pound backpack, and maneuver with a 31 pound VTR unit. To this you generally need to add the weight of a VTR battery pack or power supply. Typically, a golf cart-like apparatus is used to move the equipment around at the scene of the news event. (It has been said that 16mm equipment is portable, but high-quality ENG-VTR equipment is, to date, only **mobile.**)

Under adverse conditions, film has an advantage over present ENG

Tells of a world beyond Time Base Correction

See it with 20 20*

*A new signal processing system from Microtime

NCTA-Booth 528

Microtime 1280 Blue Hills Avenue Bloomfield, Ct. 06002 (203) 242-4242 TWX 710-425-2390

MICROTIME

For More Details Circle (166) on Reply Card

equipment. In contrast to film equipment, some ENG-VTR equipment cannot be used in high humidity, rain or snow. Problems also develop when ENG equipment is used in temperature extremes. (A Frezzolini will operate on its battery pack at temperatures down to -10° F.; a CP-16, down to $+10^{\circ}$ F.) Since vibration and motion will adversely affect recordings with most VTR equipment (and sometimes camera alignment) problems can also develop when this equipment is used in moving vehicles.

Two more on-the-job differences should be mentioned before leaving this section. ENG equipment takes a bit of a warm-up period before it can be operated. Even though this is only about 30 seconds, there are occasions in covering news when this seems like a very, very long 30 seconds! Once a film camera is loaded, you can instantly be "making pictures" each time you squeeze the trigger.

And finally, a big plus for ENG.

After microwave paths are established in a city, stories can be beamed back to the studio from various locations, without the timeconsuming and expensive need to regularly return with exposed film. The stories can either be microwaved directly back to the studio for taping as they are shot, or a VTR tape made "on location" can be beamed back later at a more convenient time, or after a simple and direct microwave path is found.

Preparing The Story For Broadcast

In a way, both film and ENG-VTRs have to be "processed" before they can be aired. With film, this involves a rather complex and expensive chemical processing phase. With video tape, the image 'processing" is accomplished by a totally electronic time-base corrector (TBC). The latter, being a real-time, on-line type of procedure, can be accomplished either as the story is transferred to a quad reel-to-reel or cart tape, or as the story is fed directly into a switcher for an on-air feed.

Time-base correctors—especially the so-called "super time-base correctors"-can accomplish some minor miracles in the area of general picture quality: improvements related to color stability and corrections, signal-to-noise ratio, velocity compensation, video compression, etc. However, as some stations have found out, they have their limits. Probably one of the biggest problems in this area has been with edits. One major station lost over 50 percent of its ENG stories until some major equipment bugs were traced down and corrected. In this case the stories simply could not survive the postedit transfer to quad carts. The state-of-the-art requirements for ENG are still rather demanding, and anything less than first class equipment and operating procedures may result in problems.

Although the processing procedures for film are much more involved and time-consuming, the problem areas are much easier to recognize and deal with. This is primarily because film has been in use for so many more years. However, film processing also has its problems, splices that come apart in the processor, chemical contamination, etc. As things now

There are



providing titling...graphics for television production

CHYRON

Electronic Graphics System,

unquestionably the most advanced and versatile system available today...the one system that offers the highest character resolution and do-it-yourself capability for unlimited type font and logo preparation, plus more features than any other TV graphics equipment.

CHYRON III Electronic Titling System,

VISIT US AT NAB BOOTH #501 B.


At a moderate price CHYRON III provides more flexibility and quality than higher priced units, including unlimited font and logo interchangeability, large message storage capability, and character resolution exceeded only by CHYRON II.

For complete information write:

TELESYSTEMS DIVISION OF CHYRON CORPORATION

223 Newtown Road, Plainview, New York 11803 • 516 249-3296 851 Burlway Road, Burlingame, California 94010 • 415 348-1144

When the FCC approves a 750kW power level for 12 clear channel AM stations to better serve the people of the United States, EIMAC tubes will do the job.





stand, both the film and ENG approaches contain a degree of risk along the way from camera to screen. When all things are considered, the amount of risk for each approach is about the same, assuming each is used within the parameters of recommended procedures.

The Editing Phase

In the editing phase of news preparation, the film and ENG approaches each have major strengths and weaknesses. ENG editing by computer can be many times more flexible and creative than film editing. Highly sophisticated and exact edits with single frame accuracy are possible with VTR stories, combining, when necessary, a multitude of video and audio sources and special effects. Edits and effects can be previewed and adjusted as many times as necessary with computer editing before final effects are decided upon. With film you are typically working with the actual reversal

footage that will be projected. A-B rolls are not quite as easy to set up and "pull off", and complex video and audio marriages are more difficult.

The editing of film, on the other hand, does not demand complex and expensive equipment. Film editing is much simpler and more direct. With a set of rewinds, a film viewer, sound reader, splicer and a three-by-four foot table space, you are in business. The editing of film (as things now stand) can be accomplished faster than VTR editing; at least for simple, straightforward news pieces. What puts film 20 or so minutes behind in a race to "air" is processing. In the time a piece of film takes to be processed, a typical video tape story can be edited for broadcast.

Relative Costs

And now we arrive at the bottom line of the whole ENG-film comparison—how much does each cost?

The initial investment for a typical, good-quality ENG unit is somewhere in the neighborhood of \$85,000. This assumes \$40,000 for a camera, \$13,000 for editing units, \$10,000 for a TBC, and \$20,000 for a microwave link. Obviously, the total can vary greatly, depending upon needs and preferences. For a large broadcast operation, a typical figure for getting into the ENG ballgame is \$200,000. If you are willing to accept the quality of modestly-priced equipment, it is even possible to "go ENG" for as little as \$7,000.

Turning to film, a first class film unit will cost about \$25,000. This assumes \$10,000 for a top-of-the-line SOF camera, \$11,000 for a processor and \$4,000 for editing and associated equipment.

Obviously, as far as initial costs are concerned, film has a tremendous advantage over ENG. However, once the initial investment is made, the cost advantage starts to move rapidly toward ENG.

For film and processing, 16mm film costs about 11 cents a foot, or about \$15-\$20 for average news stories (shot at a 2:1 ratio). Because video tape is reusable, the cost for ENG recording is a fraction of this—probably little more than \$1 per assignment under average (3/4 inch) tape life conditions. With such a cost difference, an \$85,000



Scully's new 280B family of innovative audio tape recorders has a list of improvements and features that won't quit. As a result, Scully can handle any recording assignment you have. Just take a look.

- Optional DC capstan servo
- Speeds to 30 in/sec.
- Transports up to 14" reels
- New direction sensing control logic
- Functionally illuminated controls
- 1/4" full-track to 1-inch 8-track recorders
- Innovative low-noise electronics
- Common components for interchangeability

- 14" reels for 30 in/sec. mix-downs
- Variable Speed accessory with L.E.D. exact speed read-out

Scully makes it easy for you, including sales and service which is available from over 200 distributors throughout the world. For all the facts, write, Telex or phone.


Scully Metrotech Division of Dictaphone

475 Ellia Sanast

475 Ellis Street Mountain View, California 94043 (415) 968-8389 TLX 34-5524

Scully and Metrotech are trade marks of Dictaphone Corporation, Rye, New York

CICLOTOCIA BROADCAST CARTRIDGE A 2 BY CAPITOL



Think of it as a car.

Because, in a sense, it is like a car. All of the major components are assembled to get you from point A to point B. With efficiency and precision. For example, the constant-force, foam pressure pad assures unvarying head to tape contact over the life of the cartridge. The positive, non-slip brake mechanism locks the tape, rather than the hub, assuring accurate cueing and timing. And, to assure you of premium performance, each cart is individually tested—100%—for wow and flutter,

electrical output, tension, and other properties. And because we manufacture the entire package—from tape to packaging—we can assure you of the highest possible quality control.

The Audiopak A-2 by Capitol Broadcast Cartridge.
The car you drive probably isn't as reliable as the A-2.

AUDIOPAK® A PROFESSIONAL PRODUCT MANUFACTURED BY THE SAME PEOPLE THAT MAKE AUDIOTAPE, AUDIOFILM, M AUDIODISCS® AND THE LEARNING TAPE™ BY CAPITOL®

audiopak BY CAPITOL

Capitol IM CAPITOL MAGNETIC PRODUCTS A DIVISION OF CAPITOL RECORDS INC. 1750 NORTH VINESTREET LOS ANGELES CALIFORNIA 90028

For More Details Circle (32) on Reply Card

investment in ENG equipment can be recovered in a few years.

One important thing needs to be stressed in relation to comparative tape-film stock prices, however. With film you have a permanent record of the news event which can be filed away and dug out at any future time for use in news "flashbacks", documentaries, or just to hold as an archival record. As long as the news tape is not "controversial", there is no present FCC regulation that would forbid the station from immediately reusing (erasing) the video tape. And, of course, regular tape reuse would offer maximum economy. But, it is indeed disquieting to want to "flash back" to an important news story and find upon checking that the tape now contains the 14th annual meeting of the Sopchoppy Daffodil Society!

A somewhat more prudent (but less economical) approach is to dub all news tapes onto a monthly master tape, as they appeared on the air in their final edited form. This will not give you the "out takes" that were originally shot, but

it will provide you with a second or third generation record of what was broadcast. The original tapes are then reused until they accumulate 100-200 passes. The great savings at this initial point encourages the shooting of both more "footage" and more stories. With more to select from, news editors should be able to improve the quality and quantity of local coverage. Some stations, in fact, have found that they have increased on-air "actuality footage" by 20 percent since investing in ENG equipment.

Turning to other expenses, repair costs (parts and labor) on equipment can be figured at about 10 percent a year on equipment with "moving parts", and at about two percent a year for totally-electronic equipment. Using these formulas, the upkeep on ENG and film equipment would probably be about the same.

The greatest expense, of course, will be labor or wages. The long-term advantage of ENG can be quickly erased if extra people are required. In going to ENG, a part-time or full-time man will be

saved in the area of film processing. In some cases this just amounts to a shift in position, however, if an extra person is needed to handle the portable VTR and/or microwave equipment. Because this area will represent your greatest long-term expense, you should check over the possibilities carefully here—especially if there are union implications involved.

In Summary...

ENG offers some important advantages over film when good ENG equipment is used under the proper conditions. As pointed out, however, film still has a number of important strengths. These strengths are primarily related to an ability to handle tough lighting and weather conditions...conditions that are often encountered in the TV news business. As things now stand, the best approach is to use both ENG and film, and in this way not sacrifice any news-gathering ability. In the highly demanding and competitive business of television news, all available technology needs to be used to its best advantage.

A.L.C. OR MANUAL MIXING

ON NAGRA SYNCHRONOUS RECORDERS



NAGRA SNN MINI

automatic level control for CLOSE UP DIALOG RECORDINGS

PREPARE YOUR PRODUCT FOR THE FUTURE SL STEREO SYNC RECORDER

NAGRA SL STEREO

for MUSIC OR SOUND EFFECTS
THAT HAVE VALUE IN
STEREO RELEASE



United States Distribution — Service — Sales

NAGRA MAGNETIC RECORDERS, INC.


19 WEST 44th STREET, ROOM 715 • NEW YORK, NEW YORK 10036 • (212) 661-8066

Southern California Sales and Service RYDER MAGNETIC SALES CORP. 1147 North Vine St. Hollywood, California 90038 (213) 469-6391
SEE NAGRA AT NAB BOOTH 708

For More Details Circle (33) on Reply Card

Another TFT first in AM Modulation Monitors

HE EXTENDE



Extends coverage potential

TFT's new, competitively priced Model 753 precision broadband AM Modulation Monitor has a full complement of quality TFT features, for maximum transmitter modulation to the outer limits of coverage and for proof-of-performance measurements. The Extender is in a class by itself.

- Linear phase filter
- Built-in meter attenuator
- Modulation meter and peak flashers calibrate automatically over a ±40% carrier level change
- Digital flashers for 100% negative modulation peaks and 125% positive modulation peaks
- Built-in -100% and +125% calibrators
- FCC Type Approval No. 3-234.

Extends Monitoring Capability

By adding the new TFT Model 754 Preselector. broadcast stations, consultants, and regulatory agencies can pre-program any four AM stations via thumbwheel switches. Then, they can precisely monitor, off-the-air, any one of the four. Exclusive features include:

- · Frequency synthesized digital tuning
- Digital read-out of carrier frequency deviation (optional)
- Unique IF filter design for optimum off-the-air monitoring.



SEE THE NEW TFT EXTENDER AT NAB, BOOTH 619

For a free demonstration, call or write TFT at the address below. In Canada: Orange County Assoc., Winnipeg, Manitoba.



TET TIME AND FREQUENCY TECHNOLOGY, INC. 3000 OLCOTT STREET, SANTA CLARA, CA 95051 (408) 246-6365 TWX No. 910-338-0584

For More Details Circle (34) on Reply Card

81



WBRE-TV Cuts Into Random Film Handling Costs

By George Andresky, Chief Engineer, WBRE-TV, Wilkes-Barre, Pa.

cartridge projector, the first frame can be shown as a freeze-frame on the monitor at the control board. The center monitor shows the first frame of a Seven-Up commercial. The projector is cued from the board. However, a one-second delay has been built in because the projector reaches speed almost instantaneously.

With all the talk we hear today about electronic news gathering (ENG) and video-tape, film is still an important part of our operations at WBRE.

We originate a tremendous amount of film, both for news and for location production of commercials. Also, about half of the commercials, promos and public service spots we receive are on film.

We are not rushing to convert our news capabilities to videotape. One reason is that our president, David Baltimore, see problems with TV cameras, so we are moving ahead cautiously at the moment. We have four sets of film editing equipment for the news department which provide sufficient capacity to get our news film edited and on the air.

Film projectors also cost less to purchase and operate, considering head wear and general maintenance overhead for videotape equipment. Our film projectors require maintenance, too. We clean the gates regularly and spend some time in adjustments, but in the long run, it is much less costly on a day-to-day operating basis.

We also do very little conversion to videotape cassettes. Most national spots that come in reel-to-reel on videotape are used that way. The exception is when we get a spot which is used frequently. Then, we transfer it to a videotape cassette for convenience.

For local commercials, we do all of our location shooting on film, usually using Kodak Ektachrome MS film 7256 which is processed in our own Pako EK 28 processor. Our art department usually films the commercials, and they are set up to do simple opticals, including double exposures and wipe-on lettering. When we need special effects, we dub the film to videotape for post-production.

Random Access Film

Film is not without its problems, though. One problem has been the handling of random film—especially national commercials, promos and public service spots. Like most stations, we have been splicing each spot on long reels, in the order it appears in the schedule. Anything that had to be repeated was held for a run-separate machine.

David Baltimore had been talk-

Tells of a new world of broadcast automation

Discover Digitrol 2

Microtime NAB-Booth 709

Microtime 1280 Blue Hills Avenue Bloomfield, Ct. 06002 (203) 242-4242 TWX 710-425-2390

MICROTIME


For More Details Circle (35) on Reply Card

ing with people at RCA for several years about the need for a randomaccess projector. When they announced the RCA TCP 1624 cartridge projector, we were one of the first stations in the country to install one. The projector was delivered last April. We put it on an island, which was installed a year earlier with a multiplexer, a TK28 camera and a TP66 projector. We knew the projector was coming, so we left a port open for it. Within a week of its arrival, we were using the new projector.

Film Spots

Within three months, we put about 700 commercials, promos and public service spots in film cartridges. As new film becomes available, it is automatically loaded into cartridges.

The unit consists of two selfthreading projectors. These operate independently and are controlled by internal logic. Most of the time, each projector is loaded with a film cartridge, and both are in "ready" condition-stopped on the first frame of the film. The automation operation activates the button for the first film and the correct projector is put on the air. After It greatly simplifies using film the film is finished, the other spots. The idea is to handle random projector can be activated while the film as an individual package first one automatically rewinds its contained within its own cartridge. film back into the cartridge, de-



One of the first production models of the RCA TCP 1624 was installed at WBRE-TV for use with promos, commercials, and public service spots.

For multiple runs of a spot, or schedule changes, the carts can be removed and repositioned.



NAB BOOTH 507

507 SPANNES SHINES

CARTERUGGED ONES

OVER 40 MODELS TO CHOOSE FROM

SERIES 2000

- Simple, basic, economical cart machines.
- 16 dBm output, excellent frequency response, and all the other features to satisfy the needs of many studios.
- Plug-in modules for record and audition allow field conversion.
- Two cue tones, provisions for remote control and telephone interface standard.
- Mono and stereo models for A, B, and C size carts.
 Also dual rack mount for A and B size carts.
- Unprecedented 18 month warranty.

SERIES 4000



- The ultimate single deck cart machine from SPOT-MASTER — with features and styling for the most discriminating broadcaster.
- All the same solid features as the SERIES 3000 with added standard features — microphone inputs, dummy head in record position (playback models) and many others.
- Additional optional features include an internal fault/splice detector, diagnostic metering and encoding/decoding circuits for use in automation systems.

SERIES 3000



- Auto release deck massive, quiet operating air damped solenoid and direct drive motor.
- Low power consumption less than 45 watts keeps your tapes cool.
- PHASE-LOK III head bracket minimizes stereo phasing problems.
- · Exceeds new NAB specifications.
- Automatic metering of both record and playback.
- Balanced transformer output with FET switching for paralleling machines.
- Remote control provisions and socket standard.
- Full range of mono and stereo models for A, B, and C size carts.
- Many options and accessories available.

SERIES 5000

- Modular design with fold down front panel and slide out direct drive decks.
- Auto release decks massive, quiet air damped solenoids.



- Separate electronics for each deck on 2 PC cards.
- PHASE-LOK III head brackets minimize stereo phasing problems.
- Available in 3 and 5 deck, mono and stereo models with optional record amp for 3 deck units.


BROADCAST ELECTRONICS INC.

ALSO AUDIO CONSOLES AND STUDIO ACCESSORIES

— A FILMWAYS COMPANY— 8810 BROOKVILLE ROAD, SILVER SPRING, MD. 20910 PHONE: 301-588-4983 ◆ TWX: 710-825-0432

CABLE: SPOTMASTER

For More Details Circle (36) on Repty Card



The "library" for film and tape carts was designed by WBRE president David Baltimore. The film racks move across the racks for video tape on tracks (note racks in center of photo). Baltimore estimates the storage capacity has been increased by two or three times.

Though it usually is operated from the board, the cart projector can be oper-

ated from its own panel.

positing it in its designated slot in the tray. Then, it goes on to the third film, loads the cartridge and cues the film.

When we set up the schedule for the day, it is easy to pick out and load the cartridges into the tray in order and mount the tray on the projector. If there is a schedule change, we just change the position of the cartridges in the trays. The same goes for repeats of the same commercial. After it has run, we either shift its position or take it out and move it to another tray.

Cart Advantages

The advantages are obvious. Each cartridge holds up to three minutes of film, but most of ours are 10, 30 or 60 seconds in length, so we have additional capacity if we need it. Now we can run all of our



Harris MW-5 5kW AM transmitter has PDM* going for it.

Harris' MW-5 transmitter needs only two tubes for 5,000 watts provides 125% positive peak modulation capability for a louder sound—has

plate efficiency approaching 90% for lower operating cost. All this possible because of Harris' patented Pulse Duration Modulator* (PDM) also featured in our top-selling 50,000 watt MW-50 transmitter. For complete information write, Harris Corporation, Broadcast Products Division, 123 Hampshire Street, Quincy, Illinois 62301.



HARRIS



COMMUNICATIONS AND INFORMATION HANDLING

random film on one unit instead of using two or three projectors.

In addition, we get better air quality. It is obvious that the less film is handled—or videotape, for that matter—the less chance there is for it to pick up dirt, or be scratched or damaged. We put the film in the cartridge once and leave it there. There's only one splice, and no rehandling. We're already seeing improved performance and longer life out of our film.

The ease of handling with the new projection unit has changed some of our thinking about local origination. We used to dub all of our local commercials to videotape to avoid splicing. Then we filed the originals. But now we put the film commercials right into the cassettes—splices and all—and save the time and money we used to invest in transferring to videotape.

We have had to compensate in our roll times somewhat with the new film projector. We previously programmed two pre-roll times. There was a five-second roll time for videotape lockup and a onesecond with the film projectors. With the newer VTR machines, videotape is coming down to one second for lockup, bringing it to about the same time as the reel-type projectors.

But the RCA TCP 1624 cartridge projector comes up to speed almost instantaneously, with no distortion. Since our reel projectors take one second to get up to speed, we have to live with that standard for the time being. We have programmed the cartridge machine to delay one second after the pulse comes from the automation.

We feel that it is a specialized machine, though, and we use it entirely for random-access film. We still maintain two reel-type projectors for longer lengths of film, such as syndicated programs and news.

But Not For News

We don't use the projector for news, because news film usually is for one-time broadcast. Once the film is spliced, it is rare that the show changes. So news film really isn't random, and we can save the time it would take to load it into cartridges by splicing and running it in the conventional projectors.

Having the random film in cartridges also gave Baltimore another idea. We used to store the film in cardboard storage boxes on shelves. We had four shelves for film and one for videotape cartridges, and the place was quite cluttered. He designed a set of racks which fit against the wall. The videotape racks are fixed, and the film racks roll on a track. To get to the videotape cassettes, we roll the film racks back and forth in front of them. Now we have two to three times the storage capacity in less space than we needed

We expect that film will be an important part of our operations for a long time, and so will the RCA TCP 1624 cartridge projector. We average running about 80 cartridges a day on it, and we expect it to pay for itself in time and money savings.

And just as important, it releases personnel from a routine, repetitive splicing job to more productive duties.



Jamieson No.1 in TV!

Why is the Jamieson Processor No. 1 in TV?
The best answer is from someone who owns one.
Someone you know owns a Jamieson. Probably a lot of people you know. Why not ask them about it? The best way to get an unbiased appraisal of its performance.
Or ask us ... we'll be more than happy to tell you about

the Jamieson Processors and give you references.

JAMIESON'S ADVANCED DESIGN TECHNOLOGY FEATURES

- Film advance virtually tension-free. The demand top-overdrive film transport uses no clutches, floating rollers or film sprockets.
- · Smaller machines take only half the floor space.
- Solution volumes reduced 15 times over open-tank designs.
- Temperature in primary solutions is controlled to an accuracy of a few hundredths of a degree.
- The eliptical shape of the tube protects the film and provides high induced turbulation.

•J=	
JAMIESON FI	LM COMPANY of Kreonite, Inc.
6911 FOREST PARK R PHONE: 214-350-1283	OAD • DALLAS, TEXAS 75235 • TELEX: 73-0932

Please send information on Jamieson Processors and a list of some users.	
Name	Title
Firm	Phone
Address	City
State Zip	JAMIESON FILM COMPANY 6911 Forest Park Rd. Dallas, TX 75235

See us at NAB Booth #408

For More Details Circle (38) on Reply Card

Here is the New angēnieux 42 x continuous zoom lens

we call it the "cover all" lens



and we will be proud to show it to you at the NAB Convention

BOOTH 304

angēnieux

corporation of america

1500 OCEAN AVE., BOHEMIA, N.Y. 11716 • (516) 567-1800

1500 OCEAN AVE., BOHEMIA, N.Y. 11716 • (516) 567-2424 / 13381 BEACH AVE., VENICE, CALIF. 90291 • (213) 821-5080

For More Details Circle (39) on Reply Card

A New Approach To FM Peak Control

By Dennis Ciapura

The FM Volumax is a universally recognized piece of signal processing equipment because it represents a pretty good attempt at having one's electronic cake while eating it too.

Because of the pre-emphasis employed in FM broadcasting, control of high level high frequency audio energy has always been a sticky problem and many schemes have been devised. The heart of the FM Volumax is a circuit called the Dynamic Frequency Compensator (DFC), which is really a voltage controlled treble cut circuit. The older 411 series of Volumax produced by CBS before the audio line

was taken over by Thomson CSF, contained a single DFC which operated between 400 and 15000 Hz in exact symetry with the standard 75 usec pre-emphasis curve to prevent premphasized treble bursts from overmodulating the transmitter.

The beauty of this system was in




Fig. 1 Simplified block diagram of the 4101/4111 Volumax.





Fig. 2 Typical total harmonic distortion as a function of frequency.



Think of the possibilities that the new 1410 Series offers when planning a facility. This series has two color standards, three sync generators and four test signal sources to choose from. They can be teamed to do almost any job that you want done.

Think of the signals you need.

Perhaps you need a master sync generator with a ± 1 Hz color standard, or perhaps with a ± 10 Hz color standard.


It may be that you do not want sync pulse outputs at all, just test signals such as color bars, linearity test signals and convergence patterns.

Then again you might want a genlock master sync generator plus one or more test signals. These system requirements are among the many that the 1410 series generators can be combined to deliver in one compact package.

The 1410 is flexible so that we can easily configure a generator to meet your needs now. How about the future? That's easy. Just order the plug-in card or cards for the signal you want and install it yourself

Write us, or use the reader service card, to get more information about the 1410 Series. See the 1410 at NAB-76 along with presentations on operational measurements presentations in the Tektronix Measurement theatre.

For Maxe Details Circle (40) on Reply Card








THE INFLATION FIGHTERS

World Video Color Monitors

CR 6700 17" Rack Mount Color Video Monitor. Designed for broadcast applications. All Controls mounted on front panel including pulse cross, underscan, R-G-B switches, screen and drive controls, dual inputs, internal-external sync and keyed back porch clamp. Utilizes only 15 3/4" of vertical rack space. Price: \$1,700.00



RK 6700 17" Rack Mount Color Video Monitor. A high quality utility monitor requiring only 15 3/4" of vertical rack space. Dual inputs, keyed back-porch clamp, internalexternal sync, and blue gun only. Controls conveniently mounted on front pan-Price: \$1,195.00



CR 6210 12" Rack Mount Color Video Monitor. Designed for broadcast applications. All controls easily accessible on front panel. Dual inputs, pulse-cross, keyed back porch clamp, underscan, R-G-B switches, screen and drive controls, internal-external sync. Convenient plug in modules for ease in servicing. Price: \$1,350.00



CB 6210 12" Cabinet Color Video Monitor. Convenient carrying handles for portability. All other features the same as the CR 6210. Price: \$1,350.00



CDR 9900

CDR 9000 Single or Dual Rack Mount 9" Color Video Monitors. Utilizing only 8 3/4" of vertical rack space. CDR 9000 equipped with mounting provisions for a WFM or vectorscope. Controls conveniently mounted on front panel. Dual inputs, underscan, internal-external sync, blue gun only and keyed back-porch clamp provided. Price: CDR 9000 \$ 995.00 CDR 9900 \$1,850.00



World Video also manufactures CCTV Color Monitors and Receiver/ Monitors in screen sizes from 9" to 19". Information available upon request.

All World Video color monitors are 100% solid state and utilize singlegun CRTs.



WORLD VIDEO, INC.

P. O. BOX 117, BOYERTOWN, PA., 19512 PHONE 215-367-6055

Booth No 214 N.A.B. SHOW

For More Details Circle (41) on Reply Card

the fact that a high frequency peak could be handled without causing a loss of level in the lower midrange and bass portion of the audio spectrum. The only disadvantage of the earlier system was the loss of the top octave if some strong energy in the 5 kHz region caused the DFC to roll-off from the top down. Even though a surprising amount of processing could be attained before a loss of brightness could be detected, the limit placed on the compression level by the loss of highs forced many users to operate at a moderate average level for fidelity's sake.

A major evolutionary change came when the 4010 FM Volumax was introduced. The DFC was retained for control up to about 5 kHz, but a high frequency clipper was used for the 5 to 15 kHz band. This modification allowed for a higher compression level before a loss of highs became apparent because the midrange and treble could be handled separately, each limiter section having attack and release times optimized for the relatively narrow band of frequencies that it had to handle.

Although this improvement was a step in the right direction, the waveform distortion produced by the high frequency section was found to be objectionable by some stations looking for minimum distortion components for their audio chains.

Thomson-CSF Laboratories has just introduced a third generation FM Volumax dubbed the 4111, which the company believes to be an incorporation of the best features of both of the earlier versions of the Volumax line. The new unit employs DFC's in both the mid and high frequency sections and is designed to be virtually distortion free at any frequency and any reasonable level.

Figure 1 is a block diagram that pretty well describes the theory behind the 4111's operation. The frequency control stage passes the entire audio band but only acts as a peak controller at low frequencies. Its attack and release times are selected to provide less than 1% distortion at 50 Hz, with faster peaks being passed on to the following stages. The active filters send the low and mid-range audio to the mid-range processor and the

TANDBERG 10XD bridges the gap between consumer and professional tape recorders.

Meet the world's first and only 10½" reel tape recorder that operates at 15 ips and combines Tandberg's unique Cross-Field recording technique with the world-famous Dolby* B system. Result: A guaranteed minimum signal-to-noise ratio of 72 dB, measured on a 4-track machine using IEC A-weighting. Simply put, the 10XD completely eliminates audible tape hiss!

Here are some of the many sophisticated features that make the 10XD the finest tape recorder Tandberg has ever

- 3 speeds: 15, 71/2, 31/4 ips. Electronically selected
- 3 motors; Hall-effect capstan motor
- 3 heads; plus separate bias head
- Electronic servo speed control
- including photo optics

· Peak reading meters

- · Direct transfer from playback to record (flying start)
- · Ferrite playback head with symmetrical balanced output for hum cancelling purposes and differential playback amplifier.

Remote control and rack mount optional. Pitch control by special order. For a complete demonstration of this remarkable new advance in stereo tape recording, see your Tandberg


 Electronic logic mode controls. Electronic balanced microphone · Echo, sound-on-sound, editing, A and B tests TANDBERG Tandberg of America, Inc., Labriola Court, Armonk, N.Y. 10504

*Dolby is a trademark of Dolby Laboratories, Inc.

For More Details Circle (42) on Reply Card

A. Allen Pringle Ltd., Ontario, Canada -





The new Volumax tested and described in this article.

high end to the high frequency processor. Although the mid band DFC passes low and mid-range audio, it only controls the mid band peak level, and its operation is optimized for that band. The high frequency DFC is very fast and handles only the high end. The audio band is reassembled in the summation network and amplified by an output line amplifier.

Final safety limiting is via zener diodes at the output of the line amp. In theory, it looked like this might be some kind of limiter, so, we decided to take a look at one of them to see how they worked out in practice. We conducted a three part test series consisting initially of checking the unit out in the lab to see how it stacked up against the manufacturer's specs, a comparative test with musical inputs and finally, a field test on the air under actual broadcast conditions.

Comparing Specs

Figure 2 gives what the manufacturer says is typical distortion vs. frequency for the levels indicated. This is the operational performance that could be expected if the unit were operated with 6 dB of low frequency compression and the program input had a flat output vs. frequency characteristic. As you can see from the chart, the preemphasis results in 23 dB of limiting at 15 kHz. This is really a pretty tough test for an FM limiter because musical recordings seldom exhibit that much energy at the high end and a proof would be made with an input signal of diminishing level vs. frequency.

Our test unit was very close to the typical performance shown in Figure 2 and far exceeded the 1% distortion spec listed by the manufacturer. As a matter of fact, we had to use a low frequency spectrum analyzer to accurately measure the distortion at the high end because it's down in the noise level when the unit is operated below the limiting threshold.

Figure 3 gives the response and

distortion data that we measured under less demanding circumstances. The distortion run was made at the threshold of limiting and the frequency response was checked at 30 dB below. These conditions more closely simulate what the unit would do under proof of performance test conditions.

We found the 4111 to be essentially a piece of wire with gain when operated below the limiting threshold and very nearly distortionless at relatively high compression levels. With steady state tone inputs, the frequency response is the inverse of the 75 usec. preemphasis curve, but the release times of the DFC's are so fast that the losses last only as long as the offending peak persists, so, the subjective loss of brilliance is amazingly small, as we shall see in the next phase of our tests.

The I.M. distortion was also extremely low; just over 0.1% with 60 and 7000 Hz mixed 4:1. The signal noise ratio was 76 dB, which once again was better than the specification. The 4111 uses a balanced differential input stage and no input transformer and would get a little noisier (about -67 dB) when operated in a strong TV/FM RF field; however, a transformer would be an easy addition if required and most stations could benefit from the cleaner transformerless input as shipped.

The front panel meter indicates the low frequency limiting values, so care must be taken in interpreting the meter readings when setting up the unit. If, for instance, a 10 kHz input signal was applied to the unit and the level increased until the meter just began to show gain reduction, the unit would be compressing 14 dB because the meter is referenced to the threshold of limiting below 400 Hz.

Comparative Tests

For the next phase of our test series, we rigged up a switching system that would allow us to If you are involved in the business of professional tape recording, we have an interesting proposition for you.

A couple of silent partners who will work day and night, assure excellent results, let you maintain full control and be unfailingly reliable.

They are the new Revox A700 tape recorder and the Beyer DT109 microphone/headphone combination and both of them come with excellent credentials.

The Revox A700 is the most recent addition to the Revox line which already includes the critically acclaimed A77, a machine which was decribed by the Stereophile Magazine as "unquestionably the best tape recorder we have ever tested."

Of the new Revox A700, "Tape Magazine" says, "We could find no fault with the Revox A700 and fully accept the maker's claim that it bridges the gap between the home and the recording studio." Listening to tapes made on the new Revox A700 is a revelatory experience. Tape hiss is virtually non-existent. The music seems to emerge from a background of velvety silence and at 3¾ ips the absence of extraneous noise is truly startling.

Silent Partners

As for the Beyer DT109 microphone/headphones, they are in a class by themselves. Highly sensitive and capable of withstanding immensely high sound pressure without overload or distortion, they feature modular

construction with a unique multi-pin plug in lead allowing separate wiring of left and right headphone channels, independently of the microphone.

Add featherweight comfort and effective ear sealing together with a wide frequency, true cardioid, broadcast quality microphone specially designed to work under extremes of temperature and humidity, and it is easy to understand why the DT109 has become so popular for live remote broadcasting, studio, film, television, disc jockey and language laboratory applications.

Together or separately, our remarkable silent partners could open you ears to recording and broadcasting possibilities you never knew existed.

Your nearest Revox professional/ Beyer dealer will be delighted to arrange an introduction.

We think once you have met them you will wonder how you ever did without them

without them.

| Piease tell me where | Name | State | Zip | Zip | State | Zip | State | Zip | State | Zip | State | Zip | Zip | State | Zip | Zip | State | Zip | State | Zip | State | Zip | State | Zip | Zip

Illustrations may contain optional extras.

Revox Corporation in USA: 155 Michael Drive, Syosset, N.Y. 11791






Fig. 3 Distortion and frequency response data for he 4111.

instantly compare the 4111 with the other 411 Volumax and then compare either one to wire straight through with program inputs from tape and record.

The input levels were gradually raised so we could compare each of the units to the original program input and gauge the loss of highs as the input was raised. With the front panel meters swinging the length of the green or "normal" area on their gain reduction scales (about 6dB of low frequency limiting) the 411 was audibly duller than the 4111 with most program material containing appreciable treble energy. The 4111 sounded very close to the original program input with a slight loss of highs apparent in a direct A-B comparison with very bright music. With the input level below the low frequency threshold of limiting (no compression below 1 kHz) both limiters sounded virtually identical and both sounded very close to the original program material. With very clean records and tapes, the new 4111 has a very transparent sound and is audibly better than the older 411.



THEY'RE EVERY MICROPHONE YOU EVER WANTED.

We've taken the latest advances in electret technology one step further. By combining them with advanced acoustic technology to make professional condenser microphones more portable, more practical and less costly. A lot less.

The secret is our "family" concept.

One common powering module (K2U) serves three different compact heads: omnidirectional (ME20), cardioid (ME40) and shotgun (ME80). Thus, for most studio and location situations, it's no longer necessary to carry three different microphones. Or pay for three different complete units. Each head contains its own microphone capsule and "front-end" electronics, all exactly matched to

OMNIDIRECTIONAL HEAD \$55 00 list.

CARDIOID HEAD

condenser models in all but the most critical applications.

The Powering Module, runs on a single 5.6V battery, or phantom-powered directly from your recorder, preamp or other auxiliary equipment. A miniature LED monitors power and indicates proper voltage. Connection to preamps, mixers, etc. is balanced* low-impedance via a 3-pole Cannon XLR connector. Best of all, of course, is the great versatility. In a matter of seconds, you screw on whichever head you need and go!

If all this sounds good to you, call or

its own precisely-controlled acoustical environment. Resulting in the

first electrets with response and directionality to rival our famous RF

If all this sounds good to you, call or write us. We have a lot more good things for you to hear.

Powering module and heads available separately.

Prices subject to change without notice.

POWERING MODULE \$79.00 list.

\$108.00 list.

ZESENHEISER
ELECTRONIC CORPORATION

10 West 37th Street, New York 10018 (212) 239-0190
Manufacturing Plant: Bissendorf/Hannover, West Germany

*Unbalanced version also available

For More Details Circle (45) on Reply Card




Fig. 4 Scope photo shows limiter output after pre-emphasis with musical input.

How About Clipping?

Next a preemphasized scope was connected to the limiter output to see how much clipping, if any, was taking place with an actual program input. The setup described in Part 2 of the transient response series in BE, January 1976 was used. Figure 4 is a photo of the preemphasized output of the 4111. Note that there is no flat-topping visible, which indicates that almost no peaks are reaching the safety limiters. The DFC's are very effective rise time limiters because of their roll-off type characteristic.

The 411 did show clipping with the same input level and program material.

All in all, the audio quality of the 4111 seemed to be top notch and quite comparable to state of the art audio gear in general, so, the next step was to find out if it could provide the overmodulation protection that is really a limiter's raison d'etre.


Overmodulation Protection

The 4111 was inserted into the program line of the main transmitter of WLAK-FM atop Sears tower


in Chicago for about ten days to test its operation in the field under actual broadcast conditions. Resistive pads were used to isolate the limiter's output from the transmitter input and no installation problems with respect to matching were encountered.


The unit provided the same overmodulation protection as the older 411 and since a higher input level could be used for the same subjective spectral balance, a higher average modulation level was obtained. With the "beautiful music" format in use at WLAK a 2 to 3 dB increase in average level, no apparent loss of fidelity resulted from substitution of a 4111 limiter instead of the older 411. After many hours of extended listening over the next ten days, there was never any feeling that a limiter was in the circuit, which is as it should be. Stations with a rock, country or MOR format may choose to operate the limiter at a higher input level and get an even higher average modulation level if a slight loss of high-end response and midrange balance can be tolerated.






How would you like 3 New Ampex VTR's for about \$30,000 and 3 of your old VTR's?







Sound like a good deal? . . . Well, we have one almost as good. AFA will completely recondition your present Ampex VR-2000, VR-1200 or other similar caliber VTR's for about the same price . . . and they will be as good as new!

What we do is more like rebuilding.

We are not simply talking about clean-up and adjustment. We'll tear each unit down in our facility, and replace every part that is subject to wear with genuine Ampex parts. We also replace any part which is not an original Ampex part. We realign the electronics and refinish each subassembly, fully test the entire system . . . and deliver them to you just like they came from the factory . . . maybe better!


If you've considered enthanasia for your "old" VTR, forget it.

Vintage VTR's have a "second" life at least as good as their first. The usual problem results from catchas-catch-can maintenance... the "fix it for now" syndrome, which is caused by "all-around" technicians who have to keep all your production equipment on the air. They do their best but they don't have the time to pamper a "prima donna" VTR.

Don't put off 'til tomorrow what you must do today!

Even if you could do the job as well, in-house . . . will it ever really get done? If you could have . . . wouldn't you have done it already? Can you afford not to have each VTR operating at peak efficiency at all times? The answer is simple.





If it's worth doing, it's worth doing right.

AFA has years of experience reconditioning Ampex VTR's... we're specialists. We have the special tools, replacement parts and can if necessary, manufacture certain unavailable parts to specification. We are reliable, financially secure and can supply references. After all, we will be stripping your \$100,000 VTR down to its lock washers.

After we deliver your reconditioned VTR's, we set you up with an inhouse periodic maintenance program which will assure the continued "peak performance" of each machine.

How much is unreliable equipment really worth?

Let's face it . . . you purchased the "best" because in your business, quality and reliability are essential. AFA can restore the reliability and original quality to your vintage equipment at a fraction of your

For More Details Circle (47) on Reply Card

initial capital investment. Better and cheaper than buying used... and yet you'll end up with VTR's that are practically brand new.

AFA also purchases previously owned VTR's in almost any condition. However, when we sell them to particular customers who require reliable back-up or additional units, they are in pristine condition . . . as yours will be.

Call us today for additional information, technical consultation, or a quotation. We service customers anywhere in the U.S.




A.F. Associates, Inc.

20 Booker Street Westwood, N.J. 07675 (201) 664-3000

March, 1976

With LED's in-circuit, visual proof of what's happening is obvious at a glance.

By Elmer T. Schorle Plymouth Meeting, Pa.



As every technician who has traced the intermittents that occur as a switch is beginning to malfunction knows, some very unusual things can happen when an electromechanical device thinks one thing is happening electronically, when something else has taken place mechanically. The more complex the equipment is, the wilder and stranger the effects can become!

I have been using a method of ascertaining the operation of the micro-type switches in Ampex ACR-25 Cassette VTR's in my care which gives an immediate visual indication of their performance, and at the same time renders a quick overall view of machine functions to spot trouble areas.

LED's To The Rescue

On the circuit boards using the data sent by the switch operation I have mounted small red LED's, with each labeled to designate what has taken place as they illuminate. Thus, at a glance I can tell that a "Cassette is in Transport", or the "Carriage is in Transport", or that an extractor "Claw is up", or down, or that the "Carousel is pinned". Each of these items occurring at the proper time in sequence is necessary for the ACR-25 to operate correctly, and switch intermittents are one of the most encountered forms of trouble. With the LED, I have a visual confirmation that the switch worked, or didn't, if perhaps the LED was on without the switch lever being actuated, and can eliminate sources of trouble possibilities at a glance.

LED Mounting

To mount the LED's in a professional manner, I used a ½-inch wide strip of the same type of material that the original PC board is made of, (usually pirated from discarded jumper modules) cemented to the front edge of the module using the data sent by the switch in question.

Each LED is inserted into a snug hole made near the edge of this faceplate, and labeled to designate what has occurred as it lights. They

(Continued on page 104)

BROADCAST ENGINEERING

AUTOMATE YOUR VTR



NEW PERFORMANCE WITH R-MOD

- FRAME ACCURATE ELECTRONIC TIMER
- RELIABLE REPLAY OF CUE SIGNAL
- AUTOMATIC STOP AT TAPE ENDS
- CONSISTENT FASTER LOCKUP TIME
- SHUTTLE AT CONSTANT TENSION
- HANDLING OF TWO HOUR REELS
- RELIABLE FOR REMOTE OPERATION
- INCREASED HEAD AND TAPE LIFE

R-MOD is a reel servo modification kit which consists of new DC reel motors, servo tension arm assemblies and electronic tape timer. It is easily installed in the field to provide your quadruplex VTR with superior tape handling. R-MOD rapidly pays for itself in less head wear, longer tape life and significantly more effective use of your VTR time and operating personnel.

Unless you want to buy the vacuum chamber buffered VTR, R-MOD at only \$8500 is the next best transport on the market. Before buying a new VTR, investigate the improvement R-MOD will make on your present VTR.

Want more details? Recortec is as close as the telephone on your desk. Call us toll free on (800) 586-1586. (Outside California only)

RECORTEC, INC.

777 PALOMAR AVE., SUNNYVALE, CA 94086

TEL: (408) 735-8821

TWX: 910 339 9367



DFM-3K-A THREE KILOWATT FM BROADCAST TRANSMITTER

- **FCC Type Accepted**
- Direct FM Solid State Exciter
- Color Coded Wiring
- Designed for Stereo and Multiplex
- Silicon Rectifiers
- Grounded Grid Power Amplifier
- **Designed for Remote Control**
- No Neutralization Required
- Ultra Linear Wide Band
- Only Two Tubes
- 3.5 KW Capability

Sintronic Transmitters have been installed in over 27 countries. For over 10 years, they have performed optimally under severe environmental conditions. All Sintronic Transmitters are conservatively designed and constructed. Quality components are used throughout.

Sintronic manufactures a complete line of AM and FM broadcast transmitters to satisfy every broadcast requirement. Detailed information and comprehensive product brochures on request.

Sintronic Corporation is a subsidiary of Singer Products Co., Inc. Integrity and dependability since 1937.



Main Office and Plant: 705 Haverford Ave., Bryn Mawr, Pa. 19010 (215) 525-3700

Administrative & Export Offices:
One World Trade Center, Suite 2365, N.Y., N.Y. 10048

(212) 432-1400

See us at NAB, Booth #713
For More Details Circle (112) on Reply Card

Chapter Reports

(Continued from page 14)

technical quality control throughout the Industry, will gladly supply them to stations, production houses, agencies, etc., who originate programs or commercials.)

Ken Steininger, special projects engineer, then took his turn, and spoke about the NBC radio network and its News and Information Service. The Schafer 903 Automation System, used in conjunction with the Chicago WNIS, was discussed in detail, and brochures were made available to all attending.

Chapter 28: Milwaukee, Wisc.

With April 15 just around the corner, several SBE Chapters have held meetings on the FCC's new EBS two-tone ruling, and Milwaukee Chapter 28 was no exception. On January 27, members met in the Radio City Auditorium at WTMJ to hear speakers Joseph Wu and Terry Loyd from TFT discuss these standards. Mr. Wu, assisted by TFT Applications Engineer Loyd, gave a slide presentation on the design, manufacture, and computer testing of the TFT two-tone receiver.

Chapter 32: Tucson, Arizona

The regular meeting of Chapter 32 was held Wednesday, January 28 at KGUN-TV. The primary business for the evening was to select a slate of candidates for local elec-

tions, scheduled to be held in conjunction with the National election of officers.

Chapter 36: San Diego, Cal.

The first meeting of 1976 for Chapter 36 provided an interesting program on digital information. Leroy Bellwood, director of engineering of Channel 10, presented "A New Digital Cassette Training Course" that is available from the University of Michigan. This course is pertinent to technical skills required in the commercial and non-commercial world of television.

Mr. Doug Curé, Tektronix Information Display Group, spoke on "The Distribution of Digital Information on Video Distribution Systems." His presentation was very informative, and led into a discussion of changing technology and concepts which we will all be confronted with in the years to come.

The Pacific Telephone Company also joined the program with a report on the problems and techniques in tying remote locations to a central switching or distribution point for audio and video.

Chapter 37: Washington, D.C./ Northern Virginia

The Audio-Visual Center at American University was the site of Chapter 37's meeting on January 28. The tentative schedule for the February meeting features Eric Small's presenting a paper and demonstration on the Optimod, a topic which should be of interest especially to FM and TV broadcasters.

CHAPTER 38—EL PASO, TEXAS. Frank Jordon, Chairman, KDBC-TV, P.O. Box 1799, El Paso, Texas 79999, (915) 532-6551.

CHAPTER 39—TAMPA, FLORIDA. George Shideman, 1561 S. Jefferson Avenue, Clearwater, Florida 33516 (813) 442-9133.

CHAPTER 40—SAN FRANCISCO BAY AREA. Robert B. Daines, Secretary/Treasurer, Telemet, Western Regional Office, 1261 El Curtola Blvd., Walnut Creek, California 94595, (415) 938-8887.

OKLAHOMA CITY, OKLAHOMA. Josh Socolof, Acting Chairman, KKNG(FM), 110 N.E. 48th Street, Oklahoma City, Oklahoma 73105, (405) 525-5595.

ORLANDO, FLORIDA. John Weyrick, Chairman, 5765-F Kingsgate Drive, Orlando, Florida 32809, (305) 857-3729.





Handling all this is a lot easier. When you can take this for granted.

The new Electro-Voice DS35 Single-D Cardioid.

Here's help with one of the toughest jobs...a live remote with simultaneous house sound reinforcement. The DS35 takes some of the load off.

Greater gain before feedback:

Check it out yourself. Work your system with a DS35. Compare the level you can get before feedback with that of any competitive mike. One big reason is the flat response provided by our unique Volumetric™ laminated diaphragm-designed with the aid of laser holography.

Cleaner highs, wider response:

The exclusive diaphragm design assures linear motion to reproduce more accurately, especially at frequency extremes. And state of the art port design means the best off-axis response of any single-D microphone.

More boost to the bass:

Used close up, the DS35 supplies lots of the bass boost(proximity effect) some entertainers want.

Stronger and quieter:

The rugged steel case withstands toughest abuse. The pneumatic shock mount

For More Details Circle (49) on Reply Card

absorbs hand and cable noise. Integral blast filter squelches "P-popping". So in the studio, out live, or taping, the DS35 just goes on working. You can take it for granted. And it's protected by the famous E-V Professional Microphone warranty.

DS35...\$90.00 Suggested Resale Net. Slightly Higher in Western States.

Electro-Voice®

a **gulton** company

Dept. 361V, 638 Cecil Street Buchanan, Michigan 49107

March, 1976




Fig. 1 A portion of the ACR-25 schematic of logic board A16/17 showing wiring of LED's.

(Continued from page 100)

are placed at intervals determined by available "real estate" on the PC board module to accept the two LED leads, and a 1K ¼W resistor, which is routed to the nearest plus 5v trace.


The cathode of the LED is connected to a piece of solid insulated wire, and routed to tie to the appropriate connection on the board. A sample hook-up of three LED's I have on one card is shown in the accompanying picture, with

how it looks wired in the schematic diagram.

Ampex has the switches going to ground potential to signify verification of the function, though if other methods or voltages are switched, appropriate LED circuitry can be made to fit the needs. This method can easily be expanded to verify other switch actions, and can save hours of guessing when tracing intermittent gremlins in equipment. Any place a switch is used to tell

circuitry something actuated it could be given a LED indicator, but I think it should be left to areas that could cause the worst conditions. If you had too many LED's to look to in times of trouble, it could become as confusing as it is to the electronics.

Note—Many brands of LED's would be adaptable, though I used Chicago Miniature Lamp Co. CM4-23 series, which are readily available in our area.



mi automatic TV monitoring sets free the engineers

Time was when highly trained transmission engineers had to waste their brains (and their time) watching a battery of waveforms and pictures — instead of concentrating on work more worthy of them.

Now the TV monitoring scene has been transformed. For TF2914 Insertion Signal Analyser, TF2915 Data Selector together form THE FIRST COMMERCIALLY AVAILABLE AUTO-MATIC TRANSMISSION MONITORING SYSTEM. In conjunction with a test line signal generator and inserter (such as mi TF2913), it will automatically cycle through the measurement of all the important parameters of the test line

signal from five separate inputs. Comparison with pre-selected limits is continuous, and an 'out of limits' fault can initiate executive action by automatic switching to standby, with remote alarm indication and simultaneous data transmission of fault location. Up to 24 parameters can also be measured manually by means of push-button selection and a self-contained digital voltmeter. Versions are available for all standards including the N.T.C.#7. Systems are now operating in ten countries. Applications include broadcast monitoring, common carriers and satellite operations. Call mi and discuss your application.

SEE US AT N.A.B. — BOOTH #301


MARCONI INSTRUMENTS

100 STONEHURST COURT, NORTHVALE, NEW JERSEY 07647 . TELEPHONE: (201) 767-7250 . TWX: 710-991-9752

Small Market Radio Workshop

Part 1 of a continuing series for engineers working in small market radio stations.

By Jim Purcell



There's a lot more to engineering than meter reading. The author, shown here, opens part one with some rather basic hints. Later parts will be dealing with specific problems.

Management Highlights

Most small market station owners don't have the technical knowledge necessary to properly evaluate the performance of their technical help. This article will not only give station management some insight in this area but also will help the station owner appreciate some of the problems his technical personnel face so that he can give them the support that often makes the difference between a well-run station and the other kind.

Newcomers to broadcast engineering are faced with a real dilemma today because so many stations have a small engineering staff. First Phone operators have a difficult time obtaining supervised training. Many new operators accept positions with small market stations and find themselves the only licensed personnel on the staff. With little or no experience, it can be a real hassle knowing what is necessary to keep a station operating efficiently and properly. It's also difficult for the new operator

to know where to turn when stumped by some technical problem.

Having been through the trial-byfire that is small market engineering, I feel obligated to share some of what I've learned while trying to cope with problems common to small market stations. In addition, I'll also try to share ways the new operator, who is trying to break into broadcast engineering "by the seat of his pants", can help the owner of his station realize that the broadcast engineer can be a valuable member of the total broadcast team rather than simply a millstone which the Federal Communications Commission has hung around the broadcaster's neck.

What You See Is What You Get!


How many broadcasters today can still recall the days when engineering excellence was taken for granted at most stations. Today even some larger stations are victims of less-than-professional engineering practices. And smaller stations are frequently victimized by a succession of inexperienced operators, most of whom have no greater claim to fame than the fact that they have obtained that First Phone Ticket.

So it's a good idea for a new operator to determine as soon as possible just what shape his station is in with regard to engineering. Perhaps you should even go so far as to put your findings in a report so that management will understand why any future changes you make or suggest are necessary.

Here's what to look for during your initial inspection:

TECHNICAL FILES (if any): Should be neat, orderly, complete. Filed in proper location, that is, where the equipment is located—studio manuals at studio, transmitter manuals at transmitter site, etc. I'll discuss later some of the materials that should be in your technical files.

STATION CLEANLINESS: Check inside equipment racks, con-



McMartin Industries, Inc. • 4500 South 76th St. • Omaha, Nebraska 68127 • (402) 331-2000 • Telex 48-485

For More Details Circle (51) on Reply Card

soles and transmitter, especially air filters, for excessive accumulation of dirt. These factors may indicate the necessity for thorough cleaning of all equipment which will also be discussed later.

EQUIPMENT OPERATION: Using equipment manuals as a guide, make sure all equipment operates as it should, including correct meter readings control settings and that all controls function as they should. Make certain all personnel know how to properly operate equipment. Poorly trained operators may shorten equipment life. If improper operation has continued for any length of time, this may indicate that repairs will soon be due on the equipment in question.

SPARE PARTS INVENTORY: An adequate stock of replaceable parts like tubes, fuses, panel lamps, transistors, resistors, capacitors, etc. should be on hand so that necessary repairs can be made quickly. Later we'll discuss in detail the job of reordering a neglected parts inventory.


The Buck Stops Here

You're the one now responsible for the proper maintenance of your station, so start right away to correct any deficiencies you may have noted during your inspection. Any improvements you can make will bring you steps closer to a more dependable, better-sounding station. In the process you may also be able to minimize breakdowns. The technical files are a good place to begin your improvements.

Here's what your files should contain:


- 1. Maintenance Manuals for every piece of equipment in operation, filed where the equipment is installed. Missing or incomplete manuals may be replaced by writing to the manufacturer. More completely detailed manuals, such as those for transmitters may cost something to replace. And manuals for older equipment may not be available.
- 2. Logs And Records filed by date as far as two years back—at least.

- a. Maintenance logs containing data required by FCC. I usually also keep a maintenance notebook, more detailed than that required by the FCC on maintenance logs. Each piece of gear has a section in the notebook devoted to it and all maintenance is recorded. This is valuable when trouble-shooting because it not only suggests solutions to remedy repeated symptoms but a continued repetition of a certain fault may suggest a different remedy to correct the real cause, or a deficiency in design that should be corrected.
- b. Frequency reports from monitoring service...filed by date.
- c. Proof of performance data. It's best to keep all proof data even though the Commission requires they only be kept for two years.
- 3. FCC Regulations: Keep your copy up to date and study it often. You're expected to know the law.
- 4. Broadcast Services Information: Names and addresses of firms that paint towers, repair monitors, rebuild tubes, etc.
 - 5. Technical Literature:






For More Details Circle (52) on Reply Card



GOODBYE, TRIPOD.



For More Details Circle (54) on Reply Card

- a. Tube & Transistor manuals.
- b. Engineering practices manuals. (NAB Handbook is excellent, though quite expensive.)
 - c. Engineering charts and tables.
- d. Engineering magazines including those non-broadcasting electronics magazines. I usually cut miné up after a few months and file articles according to category, i.e. "Remote Control Circuits", "Transmitter Data", etc. This makes my file of magazine articles an extremely valuable source of information.

6. New Equipment Literature: It pays to know what's available on the market and how much it costs. If a piece of equipment is continually causing trouble or is the source of down time, it's about time to replace it. You may have your own replacement brand preference, but you'll look more professional to approach management with a proposal on what to buy based on your files. You are supposed to know. And the more you know about broadcast equipment, the more management will come to rely upon you for key purchasing decisions.

So, your new equipment literature is an important file. And you can keep it well stocked by using the Reader Service card in this magazine to get the information you need.

You don't need to keep an elaborate filing system. Just one where you can easily find what you need. For example, it would be enough to file equipment by categories. At the front of this kind of file, you should keep an uncut, unmarked copy of **Broadcast Engineering's** Buyer's Guide. It contains all the active manufacturers, their addresses, telephone numbers, and several hundred categories of equipment.

You'll gradually discover additional things you may want to add to your files. The important thing is to use them. Equipment manuals, for example, can be an important source of operational theory and trouble-shooting data. Study manuals often and become familiar with the equipment. Familiarity cannot be stressed too much as an element in good engineering.

Equipment manuals also contain information that can be posted in strategic locations to aid in equipment evaluation. Typical meter



RCA Vistacons NOW!

The RCA-4593 and 4594 extended red Vistacons are now available as direct replacements for the XQ1023 and XQ1025. They complement the RCA-4592 which is directly interchangeable with the XQ1020. For improved resolution, an extended green version is also available.


The RCA square design eliminates "pin cushioning," and makes for easier, faster registration with better tube-to-tube uniformity.

All RCA Vistacons have nonbrittle base pins, and microphonicfree construction.

Use RCA Vistacons. You'll get the competitive value and the service you've a right to expect from the pioneering leader in TV camera-tube technology. For complete information call your RCA Representative or your RCA Camera Tube Distributor.

RCA Distributor & Special Products Division, Cherry Hill, N.J. 08101 Phone (609) 779-4327.





Flash Technology Corporation of America continues to lead in innovation and technology in the flash beacon field. Our new FTB-205 Beacon reduces the number of enclosures required (each beacon contains an integral power supply within its enclosure eliminating the need for a separate unit), it is smaller in size, and lighter in weight — all important considerations when mounted on a structure.

Since we offer a self-contained unit, the number of enclosures to be mounted on the structure is equal to the number of beacons required by the FAA.

Only two input power connections plus two connections for control and monitoring are required for each beacon.

The FTB-205 Beacon continues to offer previous Electro Flash features:

- A unique optical system with a sharp lower beam cutoff to reduce downward radiation (Pat. No. 3,737,645).
- An effective extended flash duration during nighttime operation (Pat. No. 3846750).
- Only 2 wires are required for all control and monitoring functions.
- Contacts available to drive a remote failure alarm.
- 3 operational intensities for 24-hour operation; 200,000 effective candelas daytime, 20,000 twilight, and 4,000 for nighttime operation.
- Lowest power input requirements.
- Regional service available.

Over 50 operational systems on tall structures from Canada to Florida prove the reliability and quality of the ElectroFlash Beacon System.

We would be pleased to assist in your design planning for specific installations and provide additional information on our FTB-105 or 205 series beacons.

Do It With Confidence

See us at NAB Booth #322

FLASH TECHNOLOGY

CORPORATION of AMERICA

111 LOCK STREET, NASHUA, NEW HAMPSHIRE 03060

TEL. (603) 883-0521

For More Details Circle (56) on Reply Card

readings may be determined from the manual and posted near each meter so that you can tell at a glance whether a piece of equipment is operating as it should.

In some cases, I actually mark the meter faces at the point where the needle should be. If the meter is used for two or more modes of operation or as a multi-meter, I locate numbers on the meter face corresponding to the meter switch position.

High Priced Stock Clerk?

If you found that you have an adequate supply of spare parts on hand, you can skip on to the next section. However, don't make your judgment too hastily since having replacement parts is important in getting the station back on the air after equipment failure.

Your inventory should include all parts which frequently need to be replaced, such as tubes, fuses, transistors, lamps, time delay relays, resistors, capacitors, rectifiers, etc. Equipment manual parts lists will guide you in preparing an inventory list. Parts should be grouped according to type, such as all tubes together, etc. Then list them in alphabetical/numerical order. Beside each part number indicate the quantity you've decided to stock (see below). You may want to keep a separate quantity number for each location, i.e. transmitter and studio locations. Beside the number indicating normal inventory quantity, you can maintain a running inventory of actual "on hand" quantities.

Whenever a part is used it should be replaced as soon as possible so that you won't find yourself caught without spare parts. Whenever I use a tube I remove the end of the carton containing the type number and use these for reordering.

Deciding on the quantity of each part to stock will depend on such factors as budget, how each unit will affect the station's capability of staying on the air legally, and the cost of down time compared with the cost of the replacement part. Always keep at least half as many of each tube type on hand and at least one of each transistor. Fuses, on the other hand, should be stocked in quantity, a whole box for every individual fuse used. Of

The Neve remote console. \$7,950* No need to compromise!



The Kelso model 8301 is a fully professional transportable sound mixing console of extremely compact dimensions, designed for high quality mono or stereo recording and broadcast production. This 10 channel console of the highest technical performance and built to exacting quality standards is ideal for location recording, mobile units or the smaller studio. Each console is supplied with a comprehensive technical manual and a spare parts kit.

It features 10 input channels for line or microphone level, equipped with LF and HF controls with shelving curves to a maximum of ±18dB boost or cut, and a 3 frequency high pass filter with 18dB/octave roll off. Pan potentiometers on all inputs. 2 main group outputs which can be combined to provide 2 independent mono outputs. 2 auxiliary outputs with separate level controls on each channel. Cue (AUD) facilities with a headphone monitoring output.

Stereo recorder playback lines provided for monitoring.

2 speaker monitoring outputs with push button source selection.

2 VU meters with source selection.

A five frequency line-up oscillator.

Talkback and routing keys are provided, with a console mounted microphone.

Transformer inputs and outputs are balanced and floating, terminated on XLR or compatible connectors.

*FOB Bethel, Connecticut Plus applicable sales taxes.

The 8301 is generally available from stock. Optional facilities as well as custom modifications available. The Kelso is one of more than 20 stock console designs available from Neve. For more information on stock and custom consoles, contact:

See us at NAB Booth #715

Rupert Neve Incorporated, Berkshire Industrial Park, Bethel, Connecticut 06801 Tel: (203) 744-6230, Telex: 969638
Rupert Neve Incorporated, Suite 609, 6255 Sunset Blvd., Hollywood, California 90028 Tel: (213) 465-4822
Rupert Neve of Canada, Ltd., 2717 Rena Road, Maiton, Ontario L4T 3K1, Canada Tel: (416) 677-6611
Rupert Neve & Company Ltd., Cambridge House, Melbourn, Royston, Hertfordshire, SG8-6AU England, Tel: (0763) 60776
Rupert Neve GmbH, 6100 Darmstadt Bismarckstrasse 114 West Germany, Tel: (06151) 81764
For More Details Circle (55) on Reply Card



course keep plenty of common value resistors and capacitors on hand as well as an adequate supply of hand tools. Another factor to keep in mind is that older equipment may sometimes be kept from becoming obsolete by ordering replacement parts that may become difficult to obtain later. This especially includes costly transformers, etc.

Really Taking Charge

If the work so far described sounds like a lot of puttering, pay attention! Here's the real stuff of broadcast maintenance-Preventive should vacuum the building thor-Maintenance. Ignored by some operators as too time consuming, this phase of the operator's job is actually the most effective in maintaining good performance from the station. Unfortunately, I've seen stations where routine maintenance had been so long neglected that it seemed that if anything was disturbed the whole system might crumble like a house of cards.

You can begin a preventive maintenance program on your next

trip to the transmitter for the weekly inspection. Instead of giving the equipment the once-over and signing the log just before you take off, why not do a real inspection and maintenance routine. Check every meter reading and investigate any deviation from normal. (Here's where posting those readings comes in handy.) Dip the plate current on the transmitter and re-tune according to the manual (usually this involves tuning to some plate current value slightly higher than minimum).

While at the transmitter site you oughly. Don't use a broom; it will raise too much dust. Keeping the building clean will minimize the amount of dust the transmitter blowers suck into the air filters. The filters themselves should also be vacuumed at this time, making sure to apply suction in the opposite direction from normal air flow. Vacuum equipment racks too, especially in summer when bugs seem intent on clogging the works everywhere.

The weekly inspection is also a good time to calibrate remote meters. First record on the maintenance log the actual readings obtained from the transmitter itself, as well as the remote meter indications as reported on the phone by someone at the studio. Then re-calibrate the remote readings to agree with the local ones and record both on the maintenance log again.


In some cases remote control units have the calibrating controls located on the studio unit. If there is no one at the studio competent to make those adjustments, you'll have to do so yourself when you get back. Don't simply adjust studio readings to agree with those at the transmitter when you were there. Make adjustments on the basis of the difference between remote and local readings at the time you were at the transmitter site.

Next On Tap

Next month we'll continue with a look at monthly maintenance, tape maintenance and coffee in the pots!

Switch to the Ross family. It's a new generation.

Maximum production at minimum cost. It's ideal. To achieve it we came up with a new generation. Ross Video Production Switchers. Cost effective design gets the best and the most for less. State of the art CMOS



reliability—human engineering combines sophistication with ease of production and logical operating procedures. Space efficiency opens up a dramatic new range of applications. Look into the RVS16-6. 16 inputs, 6 buses, dual effects generators and more, much more. Complete production capability with an electronics and power supply package that occupies only 7" of

rack space. The RVS16-4 features 16 inputs, 4 buses and effects generator—and for maximum production flexibility at minimum cost, there's our

new 10 input 4 bus RVS10-4. It's available in two formats: conventional remote control panel, or super compact, integrated electronics/control package at a super low price.

Ross Switchers are in use in major broadcast installations. Check our specs in the largest studio or the most mobile mobile, Ross Video Production Switchers are right at home.

Illustrated is our top of the line RVS16-6. Ask for technical literature on our full family of switchers.




ROSS BROADCAST PRODUCTS LTD 14 IROQUOIS PLAZA IROQUOIS ONTARIO KOE 1KO (613) 652 4889


Distributed by

Glentronix Ltd 160 Duncan Mill Road Don Mills, Ontario M3B 1Z5 (416) 444 8497

Superior workmanship and heavy-duty construction guarantee that each ITC machine will meet your station's needs.

The outstanding performance of 17,000 ITC decks proves that ITC machines are built to last.





CONFIDENCE to back all ITC tape equipment with a bold new *two-year* warranty.

Every ITC cartridge and reel-to-reel machine shipped since January 1, 1976, has been fully covered by an unprecedented two-year warranty. We are able to add the second year because of ITC's unsurpassed 6-year field performance. We know ITC machines will stand-up to your use, and we want you to know it, too.

Take advantage of our two-year warranty. Call ITC today. Collect 309-828-1381.



INTERNATIONAL TAPETRONICS CORPORATION 2425 South Main Street; Bloomington, Illinois

For More Details Circle (59) on Reply Card

© 1976 by ITC Form No: 111-0003

Segmented Helical Scan

VTR Review

By Joe Roizen

Television stations throughout the world have continued to increase their reliance on video-tape recording as a means of bringing programs to their audiences in a smoother, more efficient manner. This is quite evident when one considers that many prime-time movies are copied on tape before airing to facilitate commercial inserts and simplify equipment scheduling.

The use of very expensive and complex quad cart machines for fast paced station breaks and commercial spots is another indication of this trend. The most prevalent type of VTR assigned to primary studio applications is the

quadruplex format machine, of which more than 8,000 are now in use. To date, all attempts by other VTR formats to invade the broadcast market have had only limited success, and mostly in peripheral applications.

However, 1975 witnessed the emergence of a new breed of recorders that can best be described as hybrid machines which combine the best features of the quad (high writing speed, short scan length) with some of the benefits of helical formats (long head life, low tape usage).

The recorders, made by three manufacturers, are defined as seg-

SEGMENTED HELICAL VTR COMPARATIVE CHART

From Published Manufacturers Specifications

TECHNICAL SPECIFICATION	BOSCH/FERNSEH BCN	ARVIN/ECHO PILOT I	IVC/RANK/THOMSON 9000
TAPE WIDTH	25.4 MM/1.0 INCHES	25.4 MM/1.0 INCHES	50.8 MM/2.0 INCHES
TAPE SPEED	24.3 CM/9.5 IN./SEC.	38.1 CM/15.0 IN./SEC.	20.3 CM/8.0 IN./SEC.
HEAD SPEED	24.0 M/950 IN./SEC.	37.3 M/1470 IN./SEC.	38.1 M/1500 IN./SEC.
RECORD TIME	52/95 MINUTES	30/60 MINUTES	120 MINUTES
SCAN ANGLE	14.3 DEGREES		19.5 DEGREES
SCAN LENGTH	80 MM/3.14 INCHES		133.2 MM/5.24 INCHES
SCAN SEGMENTS	NTSC - 5/SECAM/PAL -6		NTSC - 5/SECAM/PAL - 6
PROGRAM AUDIO	TWO TRACKS	TWO TRACKS	TWO TRACKS
CUE AUDIO	ONE TRACK	ONE TRACK	ONE TRACK
ADDRESS CODE			ONE TRACK
SIGNAL SYSTEM	HIGHBAND	SUPER HIGHBAND	SUPER HIGHBAND
VIDEO S/N	PAL 43 dB		PAL 45 dB, NTSC 47 dB
DIFF. GAIN	4 PER CENT		4 PER CENT
DIFF. PHASE	4 PER CENT		4 PER CENT
K-FACTOR			2T SIN ² PULSE 1%
MOIRE	PAL -35 dB		PAL -40 dB, NTSC -50 dB
TBC ERROR	±2.5 NANOSEC.		±2.5 NANOSEC.
AUDIO S/N	55 dB/DOLBY 65 dB		55 dB
FLUTTER & WOW	0.1% PEAK		0.15% PEAK
TAPE TYPE	CRO ₂	Fe ₂ O ₃	Fe ₂ O ₃
HEAD WARRANTY	300 HOURS		1500 HOURS

Today's Programmed Automation Can Increase Your Sales ...and Profits.

HERE'S HOW.

The Broadcast Industry has leapfrogged into the Age of Automation. You have got to believe that automation is the wave of the future in our business. In 1975, stations will spend over 14-million dollars on equipment and programming. The business side of broadcasting is also automating with English printout logging and computer billing. It is projected that 90% of all stations will have some type of automation by 1977.

An Automation System for Your Station. Control

Design has the right system, whether AM or FM, monaural or stereo, 1 kw or 100 kw, established or new licensee. What is the best size for automation? Any size!

Why Lose Weekend Sales?

More sales are lost on weekends than you realize. The prospective account, that you pitched all week, can be lost on a Sunday if your station suffers from "weekend personality letdown". That's the only time many businessmen have available to tune you in. Automated programming has consistent high quality.

Improved Format. Whatever your style . . . Rock, Country Western, Middle-of-the-Road, Rhythm & Blues, or Ethnic, there's a wide choice of automated formats from the leading producers. Automation brings the top talents, the top features, and the top music to your area.

The Right Commercial at the Right Time. If the log

shows a commercial spot at a specific time, rest assured it will appear exact. There is no error because of the confusion of the moment, no missed or delayed events, no disgruntled sponsors, no makegoods. Automated programming is accurate and precise. And, good business.

Control Your Costs 24 Hours a Day. It makes

no difference if it's 3 PM on Tuesday or 3 AM on Sunday. Automation constantly gives the same quality, at the same cost, and with the same thorough attention to time and detail. The equipment can be programmed for 7 days of hands-off operation, sequencing up to 8,000 events from a multitude of sources. Automation controls costs.

People Are Important.

Each of your key men wears many hats. By eliminating the tedium of the day-to-day operations, they are freed for more profitable assignments... special local programming, sales, market planning, financial management. Automated stations have better personnel utilization, higher pay scales, more job security.

Meet Competition Head


On. The automated station is in the best possible posture. It can provide top talent and entertainment like the largest conventional station: programming that is out of the reach of competitive size stations. It has firm control over costs. It frees personnel to better meet the radio needs of the community, and to more effectively sell and service customers in its marketing territory. The automated station has the competitive edge.

Increased Sales, Higher

Profits. The automated station, through tighter cost controls, better personnel utilization, and improved programming, produces higher sales, increased revenues, better profits. Automation builds profits.

Control Design specializes in automation equipment and our name is fast becoming synonymous with broadcast automation. Many of our products are now the standard of the industry. Our systems are specified or used by leaders in broadcasting, including: Rust Communications Group, Sarkes Tarzian, Singer, and many others

An Invitation. Broadcast automation is a good investment. At CDC, we're experts in automated systems and can help you with design, financing and leasing. For complete information phone 703-751-5650 today, or complete the coupon below. We'll rush you complete data.



Visit us at NAB Booth #706

control design corporation

205 South Whiting Street Alexandria, Virginia 22304 Phone: 703-751-5650

Yes, I'm Interested.

name		title	
station/company			
address			
city	state	zip	
phone		date	
TYPE OF STATION □ □ Please have CDC repr □ Just send literature.		AM/FM	
MY REQUIREMENT IS:	☐ Immediate. □		


For More Details Circle (60) on Reply Card



European engineers inspecting the Echo Science Pilot 1 backpack at the Montreux Symposium. Arvin/Echo had several on display in both portable and console configurations.

mented-scan helical machines because they all divide the TV image into segments (like the quad does), but use a different number of TV lines for each segment or head band. The three recorders are called the IVC 9000, the Echo Science Pilot I and the Fernseh BCN. They are not compatible with each other as each has a different set of geometric parameters and dissimilar electrical operating characteristics.

The IVC 9000, which is also sold by Thomson-CSF and Rank Cintel, was first introduced at the Montreux conference in 1973 and has been to the major broadcast conventions since. Over 60 of these machines are now in use. Both the Fernseh BCN and the Arvin/Echo Pilot l VTRs were shown at last year's Montreux Symposium in May, and elicited considerable interest among broadcast representatives at that conference. While these three recorders show some similarity in design philosophy, they are different enough to require separate descriptions of their tape formats and operating features.



BEI AUTOMATIC LIGHT CONTROL SYSTEMS FOR FILM CHAINS

BEI-709...LARGE IMAGE / BEI-410...SMALL IMAGE

Now, upgrade the speed of response, reduce maintenance and achieve better overall performance of your film chain.

BEI-709 and BEI-410, the only systems universally compatible to any film chain presently in operation.



FOR MORE INFORMATION CALL: (913) 362-4400

OR WRITE: BESTON ELECTRONICS INC.

9024 WEST 51ST TERR. SHAWNEE, KANSAS 66203 THONISON-CSF LABORATORIES, INC.

One good name becomes another.

CBS Laboratories Professional Products
Department, responsible for the development, manufacturing and marketing of broadcast products, has become Thomson-CSF Laboratories, Inc., a wholly owned subsidiary of Thomson-CSF, S.A.

Thomson-CSF, S.A., one of the world's leading professional electronics companies with over 48,000 employees, has, with this acquisition, turther increased its commitment to the American broadcasting industry.

Although our name is new, we continue to offer the very finest in broadcast equipment including Audimax®, Volumax®, Vidifont®, Image Enhancer and Color Correction Systems. And now we are introducing Microcam™, the revolutionary portable color TV camera, and the complete line of Thomson-CSF products, including the TTV 1515 Triax Color Camera.

We will continue to expand our research effort in the same tradition of professional excellence that has made CBS Laboratories the standard for the industry. We also will maintain the same professional development, engineering and marketing management staff.

You will continue to find the same innovative thinking and the same dedication to quality. We've got it all together under one great new name . . . Thomson-CSF Laboratories, Inc.



THOMSON-CSF LABORATORIES, INC.

37 Brownhouse Road, Stamford, Connecticut 06902 (203) 327-7700 / TWX (710) 474-3346

For More Details Circle (62) on Reply Card

Bosch/Fernseh BCN

This recorder was developed to meet European LIVE journalism requirements and to serve as a mobile or portable VTR for program acquisition away from the studio.

The recorder is a segmented helical machine using two heads, and one-inch tape. It comes in portable, mobile or studio configurations, with the smallest package (BCN 20) weighing 20 kilos (44 lbs.) without batteries or tape. The

studio units (BCN 40 and 50) are in console form and can include over-transport monitoring facilities.

The track pattern on the oneinch CRO₂ tape includes one video track, two program audio tracks, an auxiliary audio track that can serve as a cue or address code track and a control track.

Longitudinal tape speed on the BCN series is 24.3 cm/sec (9.5 ips), and this gives a 52 minute recording time on the portable. The console units which accept larger reels

can provide up to 95 minutes of record or playback time. Head writing speed is 24 m/sec (950 ips).

The video headwheel has two video heads, 180° apart, and two erase heads for "flying erasure" to accommodate editing needs.

The SECAM and PAL image are segmented into even 52 line segments, with 6 tracks forming one field. The NTSC version will use an odd segmentation of 5 tracks per field. A line-by-line autochroma eliminates or minimizes head banding.

As far as video and audio performance goes, the BCN units shown at Montreux, and later in Darmstadt, showed third and fourth generation copies that were airworthy. Video performance specs on the European standards, with a 5 MHz bandpass were just slightly lower than quad specs. Audio specs for the two high quality channels using Dolby A correction were at broadcast levels.

The BCN unit has not yet been demonstrated on the NTSC standard, however their engineering staff have studied the differences and are confident that the NTSC version of the BCN will meet domestic broadcast requirements.

Arvin/Echo Pilot I

This VTR is not exactly a new-comer to television, having been shown in NTSC versions at some pre-75 NAB shows. Echo Science (formerly Westel) has been building segmented helical recorders for instrumentation and military applications for many years. Recently Arvin acquired this company and a new emphasis was put on developing a new broadcast version of their wideband airborne VTRs,

Echo also chose to introduce their Pilot I recorder at Montreux as a contender for the European LIVE journalism market.

This recorder is a two-head, segmented-scan machine using one inch tape, however with a longitudinal tape speed of 38.1 cm/sec (15 ips) and a head-write rate at 37.3 m/sec (1470 ips), its tape geometry is quite different from the BCN. There is, therefore, no interchangeability between these two one inch machines.

The Pilot I also comes in portable and studio versions. The



For More Details Circle (63) on Reply Card


Shopping for a Distribution Switcher?

SAVE SPACE.

One of our competitors describes their 40 x 60 AFV switcher as occupying only two equipment racks. An equivalent TVS/TAS-1000 switcher takes about 2/3 of a single rack — without compromising performance specs (audio hum and noise measures -80 dBm on the TVS/TAS-1000 vs. -57 dBm on the competitive unit) and without use of single-source custom hybrid components.

SPEND LESS.

Another competitor boasts of video switching at less than \$30 per crosspoint. The TVS-1000 sells for as little as \$23 a crosspoint, and this price includes professional quality vertical interval switching, on-board electronic latching, and 100% computerized testing of all parameters through all crosspoints.



40 x 50 AFV Switcher

SPECIFY THE SWITCHER WITH PROVEN RELIABILITY.

The TVS/TAS-1000 is more reliable because its simple design requires fewer active components in the signal path. This reliability has been proven at installations throughout the world in configurations ranging from 10×10 to 80×50 . To find out more about the one switcher offering compact, cost-effective signal distribution with true broadcast quality and reliability, contact the nearest TeleMation sales office.

TVS/TAS-1000 Video/Audio Distribution Switchers





TeleMation, Inc. P. O. Box 15068, Salt Lake City, Utah 84115 (801) 487-5399. Other sales offices located in: San Francisco (415) 348-3322 ■ Los Angeles (213) 845-7831 ■ Chicago (312) 729-5210 ■ Atlanta (404) 451-1801 ■ Washington, D. C. (301) 937-8700 ■ New York (212) 575-1466 ■ London ■ Rio de Janeiro ■ Sao Paulo ■ Santiago ■ Mexico City ■ Cairo.

FUJINON BCTV LENSES*



	1/4"	1"
1. Complete Field Zoom (Pictured above) With 1.5x and 2.5x servo operated built-in extenders.	22x25 f:2.2	22x18 f:1.8
2. Wide Angle Lens Compact and shortest M.O.D. with built-in 2x extender.	10x15 f:2.8	10x11 f:2.1
3. Studio Standard High transmission, aberration free, short M.O.D. multi-range lens.	16x17 f:2.1	16x13 f:1.6
4. Low Cost Field Zoom Available with 1. 5x and 2.5x add-on extenders.	14x37.5 f:2.2	14x29.5 f:1.8
5. Low Cost Studio Standard High quality, compact lens with normal range.		K10x16 f:2.0
6. ENG Lenses (Pictured below) Extreme light gathering power with ideal	1 " K7x11 f:2.0	2/3" A10x10 f:1.9 A7x9 f:1.4

Special and Exclusive:

ranges of zoom and

Extreme Width Angle Fixed Focus Lens.

7. Rota-Version Image rotation and inversion optical system. Mounted between 3pbo 1¼" color camera and zoom lens.

f.1.8/9mm f1.4/6mm

KF9A



*All Fujinon BCTV Lenses have Electron Beam Coating, the world's most advanced lens coating process. EBC makes our lenses the almost perfect transmitters of light. Thus, our zoom lenses' ability to transmit light remains remarkably constant from wide angle to telephoto.

See you at the NAB Show Booth 541



Fujinion Optical, Inc., 420 West End Avenue New York, N.Y. 10024 Phone: (212) 724-9834

For More Details Circle (65) on Reply Card



Bosch/Fernseh exhibit at Montreux included VTR's in different configurations. This studio version includes picture and waveform monitor in an over-console bridge.

backpack unit weighs 17 kilos (37.4 lbs.) and permits 30 minutes of recording while the studio unit, which can have a full complement of waveform and picture monitoring equipment over the console version VTR, accommodates 60 minute tape reels.

Track geometry on the Pilot I is similar to the BCN, with a video track, two program audio channels, a cue/address code channel, and a control track. Special features claimed for the Pilot I signal system are: super highband mod/demod, pilot carrier color correction, color edit framing and dropout compensation. Video specs equal or superior to quad recorders are achieved with normal Gamma Ferric Oxide (Fe₂0₃) tape. Audio specs are also to broadcast quality levels. Multiple generation recordings produce good results.

The IVC 9000

As far as broadcast applications are concerned, the 9000 was the first segmented helical machine that attracted industry attention to this format. The 9000 was primarily designed as a program originating VTR. It was introduced in its PAL/

SECAM configuration in Europe at Montreux 73, and subsequently in an NTSC form at the Fall Conference of the SMPTE the same year.


The 9000 is a segmented-scan, two head helical machine using two inch tape. Head writing speed is 38 m/sec (1500 ips), which allows the use of super highband (9-12 MHz) for the carrier and deviation frequencies. Tape longitudinal speed is 20.3 cm/sec (8 ips) giving over two hours of playing time on a 26.7 cm (10.5 in.) reel. Track geometry on the tape consists of one video track, and three audio tracks (2 program, one cue) along the top edge. A control track and separate address code track are along the bottom edge of the tape.

This VTR is also called the Rank Cintel 9000, or the Thomson-CSF TTV 3500.

The 9000 comes in a console configuration with a monitoring bridge on top that can hold picture monitors or associated equipment. Waveform monitoring and the editing system is integral with the control panel on the right hand side of the VTR.

The 9000 uses two long life, hot

Capitol Records Tests, Calibrates, Evaluates, Approves, Repairs, Quality Controls, and Reviews with the Stanton 681 Cartridge Series



The physical process of making phonograph records is not for amateurs. It is a job for craftsmen of the highest order, craftsmen who know exactly what they are doing. Naturally, they need the precisely right tools to do the job.

In the case of Capitol Records, the highest quality tools are employed throughout the process. That is why Stanton 681 Calibration Standard Series Cartridges are used, with various styli that are designed specifically for each critical measuring and listening job.

It has proven to be a great advantage to Capitol Records to standardize their entire operation with the 681 Series and three basic styli:

The D6807A — for cutting system check-outs.

The D6800EEE (our famous Triple-E) — for the most critical listening.

The D6872AMC - for tough nickel-plated "mothers".

The Stanton 681 Calibration Standard Series enjoys almost universal acceptance throughout the Recording Industry. After all, it

was created in order to satisfy the need for a cartridge of sufficient sophistication to be used as a primary Calibration Standard in system checkouts for linearity and equalization. Stanton Magnetics met this need by producing an "absolute" cartridge standard:.. stereo cartridges of such linearity and overall quality as to gain immediate acceptance within the Recording and Broadcasting Industries.

The fact that Capitol has selected the Stanton 681 Calibration Standard Series for use throughout the operation is a testament to its quality.

All Stanton Calibration Standard Cartridges are guaranteed to

meet specifications within exacting limits. Their warranty comes packed with each unit...The calibration test results for that individual cartridge.

Whether your usage involves Recording, Broadcasting or Home Entertainment, you can enjoy professional audio quality with Stanton Products.



For further information, write: Stanton Magnetics, Inc. Terminal Drive, Plainview, N. Y. 11803.

This new Stanton advertisement will appear in major consumer publications.



The IVC 9000 recorders have been having some marketing successes. Here you see two machines in a Rank Cintel booth operating on the PAL standard.

pressed ferrite heads that can give 3000 hours of service before replacement. The head drum also carries the flying erase head.

Video and audio performance specs are equal or superior to current quad recorders, and this is achieved with normal (non CRO2) longitudinally oriented two inch tape. Tape longevity is also improved by constant tension spooling through the use of vacuum columns, and a vacuum collar keeps the tape away from the scanner during standby modes.

Summary

Segmented helical VTRs now offer a gamut of physical configurations and electrical characteristics which fit them for many specialized applications in television broadcasting. While it is unlikely that they will replace the quadruplex format in the near future, it is probable that a growing number of these VTRs will be acquired by production houses, TV studios or CCTV program originators to satisfy specific needs that are met by the segmented helical format.

norbnad

LOOK AT IT THIS WAY.

"Grandson"

will help make an impact on your listeners and your profits using proven multi-track production techniques. We guarantee you'll love GRANDSON'S new production results and unique versatility. Where else can you find an affordable, fully modular, professional recording/production console with 18 mixing positions—and on-air capability?

Ask us about GRANDSON today.



auditronics.inc.

P.O. Box 12637 / Memphis, Tenn. 38112 / 901/276-6338

The world leader in recording consoles at sensible prices.

There's News Out There...



and Farinon's Portable, Frequency-Agile Microwave Gets It On The Air!

The new FV Portable Microwave system is available for all bands from 1.99 to 13.25 GHz.

You dial-tune to your operating frequency on the spot. There's no need for bench-work before you set up a remote pick-up. No filter pre-selection. You don't even need a screw-driver.

You can plug in video monitors, or clampers, or up to three sub-carrier channels.


You can run 500 feet of cable between the RF head and the FMT or FMR remote unit without roll-off or equalization.

And you get 1-watt output level from 6.875 to 13.25 GHz, 5-watt output (optional 20-watt) from 1.99 to 2.11 GHz, ±0.002% frequency stability; 60-dB signal-hum ratio from dc to 10 kHz, and 70-dB signal-noise ratio from 10 kHz to 5 MHz.

Farinon Electric, 1691 Bayport Ave., San Carlos, CA 94070, U.S.A. Tel. (415) 592-4120. Telex 34-8491. ... in Canada: Farinon Electric of Canada, Ltd., 657 Orly Ave., Dorval, P.Q. H9P 1G1, Canada. Tel. (514) 636-0974. Telex 05-82-1893.



NAB Booth 110



STATION WWDC

Washington, D.C

for outstanding and meritorious ability and intelligence demonstrated in the decision to install Aural Studio - Transmitter Link equipment and the high degree of knowledge exercised in making the equipment selection."

Why STL?

- No "lost air" time due to cut, wet or electrically charged telephone lines.
- 2. Better Sound Quolity Than a Closs
- AAA telephone line.
 3. EVENTUAL COST REDUCTION in
- operating expense.

 4. Complete control of entire broadcast system.

Why Dual Channel?

- 1. A Dual-Chonnel costs less than a
- Better Reliability than a Composite. "Built in Backup."
 Greoter Channel Separation than a
- Composite.
- 4. Less Signal Drive Required to Receivers means additional system Fade Margin.
- 5. Less Test Equipment Necessary and mare Positive System Diognosis.
- Stereo Generator is away from Studio and Unauthorized Tampering.
- Stereo Generator and Broadcast Transmitter Compatibility without Interface.
- 8. Having a Dual-Channel STL is like having a Spare Link.
- Two Remote Control and Two Sub-Carrier Capability.

Why MARTI?

- 1. Channel Separation more than 65
- 2. Channel Response matched to 0.25 db.
 3. Distortion less than 0.5%.
- 4. All Solid State.
- 5. A Simple, True Direct FM Plug-in
- 6. Complete accessibility to Modules without removal from rack.
- 7. The Marti System Delivers Top Performance with Transmitter manufacturer's Stereo Generator.
- 8. Marti STL Systems Log over TWO MILLION (2,000,000) Broadcast Hours each Year.

 9. AVAILABLE FROM STOCK.

The Stereo STL with "Built-in Backup."

Dual Channel System (Stereo) \$4160.00 Single Channel System (Mono) \$2290.00

(Does not include cost of Antennas or Transmission lines).



For More Details Circle (69) on Reply Card

Do You Really Know When To Beep?

An investigation of the regulations and where they're found turns up some interesting answers.

By Harold Dorschug, WTIC, Hartford, Cn.

Your newsman has just given you a tape of a telephone interview to check. While it's running the boss sticks his head in the door, listens a minute, then asks, "Where's the beep?" Your mouth gets a bit dry as you answer, "We don't need to use it." His reply chills you a little. "That's funny—I just read a newswire story that says we can lose our telephone service if we fail to beep.'

Are you sure you're right?

One state broadcasters association has just advised its members:

The FCC has ruled against eliminating the mandatory beep tone that warns when a phone conversation is being recorded. Communications Certification Laboratory had argued that the

rule is unenforceable and costly. The FCC commented, "We believe that the privacy of communication is of paramount importance."


Chances are that what you are doing is OK, but let's see what the regulations really say. After all, telephone recordings make up an important segment of programs today, particularly with the emphasis on electronic news gathering and it certainly is a subject of much confusion.

Probably you have already searched Part 73 of the FCC Rules and Regulations from end to end and couldn't find the word beep. Only in Sec. 73.1206 is there any mention of recording a telephone

"I take it, then, that you don't want to be on TV?"



Announcing the TEM-7 AND TEM-13 TRANSMITTERS



A New
All Solid State
Microwave
For The Television
Broadcast Industry
7GHZ and 13 GHZ

- ALL SOLID STATE DIGITAL FREQUENCY CONTROL ON TRANSMITTERS
- CONTINUOUSLY VARIABLE FREQUENCY ADJUSTMENT
- MICROMETER FREQUENCY DIAL
- AUTOMATIC FREQUENCY CONTROL ON RECEIVERS



This new microwave equipment was designed with the broadcaster in mind and is based on manufacturing and field experience since 1961. Applications are STL, Inter-City Relay for fixed installations, Portable for electronic news gathering, and Remote Pickup for temporary installations.

For Complete Free Information on Specifications, Features, Reliability and Performance, write:

Tepco Corporation

P. O. Box 680, Rapid City, South Dakota 57701 • Phone 605/343-7200

FREE microwave profiling service at Tepco Booth 934 at the NAB Show March 21-24 at McCormick Place, Chicago. Write for details in advance of the show.

New from Cooke

SMPTE

Video Taping/Editing Accessories

OUR NEW SMPTE TIME CODE SYSTEMS PROVIDE UNIQUE FEATURES AND THE LATEST STATE-OF-THE-ART DESIGNS.

SMPTE TIME CODE GENERATOR



Fully compatible with any SMPTE time code editing system, and meets or exceeds all SMPTE specs. Operates on sync or com-

posite video input. Drop frame mode keeps generator on time when used with NTSC color video sources. Timing is unaffected by momentary power drop outs. Easy time set and large LED display readable at 30 feet. Two isolated outputs at +11 dBm into 600 ohms. Options include 10 outputs and 32 user bits per frame.

SMPTE TIME CODE READER/CHARACTER GENERATOR

Reads SMPTE code, generates 36 line high resolution digital characters, and adds time code characters to video. Valuable quad



recorder time can be reduced by making editing decisions off-line on inexpensive helical or cassette machines. Allows time code display on studio or mobile unit monitors during production or VTR playback.

TAPE TIMER



Replaces mechanical counter and motion sensor on RCA and Ampex VTR's. Optical system provides greater accuracy than mechanical

counter with the added feature of large easy to read LED digital display. Optional remote readouts and thumbwheel time set switches.

BE SURE WITH COOKE BROADCAST PRODUCTS

MASTER CLOCK SYSTEMS • VIDEO/AUDIO PATCHING EQUIPMENT • VIDEO/AUDIO/PULSE DISTRIBUTION MODULES • VIDEO TAPING/EDITING ACCESSORIES NAB BOOTH #805

OOKE ENGINEERING COMPANY

DIVISION OF DYNATECH LABORATORIES, INC. 900 SLATERS LANE, ALEXANDRIA, VA. 22314 TEL: 703-548-3889 TELEX: 89-9454

AVAILABLE IN CANADA FROM:

TELCOM RESEARCH

P. O. Box 271 STONEY CREEK, ONTARIO TEL (416) 622-1372

For More Details Circle (70) on Reply Card

conversation and that without any reference or requirement for using a beep signal.

Well then, it must be in the Communications Act of 1934, that sacred manifesto of Congress upon which all American broadcasting exists. No, save time looking, for even that doesn't mention the beep.

What else is there? Brace your-self—you'll never guess. The tariff of your local telephone company. Regulations governing telephone recordings have the weight of law only insofar as tariffs are approved by the appropriate regulatory body which is the FCC, in the case of interstate traffic. No wonder we broadcasters are confused.

After The Shooting

After World War II the ready availability of practical recorders caused the business world to consider their efficiency in documenting telephone discussions. Much faster than a secretary's transcript and incapable of typographic error, their attractiveness soon put them to work. Concerned about privacy, the telephone industry discussed with the FCC adequate means of advising parties to a conversation that it was being recorded. The requirement of the beep signal in the tariff was the result.

The original concept applied only to recording conversations and did not permit broadcasting the conversation directly. However, once the tape was made it could be played into a station's facilities like any other recording. Even the beep tone could be edited out since it had served its purpose during recording.

The One-way Beep

The next logical step was to delete the beep from the recording while at the same time sending it to the person being recorded. By the early 1960's telephone companies were offering recorder connectors which did that. They were, unfortunately, somewhat clumsy in that they disabled the local telephone during the actual recording process to prevent two-way discussions.

Finally, after the famous Carterfone decision making it possible to tie the telephone network to recorders via a simple approved coupler, the regulations for broadcast recording work were relaxed.

DFS-3000 Digital Framestore Synchronizer

It would take a wall full of equipment to handle the job that DFS-3000 does in just 8.75 inches of rack space. In fact, every synchronous treatment needed for the full spectrum of NTSC compatible broadcast activities is literally at your fingertips in this light, rugged, fully portable system that goes anywhere.

Just check this list of available features:

- Two complete fields of store for full broadcast versatility.
- Infinite window TBC corrects time base errors on any VTR including ENG.
- Look Ahead Velocity Compensator cleans up color vectors on direct color VTR's for truer color presentation across entire picture.
- Video Compressor enables producer to insert second live image in any quadrant of screen.
- Joystick Control allows compressed picture to be positioned anywhere on screen.
- Broadcast Quality SPG permits synchronizer to be used as station reference.
- Memory Analyzer ensures system integrity.

- · Frame or Field Freeze for special effects.
- Remote Control Panel for production flexibility.
- Synchronous clean-up of non-synchronous switches eliminates picture tearing and rolling.


All these features, and broadcast quality too, are packaged complete with power supply and analog circuitry in this fully modular system that weighs less than 60 lbs. Even more significant, power consumption is a mere 250 VA, keeping heat problems to a minimum.

For information on our demonstration program, call or write George Grasso, MCI, P.O. Box 10057, Palo Alto, CA. 94303. Phone: (415) 321-0832.



See us at NAB: Booth 926

We pack more in here...



so you do less out there

Fin More Details Circle (71) on Reply Card

NEED EQUIPMENT?

is your best source

FOR NEW OR USED BROADCAST EQUIPMENT

MOST MAJOR BRANDS • FAST SERVICE LARGE INVENTORY SATISFACTION GUARANTEED FINANCING AVAILABLE ON \$500 OR MORE

contact ALLIED before you buy or trade


317- 962-8596


IF YOU ARE NOT RECEIVING OUR MONTHLY CATALOG CALL OR WRITE

ALLIED BROADCAST EQUIPMEMENT 124 South 6th Street

Richmond, Indiana

For More Details Circle (124) on Reply Card









THE ESE EBS-76 WITH AUTOMATIC GAIN CON-TROL, efficiency, economy and specifications that meet or exceed all basic FCC requirements.

ENCODER FEATURES

- Output level to +18dBm balanced into 600 ohms.
- Automatic 22.5 second timing. (Adjustable)
- Switching of both sides of program line.
- Crystal controlled tones.
- Remote control capability.
- Reliable C-Mos circuitry.
- Stereo line switching available.
- Valid closed circuit testing with single switch.

DECODER FEATURES

- Automatic Gain Control makes tone levels equal from all sources - accepts any input from 100mv to 5v without adjustment.
- Built to work with existing EBS radio.
- Derives tones from speaker or tuner output.
- Adjustable delay.
- LED's on PCB indicate each tone received for easy adjustment.
- PLL-linear and C-Mos IC's for reliability.

FCC type-approval pending. Kit version may require certification of performance by station engineer. WRITE, WIRE OR CALL TODAY.

Even now steps are being taken to modify interconnect rules more as the result of the proliferation of automatic answering devices. Undoubtedly they will affect broadcasting and ENG.

Stations in Connecticut, for example, are served by The Southern New England Telephone Company (SNETCO), a Bell System affiliate. The applicable part of their General Exchange Tariff is found in Tariffs Part II, Section 25, Sheet 8. Section B of Subscriber-Provided Terminal Equipment in subparagraph 4 describes equipment for the recording of two-way telephone conversations. It makes interesting reading, but the most important part to the broadcaster is this condensed by the author and with emphasis added):

Connection of subscriber-provided voice recorder equipment with local exchange and toll facilities is permitted only by means of direct connection through SNETCO furnished connecting equipment which inserts the specified beep, provided, however, that recorder connector equipment without the automatic tone device may be furnished when the recording equipment is used by an FCC licensed broadcast station subscriber for the recording of two-way telephone conversations solely for broadcast over the air.

Your telephone company has a similar tariff. It must be made available for public inspection at a convenient location where you may examine this part. Or you may be able to prevail upon your service representative to make a copy of it.

Advance Notification

One more point that's very important. With the ease and freedom in using recordings of this type, the FCC took action to protect the caller's privacy by requiring advance notification before recording. This is set forth in Sec. 73.1206 and actually applies whether the call is to be broadcast either direct or by recording. Recently, several stations have been fined for failure to comply.

There it is. Did you give your boss the right answer?

505½ CENTINELA AVENUE • INGLEWOOD, CALIFORNIA 90302 • (213) 674-3021


130

For More Details Circle (72) on Reply Card

BROADCAST ENGINEERING


NEW PRODUCTS FROM ACCURATE SOUND HELP SOLVE YOUR AUDIO PROBLEMS









POWER AMPLIFIER



ASCO MODEL 445-M




CASSETTE RECORDER





440 STYLE PC CARDS



NUCLEUS SC100

...Whatever your problems: new equipment, rebuilt equipment, reconditioning or updating. ASCO's "Total Systems" capability can solve your problem.

RECORDER/ REPRODUCE SYSTEMS

ASCO provides complete recording systems using Inovonics, three speed electronics, AG-440, Ampex 351, Scully or other electronics. The transport features our new tape motion control box that eliminates the tape handling deficiencies typical of most older tape transports. Contact us about your needs and the system components you would like to use. Price: System shown is an ASCO/Inovonics 375-2C, 3 speed—\$3,700.00.

440 STYLE PC CARDS

We have AG-440B style reproduce, record, bias and EQ cards. Also extender cards for the above.

Price:
Bias\$120.00
Record120.00
Reproduce
Reproduce EQ
Record EQ
Extender Cards20.00 ea.
(not shown)

MIXING CONSOLE

The ASCO/ MIXFET DJ-11 Mixing Console is designed for advanced discotheque and broadcast production use. Unique low distortion and noise specification by use of field effect transistor technology. Features include: electronic pan from phono 1 to phono 2, talkback microphone tape ability, equalization on all channels, up to 4 mics and 4 line inputs in stereo or mono and VU meters with + 4 dBm output front panel headphone jack.

CASSETTE RECORDER

This ASCO CRP-4T cassette recorder is designed primarily as an on-line logging recorder for broadcast use. It is a four channel recorder/

reproducer with many transport functions including: skip-forward, skip-back (i.e. automatic fast motion to play mode)-automatic play with either continuous run or BOT/ EOT sense—
optional bi-directional play—optional capstan
engage for search and cue—digital readout tape
position indicator—any speed available between
.5 and 20 ips with variable speed option—all functions remote controllable.

The system is packaged in a two module bay with provision for module to module dub function. The package size is 7" high x 19" wide

Currently ASCO is developing a version of this unit to replace the cartridge format machines already widely used

The ASCO/ MIXFET M150 is an all-tube single channel professional power amplifier. 150 watts rms, 19" rack mount. Frequency response at 1 watt. 9 Hz to 70 kHz +1 dB. Bass boost continuously from 0 to +12 dB at 50 Hz. Subsonic filter—1 dB at 30 Hz: -25 dB at 10 Hz. Price: \$750.00

ASCO MODEL 445-M

Two channel reproduce only electronics, using standard 440 style cards. Available with or without front panel meters, in a 3½" rack mount chassis. Features a built-in power supply and two speed/ EQ settings. Provision is made for remote EQ selection. Transport power is derived from a rear panel jack. Output level +4 or +8 dBm balanced. Price: \$595.00 without meters/ \$695.00 with meters.

NUCLEUS SC 100

Solid state, single channel record/ reproduce electronics designed to replace Ampex 350/ 351

tube type electronics. Includes a built-in power supply and provides transport power via a rear panel jack. Two speed/ EQ choices. Output level +4 or +8 dBm balanced. Input impedence 100k ohms. Price: \$550.00

TRANSPORT CONTROL BOX

The ASCO 2000 Control Box is a solid state, retrofit modification for older 351 style transports. Features include: fast motion dynamic braking (i.e. braking is accomplished by reverse motor torque until reel stoppage, then normal brakes are engaged)—tape motion sensing that eliminates tape breakage by locking out the play function until tape has stopped—edit function constant tension holdback with optional constant tension takeup—optional constant torque holdback and takeup—access is provided for search and cue equipment interface—provision for tape lift function—delayed stop for "pop free" bias turn off—torque boost to accomodate high speed fast start-logic design provides access from any transport mode to any other transport mode—provision is made for logic lever control of all function—optional slow start capstan—capable of three speed operation—switch selectable tension settings to accommodate different tape

TRANSPORT RECONDITION

ASCO reconditions tape transports, motors and head assemblies. Our transport service includes replacing all necessary bearings, guides, rollers, springs, brakes, solenoids, switches, guards and

pads.
We completely strip your transport and refinish the top plate, then rebuild the transport like new. Head service includes complete tear-down, clean and rebuild with new springs, guides and recapped heads. Price: \$295.00.

Send for our illustrated catalog with new and used equipment listings.



ACCURATE SOUND COMPANY

114 5th Avenue, Redwood City, California 94063 415/365-2843

For More Details Circle (73) on Reply Card

yes its TRUE... the PRICE of Cross-Pulse & Color monitors HAS DROPPED

Now you can convert any monitor to a cross-pulse monitor with VACC's new \$345* model CPG-1 Cross Pulse Generator. Your monitor requires no modification. Fill out the coupon below for more information. At the same time, ask for a free copy of VACC's Troubleshooting Chart. This handy wall chart has actual photos showing typical video conditions such as normal sync with and without burst, time-base errors, overshoot, clipped sync, and many more. VACc's chart is a valuable aid when adjusting and troubleshooting video problems using a cross-pulse monitor.

If a video monitor is needed, install a VACc Electrooptical Isolator in a Sony receiver. A engineer or
electronic technician can install a model A-1 in a 12",
15" and 17" Sony receiver in less than an hour. Model
Al-A should be installed in a KV1711, KV1722 and all
19 inch Sony receivers. You add only one-half pound
to your receiver and your Sony can be used as a
high quality monitor or retained as a reciever by
merely flipping a switch. Isolation is far superior
to heavy transformer isolated monitors and you
can connect up to 20 monitors without troublesome ground loops if all monitors have VACc isolators.

by popular request NEW DEMODULATOR KIT

NEED AUDIO/VIDEO-OUT TO RECORD OFF-THE-AIR? Order VACC's new model D1 or D1A Optical Demodulator. Similar to, but smaller in size than the widely used VACC A1 or A1-A Optical Isolator, VACC's new optical demodulator kit is easy to install and has the same outstanding isolation and weight advantages. Use model D1 for Sony's KV1201, 1203, 1212, 1214, 1500, 1511, 1710 and CKV 171 and the D1-A for KV1711, 1722, 1910, 1922 receivers. Yes, you can install the A1 and D1 or A1-A and D1-A in the same Sony receiver to have a receiver monitor demodulator. Add VACC's Cross Pulse Generator and you can have all four functions using one CRT.

See us at NAB Booth #142



VIDEO AIDS corporation of colorado 112 West 4th Street, Loveland, Colorado 80537 phone (303) 667-3301

Paris Show Dates Set

When Paris reawakens in April, it will become the focal point of electronics for six days, from April 5 to 10, 1976. A crossroads of technology, the Salon International des Composants Electronics epitomizes a world in transition due to the electronic components industry.

Every year, over 60,000 visitors attend the Show and exchange their invitations for a permanent entrance card. Fifteen percent of these visitors are from 90 different countries other than France.

The show is divided into four sections: components, measuring devices, materials and equipment, products and methods. Everywhere, over the more than 3 miles of passageways which criss-cross the Show, 1000 firms from 30 countries welcome visitors in attractive reception centers and lounges. International participation is considerable, with more than 50% of the exhibitors from foreign firms (including over 100 exhibitors from Germany and 250 from the U.S.).

The Show also covers symposia, technical conferences and communications. Such meetings provide useful exchanges of views between manufacturers and users. There is a large setup for reviews and international technical publications. A press room welcomes over 500 French and foreign journalists. At their disposal is a fully documented file on the Show, background studies, etc.

French Trade Shows and Air France have joined forces in order to offer prospective visitors to the Show a low-cost travel package, which will include round-trip economy airfare, six nights accommodations at either the Sofitel de Paris or the Paris-Sheraton, continental breakfast each day, arrival and departure transfers, a bateau-mouche sightseeing tour, and all services and taxes. Total cost of the trip (which will leave New York on April 2 and return on April 9) is \$510, with a single supplement of \$70. Deadline for all reservations is March 16, so don't delay.

For additional information on the International Electronic Components Show or on special travel arrangements, please contact: French Trade Shows, 1350 Avenue of the Americas, New York, NY 10019. The telephone number is: (212) 582-4960.

International Video Disc Conference

Organizers of the first-ever international video disc conference have announced more top-line speakers. This three-day event will be opened officially at London's Royal Lancaster Hotel on

April 13 by **Lord Harris**, Minister of State at the Home Office with special responsibility for Broadcasting.

Much has already been written about the technology of video disc hardware systems. Emphasis at this conference—called Video Disc '76—is being put on programmes their finance and their marketing.

International publisher Robert Maxwell will be putting the publisher's viewpoint in one of the afternoon sessions. He will be joined by a number of speakers in the session titled 'Impact on Industry and Commerce', which will be chaired by Robert Heller, editor of "Management Today". One aspect of advertising will be represented by Harold Lind, Director of Research at the Advertising Association. He will talk on "The application of media planning to the Video Disc as an advertising vehicle". Television documentary producer Roger Graef, recently responsible for the controversial ITV series "Decision", will speak in the session "Broadcasting, Cinema and the Arts".

Speakers from overseas include: John Findlater, President of MCA/Discovision, USA; Gerald Raucamp, who heads the multi-media Carillon Audio Visual group, Amsterdam; Rolf Schiering of AEG Telefunken, responsible for marketing the TeD video disc system; Bengt-Arne Vedin, from a leading Scandinavian publishing group; and Charles Arden, vice president of the Visiondisc Corp., USA.

Among speakers from England will be: **Professor** Asa Briggs, historian, Vice Chancellor of Sussex University, authority on broadcasting and audiovisual communication; Alan Watson, one-time economics expert at the BBC and now head of Audio Visual Services at the EEC in Brussels; Dr. Boris Townsend, of the Independent Broadcasting Authority, well-known lecturer and TV engineering specialist; Leslie Ryder, senior official for Learning Resources at the Inner London Education Authority; Bernard Happe, technical expert and author in the field of film and video processing, and Technical Editor, "Screen Digest"; Roland Chase, chairman of Colour Film Services, leading authority on film-to-video and video-to-film techniques; Ian McAlley from McAlley Associates, management consultant with particular experience in video marketing; Robert Abrahams, copyright adviser to EMI; and Tony Griffith and R. W. Bayliff from Decca.

The entire programme will be under the chairmanship of **John Chittock**, film and video columnist of the Financial Times, editorial chairman of "Screen Digest" and an international authority on the video industry.

For all details, organization and bookings of this unique conference, please contact Pia Gross on 01-629-9381.


South Of The Border, Too

The U.S. Department of Commerce has announced that "BROAD/COMM '76", an exhibition

THE WILKINSON AM2500B 2.5 KW AM BROADCAST TRANSMITTER


FEATURES

- · Solid State Modulator Driver
- Solid State Exciter
- Only One Tube Type (4) 4-1000A
- · Variable Vacuum Capacitor Tuning
- Motorized Variable Capacitor Loading
- Low Distortion, High Level Modulation
- Accessible Drawer Construction
- · Solid State Timing Circuits
- Self-Testing Silicon Power Supplies
- Automatic Recycle
- Simplified PA Tuning Only two controls
- Double Duty Plate & Modulation Transformers
- · Pretuned at Customer's Frequency
- Power Cutback (optional)
- Designed for Remote Control
- Ample, Roomy Cabinet for Ease of Service
- Completely Metered
- Uses Standard Parts with Original Maker Numbers





701 CHESTNUT ST. TRAINER, PA. 19015 TELEPHONE (215) 497-5100



For More Details Circle (171) on Reply Card

of professional broadcasting and communications equipment.

This exhibition, which honors the U.S. Bicentennial, marks the second exhibition of this successful theme at the Mexico City Trade Center. The first telecommunications exhibition in June 1974, closed with projected sales of almost \$20 million.

In the very dynamic market for radio and TV broadcast equipment the U.S. share alone rose from approximately \$21 million in 1972 to \$33.3 million in 1974. The U.S. faces major competition in the Mexican telephone and telegraph market due to former Swedish ownership of the facilities and continuing contractual arrangements with former suppliers. Even so, the U.S. supplies a significant portion of central office equipment, subscriber/user equipment and handsets to the Mexican telephone system. In all other areas of communication equipment, the U.S. dominates the market.

Best sales opportunities for communications and broadcasting equipment include but are not limited to: Radio/TV Broadcast Equipment—audio consoles; stereo audio consoles; AM, FM and TV transmitters, turntables and accessories; amplifiers; professional TV lenses and cameras; color cameras; movie cameras (8 mm., 35 mm.); link systems; video cassette recorders; video cassette recorder/players; TV color sets (non-household) and TV monitors; magnetic video tape; professional recorders (1/4", 1/2", 1"); studio lighting equipment; antennas; optical and magnetic sound equipment; video cartridge machines; loudspeaker systems and microphones; studio production switchers; and video mobile units.

Participants in this exhibition will benefit from a professional market promotion campaign beginning three months prior to show date. Other benefits include design and construction of exhibit booth, utilities, shipping instructions and coordination, hospitality services; and search for representatives or potential licensees.

Participation in this exhibition is limited to U.S. manufacturers of communications and broadcast equipment. Interest in this exhibition is already running high and space is limited. Companies interested in participating should contact the project officer as follows: Mary R. Wiening—(202) 967-4463 DIBA/OIM—Room 4031, U.S. Department of Commerce, Washington, D.C. 20230.

Small Market FCC Waiver

The FCC has acted in response to three requests for waivers or modifications of its small-market policy, which limits each network company to a single station in a market with four or fewer AM stations, and to two affiliations in a five-station market.

The licensees of AM stations KNIE, Cheyenne, Wyo. and KEYY, Provo, Utah, requested waivers to permit them to affiliate with ABC despite one other

ANY OF THESE YOU?



A broadcast station that wants smooth, multi-speed slide dissolves while committing only one film chain to slides?

A lab that needs a simple, economical way to convert training productions from slides to video cassette, color corrected, with dissolves and special effects, and all from just one film chain in a single pass?

A small market station that would like to produce high quality, low budget slide commercials?

A college that needs to videotape its slide based, multi-media instructional programs?

A broadcast station that wants 3second random access availability of up to 32 slides?

A production company that would like to completely pre-program slide commercials and training programs, including special effects and multi-speed dissolves, before video taping?

If even one of these descriptions matches your needs, then you need to see the incredible, new Selectroslide Producer 32 film chain slide projector. There's never been anything like it before.

Direct descendant of the respected Spectrum 32, with its interchangeable slide drums and time proven mechanism, the new Producer 32 is the first slide projector to incorporate a microprocessor. It controls the servo maga-

Spindler Sauppé

North Hollywood, Ca. 91605 (213) 764-1800 TLX SPINSAUPPÉ LSA 651306

For More Details Circle (168) on Reply Card

zines for high speed random access operation; provides eight different dissolve rates, ranging from cut to 300 frames (10 seconds); controls special effects such as flash, fade-out and fade-in, alternate, and superimposition, at all dissolve rates; creates left and right crawls; and makes possible memory programming of dissolves and special effects. The Producer 32 may be operated in real time, from its electronic memory, or from pulses encoded onto an audio track.

And there's more. Much more. Producer 32—probably more than you ever dared hope for in a professional film chain slide projector!


During the NAB Convention, see a demonstration of the Producer 32 at the Cohu Exhibit Booth #302. The Producer 32 will also be in use at the NAB booths of Harris Gates Division, I.V.C., and Telemation.

March, 1976

MCMARTIN

EBS "TWO"

READY FOR APRIL 15TH DEADLINE!



EBS-2 Decoder-Two Tone Monitor FCC CERTIFIED

\$ 99.50



TG-2/EBS Encoder-Two Tone Generator FCC TYPE ACCEPTED

\$225.00

with



AMR-1 Fixed Single Frequency AM Receiver \$ 99.50

or the NEW

AMR-3 Three Frequency AM Receiver

\$125.00

or



FMR-1 Fixed Single Frequency FM Receiver \$ 99.50 FCC CERTIFIED

McMartin, a leader in the development of broadcast equipment has available **for IMMEDIATE DELIVERY** the NEW Two Tone Emergency Broadcast System. This system complies with all FCC Regulations. A complete AM or FM system (EBS-2, TG-2/EBS and AMR-1 or FMR-1) will cost you **only \$424.00**.

or with the **NEW AMR-3**\$449.50

see us at Booth 609, NAB/76

McMartin Industries, Inc. 4500 South 76th Street Omaha, Nebraska 68127 (402) 331-2000 • Telex 048-485

For More Details Circle (78) on Reply Card

AM FCC Waiver

(Continued from page 134)


ABC AM affiliation in the market.

The third request was from Texas State Network (TSN), which sought relief from the application of the small market policy to its TSN and new Continental News Service (CNS) operations. In a July 1975 order, the Commission imposed this condition on TSN when it granted a waiver of the "dual network" or "simultaneity" rules to accomodate a limited amount of simultaneous broadcasting by the two TSN operations.

The FCC granted permission for one additional AM in Provo and Cheyenne to be affiliated with one of the ABC radio networks, in addition to the one AM station in those cities already so affiliated.

The Commission also modified its July 1975 order that imposed a condition on multiple AM affiliations by TSN with AM stations in the same market. TSN now may have, with its TSN and CNS networks, affiliation with more than one AM and FM station in a market, provided that in any market where TSN is affiliated with more than one AM station, at least one AM or FM station must remain that does not present TSN or CNS programming.

If it affiliates with an AM station that has an associated FM station, or vice versa, TSN must ensure that its programming is not presented by the other station of the combination, the FCC said.



See us at NAB Booth #825 For More Details Circle (79) on Reply Card

NRBA puts priority On license renewal

The Board of Directors of the National Radio Broadcasters Association at its January 12th meeting in New York City decided to give top priority to the Association's efforts to effect passage of a radio license renewal bill in the current session of Congress. "There appears to be great sympathy and support in the Congress for radio-only license renewal legislation," said Robert Herpe, NRBA Board Chairman, "and we are hopeful that the latest draft version of our bill will satisfy all interested parties and go on to early acceptance by the Congress."

The NRBA Board also voted to mobilize radio broadcaster opposition to the pending legislation providing additional performance fees and to work toward meaningful de-regulation of radio. "These are two areas of great importance to radio broadcasters," Mr Herpe said, "which seem to us to be receiving less attention than they deserve."

Chairman Herpe also reiterated that NRBA's major thrust is a campaign to convince Congress, the FCC, and the public interest groups that radio and television are very different from each other and should be regulated and legislated for separately and differently.

The NRBA Board also voted to increase the number of its regions from nine to perhaps fifteen; to expand and mobilize its State Directors organizations; to conduct eight regional and about twenty local workshops for sales, promotion and management; to make available special membership dues for radio station groups and to expand the NRBA membership solicitation campaign which begins this month.

The NRBA Board confirmed the Palmer House, Chicago, as the site of its 1977 National Radio Broadcasters Conference & Exposition and chose Boston as the host city for 1978.

Two suits are filed On family viewing hours

Broadcasters say family viewing hours were adopted voluntarily and do not violate the right of free speech of those who produce television programs.

Their position was outlined in a joint motion urging a U.S. District Court in California to dismiss two suits alleging that the family viewing concept was dictated by government, abridges the First Amendment rights of screen writers and others, and violates the anti-trust laws.


The motion denied the existence of any state action that would constitute a First Amendment violation and contended that the plaintiffs failed to exhaust administrative remedies provided by law.

It was filed jointly by the National Association of

TELEDATA SYSTEMS

YOU CAN AFFORD TO TRUST YOUR "AIR TIME" TO US...

X-32, 32 CHANNEL TRANSMITTER REMOTE CONTROL




•expandable to 80 channels

For More Details Circle (175) on Reply Card

\$3895


X-10 ANTENNA REMOTE CONTROL FOR "LIVE JOURNALISM"



\$1495

For More Details Circle (176) on Reply Card

S-14 STATUS AND CONTROL SYSTEM



\$1595

For More Details Circle (177) on Reply Card

Please visit us at NAB, Booth 937, for complete details.


TELEDATA SYSTEMS, INC.


108 Aero Camino, Goleta, CA 93017 805-685-2317

in Canada contact: Orange County Associates, 1125 Empress, Winnipeg, Man. R3E 3H1

WE SPECIALIZE IN -

EBS DECODERS





FEATURES:

- May be driven by any receiver capable of a 100 mW output into an 8 ohm load (including the "carrier break" type monitor you may already have).
- Simple installation only two necessary adjustments.
- Simple operation.
- Signal loss indication-complete color coded status lighting.
- Ultra stable Phase-Locked Loop tone decoders.
- Tone detection unaffected by signal fading, adjacent channel interference, or static bursts.
- Frequency counter outputs from tone decoders.
- Will detect and decode an Attention Signal with harmonic distortion levels of 10% and signal to noise ratios of 0dB.
- Alternate 600 ohm input.
- -20 dBm 600 ohm output for rebroadcast purposes.
- Plug-in 4PDT relay for external alarms.
- IC regulated supply.
- Alarm timing accomplished with a unique digital timer which is unaffected by age or ambient conditions.
- Installation flexibilty to suit any needs.

FOR MORE DETAILS, CALL OR WRITE:

BRYANT ELECTRONICS

P.O. BOX 83201, LINCOLN, NEBRASKA 68501 (402) 475-8080

For More Details Circle (80) on Reply Card

Family Viewing

(Continued from page 137)

Broadcasters and the three television networks—ABC, CBS and NBC.

The two cases, pending before the U.S. District Court for the Central District of California, were brought by the Writers Guild of America and others and by Tandem Productions. The Writers Guild is demanding injunctive relief charging that setting certain hours aside for family viewing thwarts creativity. Tandem Productions is asking for both injunctive relief and monetary damages.

The broadcasters' motion pointed out that the concept of family viewing was adopted voluntarily by broadcasters and was not directed, dictated or compelled by the Federal Communications Commission.

"In the absence of any FCC compulsion, broadcaster action is not a state action, and...plaintiffs have no First Amendment rights to be free from the selection and editorial process undertaken by private broadcasters."

Responding to plaintiffs' claim that broadcasters are licensed and therefore perform "a government function," the joint motion said:

"In two recent cases, the Supreme Court has specifically held that the existence of licensing or general government regulation does not convert private action into state action...Plaintiffs are clearly mistaken (in their) claim that broadcaster action is

(Continued on page 140)

TENTEL TENSION GAGE SOLVES YOUR VIDEO PROBLEMS*

(*And avoids future problems)

THE TENTEL TAPE TENSION GAGE accurately diagnoses your video tape transport problems. Whether your machine is a ½" EIAJ, U-matic, 1" Ampex, 1" IVC or even a 2" quad, the Tentel Tension Gage will help you solve problems vital to:



- INTERCHANGEABILITY (Can you record on machine A and playback on machine B?)
- HORIZONTAL TIME BASE STABILITY (Will recordings "hook" or "flag" when played on another machine?)
- TAPE DAMAGE (If your supply tension is too high or your take-up tension is too low, your tape may jam, wrap around the capstan or misguide, causing edge damage!)

Tentelometers have been approved by leading manufacturers of quality tape recording equipment...including **Ampex**, IVC and **Sony**. Schools, universities, CATV and other closed-circuit communications users throughout the world have found the **Tentelometer** to be an invaluable troubleshooting tool.

Send for your FREE copy of the new TAPE TENSION INSTRUCTION BOOKLET providing tape tension information for U-matic, Ampex and IVC video tape machines.

Tentelometer, including carrying case, from \$179.

SEE US AT NAB BOOTH #228



For More Details Circle (82) on Reply Card
BROADCAST ENGINEERING

Foreign Language Station's Warnings

All licensees broadcasting primarily in a foreign language shall transmit emergency information both aurally and visually in both English and the foreign language, the FCC added.

The Commission said television licensees could use any method of visual presentation which results in a message easily being readable on the receiver's television screen, and which conveys the essential information contained in the aural bulletin.

It said stations participating in the Emergency Broadcast System would be responsible for visually transmitting any EBS programing.

The Commission noted that the Public Broadcast Service (PBS) has filed a petition for rulemaking to establish transmission standards governing closed captioning for the deaf that would require a special decoder on home television receivers. It said the PBS proposal goes well beyond emergency communications uses, and would include abbreviated narrative captioning for programing generally.

The Commission said it was aware of possible problems of incompatibility arising from the simultaneous use of open and closed captioning systems during a single emergency, and proposed to take this into account in connection with any further action on the PBS petition.

NAB Prepares For Radio Month


Fourteen radio broadcasters from every market size recently met to expand ideas for 1976 Radio Month (May 1-31) put forth by the Radio Information Office Committee of the National Association of Broadcasters. The group of general managers, program directors and promotion managers, recommended that NAB supply copy, one-line statements and taped testimonials of people's memories of radio highlights.

The material may be used in

various ways by stations to develop their own radio month campaigns, a concept endorsed by the RIO Committee. The theme for this year's campaign is "Thanks for the Radio".

The participants, representing formats from classical and religious to disco and progressive rock, further recommended that this year's material be geared to fit individual station sounds and that the majority of the spots be ten and thirty seconds in length.

Participating in the conference were: Allyson Artist (WGMS AM/FM), Sandi Barclay (WRC/WKYS), Gene Davis (WTOP AM/FM), Arch Harrison (WJMA AM/FM), Bruce Houston (WEAM), Bob Hughes (WASH AM/FM), Ross Hunter (WJMA AM/FM), Terry Kleger (WBOC AM/FM), Ellen Manowitz (WMAL AM/FM), Roy Martin (WFAX), Greg Pearson (WEEL), Bill Spencer (WAGE), Bert Thornton (WTRI), and Chuck Thornton (WTRI).



all new automation system from

It's here! The all-new DP-2. Microprocessor controlled, it offers more custom features than any other unit available today... features such as 8,000 event capacity; built-in external function control; automatic record of network; automatic transmitter logging option; mag tape, paper tape and solid state storage facilities; interfacing to business computers; sub-routines in any size; video readouts and programming; and up to forty audio

The DP-2 is available in low-boy console with desk as shown or in standard racks. It's versatile and inexpensive... and it's from the people who invented computer assisted broadcasting—SMC. It's loaded with features that will "hype" your station's air sound and profits.

Get all the facts on the new DP-2 system for yourself. Return the attached coupon today for more information.



channels.

Systems Marketing Corporation 1005 W. Washington Street Bloomington, Illinois 61701

309-829-6373

Broadcast Automationour only business

I want to know more about DP-2. Send complete information and have your Representative call me.
Name
Station
Address
ZipPhone (area code)
75-105

For More Details Circle (83) on Reply Card



equipment that works for you—Solid state stereo and mono 5-channel audio mixers, amplifiers and preamps, the finest turntables and precision tone arms. Using modern, trouble-free technology and RUSSCO-RUGGED construction, we bring you products you can really depend on. There's just no other name to consider for Top Quality and Economy!



BESTEIN

For More Details Circle (84) on Reply Card

Family Viewing

(Continued from page 138)

government action because broadcasters perform a 'government function'...

"The courts, conscious of the special problems which arise in applying the First Amendment to broadcasting, have consistently and correctly held that, in the context of the statutory scheme covering broadcasters, the First Amendment rights of providers of broadcast material are not violated by the exercise of editorial judgments by broadcasters...

"The Supreme Court (has) pointed out that Congress has chosen to leave the decision of what will be said over the airways to the broad discretion of broadcasters."

The joint broadcaster motion said plaintiffs' incorrect argument that their First Amendment rights were violeted "does not obviate the duty to exhaust available administrative remedies" by requesting a hearing by the FCC.

"Plaintiffs are attempting to circumvent the statutory procedures," the motion said. "...FCC's deliberative and enforcement powers are readily accessible to interested parties...

"For this Court to entertain those actions would thwart the policy embodied in the Communication Act's requirement that parties aggrieved by FCC reports or actions challenge those reports or actions by a petition for rehearing...

"It is well settled 'that no one is entitled to judicial relief for a supposed or threatened injury until the prescribed administrative remedy has been exhausted'."

Perfect Timing



console mount clocks and timers

Reliable ESE clocks and timers are now available in compact (2" x 3.7" x 3.6") console mount enclosures with bright easy to read .33" red LED's. Provided with rear solder pins for connection to your own switching or the optional remote connector, 6' cable and pushbutton set. Other options include: BCD Output; Crystal Timebase; 220V-AC-50Hz; and Kit Form. In addition the ES-370 is available with Stop and/or Relay Contact Closure at Zero.

ES-172 12 Hour Clock \$125. ES-174 24 Hour Clock \$125. ES-370 100 Min. Up/Down Timer \$180. ES-570 60 Minute Timer \$125. ES-572 12 Hour Clock/Timer \$150. ES-574 24 Hour Clock/Timer \$150.



Write, Wire or Call: (213) 674-3021

5051/2 CENTINELA AVENUE • INGLEWOOD, CALIFORNIA 90302

For More Details Circle (85) on Reply Card

AGAIN & AGAIN POTOMAC INSTRUMENTS IS

STATION ATTO

First FCC Approved Antenna Monitor

AM-19(204)

First Harmonic Reading Standard Broadcast Field Strength Meter

FIM-41

First Digital Antenna Monitor

AM-19D(210)

First Frequency Synthesized RF Bridge Source and Coherent Detector

SD-31

First Solid State VHF Combination Field Strength Meter & RF Generator

FIM-71

And Other FIRSTS to be Announced

CONTACT US NOW FOR DESCRIPTIVE LITERATURE ON OUR COMPLETE LINE OF BROADCAST INSTRUMENTATION.

OTOMAC NSTRUMENTS

932 PHILADELPHIA AVE. SILVER SPRING, MD. 20910 (301) 589-3125

For More Details Circle (99) on Reply Card

transmitter, DFM-3K-A, 3,500-Watt FM transmitter.

SMC (Systems Marketing Corp.) Booth 709-A

DP-1, automation system.

NEW: DP-2 and "RAS-PRO" automation equipment.

Sparta Division of Cetec Corp. Booth 615

AM and FM transmitters, studio furniture, studio audio equipment (audio mixing consoles, turntables, microphones, preamps, monitor amplifiers, tape cartridge equipment), remote audio equipment, accessory items for broadcast and production of audio.

NEW: "C"-Series high power AM transmitters. Solid state 1 kW AM transmitter. "Gibraltar" all-new tape cartridge system.

Stanton Magnetics Inc. Booth 811

Magnetic stereo cartridges, headphones, preamplifiers and turntables.

(Continued on page 148)

Exhibitors

(Continued from page 68) (Begins on page 48)

logging recorders with time code plus up to 4-simultaneous channels with 24 hr. per reel capability. Variable speed accessory for 280B servo recorders.

NEW: 2858-2 reproducer only, made in 280B format.

SESCOM, Inc. Booth 119

Audio transformers, mic-splitting transformers and assembled boxes, audio modules, in-line filters, pads, & transformers.

Shure Brothers Inc. Booth 324

High fidelity products, microphones, sound systems, and related circuitry items.

NEW: Shure models SM10 and SM12.

Sintronic Corporation Booth 713

AM-1K-A, 1,000-Watt AM transmitter, DFM-25K-B, 25,000-Watt FM



Directional Antenna Monitoring Simplified

Jack Hansen, WFMD, Frederick, Md.

With the Model AM-19D (210) Digital Antenna Monitor, accuracy is assured and operating cost savings are realized. Now antenna phase angle and loop current ratio readings can be taken by lesser grade operators. The easy-to-read numeric readout provides exact readings and eliminates interpretation errors common with conventional meters. Resolution is 0.1° for phase angle and 0.1% for current ratio.


Contact us now on this and other FCC type approved Antenna Monitors.

OTOMAC NSTRUMENTS

932 PHILADELPHIA AVE. SILVER SPRING, MARYLAND 20910 (301) 589-3125

For More Details Circle (100) on Reply Card

Grand color monitors... Great dollar savings!



Anyway you look at them, Unimedia's SMT color monitors are good news! Professional quality . . . affordable prices.

The SMT Line is a complete family of one-gun color monitors, from 9-inch portables and rack models through 12, 15, 17, up to 19-inch rack-mount models. All share the same clean styling, single gun color tube picture quality, and blue-gun only set-up convenience. Professional options include pulse-cross, A-B input, external sync, switchable underscan, and tally-light features. Most are priced right around \$1,000. Some higher . . . some considerably less.

If you're a broadcaster, CCTV or Cable operator, or production studio operator you can share in the dollar savings inherent in Unimedia's simple, straightforward SMT design. Now you have a golden opportunity to replace obsolete monochrome models with new SMT color monitors at attractive prices. Or replace tempermental large-screen color jobs with SMT 12s, 15s, 17s, or even the new 19s. If you're starting a new facility, Unimedia monitors can save enough to buy you an additional piece of needed equipment.

And Unimedia SMT Color Monitors are professional in every sense of the word. Their long-term dependability is the result of engineered design simplicity and quality components. We've delivered over four thousand units to satisfied customers in the last four years. You'll find NTSC and RGB models. In the nine-inch line you'll choose from singles, duals, and combination models with waveform monitors, vectorscopes, or audio speaker-amplifiers. Or combine a color nine with a high resolution monochrome nine for camera focus and registration.

You really owe it to yourself to check out the complete Unimedia line before you install another monitor in your facility. Write . . . or phone today. Remember . . . saving money isn't all that bad!

UNIMEDIA, 22525 Kingston Lane, Auburn, Calif. 95603 Telephone: (916) 272-1971 or (916) 878-1250

unimedia unimedia unimedia unimedia

For More Details Circle (89) on Reply Card

NAB Selects Goodman For Distinguished Service

Julian Goodman, NBC Board Chairman and Chief Executive Officer, has been selected by the National Association of Broadcasters to receive the industry's highest honor—the Distinguished Service Award for 1976.

The presentation will be made during NAB's 54th annual convention in Chicago at the opening General Assembly on Monday, March 22.

The NAB award, established in 1953, is presented to individuals who make "significant and lasting contributions to the American system of broadcasting by virtue of singular achievement or continuing services for or in behalf of the industry in any or all phases."

Over the years Mr. Goodman has received many prestigious awards for his contributions to the broadcasting industry and in the preservation of First Amendment rights.

He is one of 10 living journalists elected to the Hall of Fame of Sigma Delta Chi's New York



Chapter for his "unique and lasting contributions to the profession of journalism." He also has received the 1974 George Foster Peabody Award, the International Radio and Television Society Gold Medal and the Southern Baptist Radio and Television Commission's Distinguished Communications Medal.

Goodman began his NBC career in 1945 as a news writer for WRC Radio in Washington, D.C. Several years later, he oversaw the combining of the NBC Radio and TV News and Special Events.

Goodman pioneered the use of tape for radio broadcasts of news events, participated in the development of "instant news specials" initiated by NBC News and managed a full-time worldwide staff which at the time totaled 900 writers, editors, camera operators and technicians.

One of the highlights of his career came in 1955 when he paved the way for the first filming of a Presidential news conference. He also supervised such widely acclaimed specials as "Journey to Understanding" based on the travels of President Eisenhower and Soviet Premier Khrushchev.

Goodman has been responsible for many policy changes within NBC. His interest in improving children's programming led to a new office at NBC—Vice President, Children's Programs. NBC-TV was the first network with such an office.

TESTING IS BELIEVING!



We want to prove that we're at least as good as our specs.

So we're inviting all Broadcast Engineers, Consultants, and anyone else, to test our FM Exciter at the NAB (Booth 602). You'll be excited by the results!

CCA

CCA Electronics Corporation
716 JERSEY AVENUE, GLOUCESTER CITY, NEW JERSEY 08030
PHONE: (609) 456-1716 TELEX: 84-5200

© Copyright CCA Electronics Corp.

For More Details Circle (91) on Reply Card

March, 1976

Experience Policy Polic

For a 2020 look at tomorrow

see Microtime

NAB-Booth 709


Microtime 1280 Blue Hills Avenue Bloomfield, Ct. 06002 (203) 242-4242 TWX 710-425-2390

MICROTIME

For More Details Circle (92) on Reply Card

VISCOUNT

PROFESSIONAL... and... AVAILABLE



KEY FEATURES:

- * 14 inputs 8 sync, 6 non
- * 4 busses
- * 27 std. wipe patterns
- * int.,ext.,chroma key
- * composite, ext. RGB
- * soft key, wipe of key
- * mix-blink on wipe-key
- * spot light effect
- * black burst, clr. mat.gen
- *'on-air'inputs indication
- * full preview
- * colour timed, any path
- * vert.int.switching
- * processing amplifier
- * remote control panel

*\$9250-'II50B' (shown above) also available: \$ 7500 - '1150A'



INDUSTRIES

EAST 69th AVENUE ICCUVER, BRITISH COLUMBIA NADA - V5X-2W9 {ONE (604) 327-9446 - TELEX (04) 508-605

Early Bird CCTV Video Seminar

Tektronix will present a daily Tektronix theater on Closed Circuit TV each morning of the convention in the Hilton, Palmer House, and Hyatt Regency hotels from 7:00 to 8:30 am.

The tape will be piped into all rooms. Its content should be of special interest to video engineers. The tape is based on video circuit and transmission measurements. And it's a continuation of their booth theme where they will have a continuing theater-type seminar on how to make measurements in AM, FM and TV.

Zapping Consumer Fraud

With more than thirty years experience in exposing consumer fraud between them, three professionals have banded together with producer/ syndicator Donald Herrick to form the National Broadcaster's Group to release a radio series called "Have You Been Taken Lately?". Information relating to the series has already been made available to more than 6,000 radio stations.

The three: Joseph Cartwright, attorney, with ten years accumulated experience with the Better Business Bureau, Minnesota State Attorney General's Office and the Ramsey County Attorney's Office; Jerry Patterson, writer, author of two books and various magazine articles on consumer fraud; and Allen Gray, broadcaster, whose thirteen years experience with CBS' Housewives Protective League predates "Truth in Advertising" et. al.

The program series has been subjected to a critical appraisal in the nation's largest market—as well as several smaller ones. Reaction has been favorable with several stations already impatient over necessary procedural delays.

Sixty-five programs have been recorded and are ready for immediate distribution. 260 programs have been scripted, and the firm plans to script two full years of programming, all of which will be updated as new information becomes available.

Each program of the "Have You Been Taken Lately?" series has two and one-half minutes of program content with flexibility. The series can be added to news breaks, or regularly scheduled five days a week as a sponsored feature.

SBE Convention Plans Are Detailed On Page 12

NAB Products

(Continued from page 46) (Begins on page 40)

Cartridge Tape Machine

The introduction of a completely new line of broadcast audio cartridge tape reproducers and recorders has been announced by Charles E. Collett, Beaucart Division Sales and Marketing Manager, UMC Electronics Co.

Each Beaucart features the patented pancake hysteresis synchronous direct drive motor developed by UMC's Beau Motor Division. This motor represents a new breakthrough in the areas of size, weight, temperature rise, and power consumption. It provides substantial assistance in reducing Beaucart's flutter and wow. The Beaucart line of cart machines meet the newly adopted NAB standards for this type of equipment.

Two basic Beaucart models are available, each in mono or stereo, record or playback, for either desk or rack mounting. The Type 10 for A-size cartridges, measures a trim $3\frac{1}{2}$ " high x $5\frac{3}{4}$ " wide x 15" deep and may be mounted three units across in a standard 19" rack. Record/playback combinations are mounted side-by-side for either desk or rack use. However, this model may be stacked one above another in various combinations to meet demanding customer applications. For processing A, B, and C-size cartridges, a Beaucart Type 20 is available with dimensions of $3\frac{1}{2}$ " high x 10-1/8" wide x $12\frac{1}{4}$ " deep. Units may be stacked one above another in different configurations.

For More Details Circle (185) on Reply Card

Digital
Recording System
Ampex Corporation and CBS

Inc. have announced the development of a new digital recording system capable of storing thousands of color slides and still pictures magnetically on computer disc packs for use in television broadcasting.

The Electronic Still Store System (ESS) was a joint development of Ampex and CBS, and is the first broadcast product to use digital recording techniques for video images.



Stability, smooth action and quality are the key ingredients in every Quick-Set product. This is why we can offer a lifetime guarantee against defects in materials and workmanship. We back this with worldwide distribution and service to give you the professional support you deserve.


Send for our complete catalog.



instrument positioning equipment

3650 Woodhead Drive, Northbrook, Illinois 60062 312/498-0700 Telex: 72-4362

For More Details Circle (116) on Reply Card



NEW 2 GHz CIRCULARLY POLARIZED "GOLDENROD" ANTENNA

- Ideal for Remote TV Broadcast Operations
- Equivalent Performance to Two Foot Parabola with Minimal Wind Loading
- Folds Down Flat on Roof of Mobile Van
- Circularly Polarized to Eliminate Multipath Signals
- 19 dBi Gain
- 18° Beamwidth, Nominal FOR FURTHER DETAILS CONTACT:

nurad, inc.

2165 Druid Park Drive Baltimore, Md. 21211

301-462-1700

For More Details Circle (172) on Reply Card

Under development for the past 18 months, the ESS electronically converts the analog television signal into digital form and stores the information on magnetic disc packs. Slides and stills can be randomly selected from bulk memory with an access time of less than 100 milliseconds.

The basic ESS system can store up to 1,500 video frames on-line for immediate random access and is expandable. Disc pack shelf storage is virtually unlimited.

In addition to the record and reproduce modes of operation, ESS can rearrange selected stills in any sequence for inclusion in a program; and two independent video outputs permit preview, dissolve, mixed and special effects to be performed in the normal way at the studio switcher.

For More Details Circle (186) on Reply Card

Intercom System

RTS Systems of North Hollywood, California has announced the

introduction of the "TW" Intercom System. A two-wire, closed circuit headset system, the RTS "TW" can be used in the field for all phases of T.V., film, music concert, theatre and A/V production.

In its standard configuration, up to 50 "belt-pack" user stations can be connected on line to two independent channels. Each rugged user station features noise-free, high-fidelity performance with these new additional features: built-in mic limiter, carbon or dynamic mic input, flashing call light with variable frequency adjustment for selective paging, two-watt headphone power amp with low distortion and extended response (150Hz to 10 kHz) and individual aux audio input, as well as common on line at power supply.

With #22 gauge cable, the RTS "TW" will operate on 2,000 feet of line. Two individual power supplies (Models PS-10 and PS-50) are available, which will operate up to 10 or up to 50 user stations. The supplies and the user stations are all available in rack mounting packages for permanent installation. The rack mount models feature standard three channel operation.

For More Details Circle (187) on Reply Card


EBS Encoder-Decoder


The Rivers Associates FCC Type-Accepted DU-ALERT 2 EBS EN-CODER has been designed to provide a reliable, inexpensive method of meeting the new requirements for EBS Alerting to be effective April 15, 1976.

The required 853 and 960 Hertz tones are crystal-controlled for high accuracy and stability, and the high audio output level is sufficient to feed multiple transmitters, if necessary.

The DU-ALERT 2 is available as a separate encoder or can be combined with the 7506 Decoder in a single 3½ inch rack-mount assembly for a complete EBS PACK-AGE. A one or two-channel crystal-controlled AM receiver option can be included in the same package.

The Model 7506 EBS TWO-TONE DECODER has been Certified by the Federal Communications Commission as providing a reliable method of meeting the new EBS alerting requirements.






- MEETS FCC REQUIREMENTS OF 2% ACCURACY
- SEPARATE METER WITH LIGHTNING PROTECTION SWITCH PROVIDES CONVENIENCE AND SAFETY
- TCA-XM MODEL AVAILABLE FOR PANEL MOUNTING
- DUAL RANGE SCALES AVAILABLE FOR DAY-NIGHT POWER CHANGES

The new Model TCA broadcast antenna current measuring systems replace conventional thermocouple meters to provide a substantial increase in accuracy under all operating conditions. Antenna current samples are taken from the current carrying conductor by a toroidal current transformer. Voltage developed across a terminating resistor is rectified by a patented temperature compensated circuit and displayed on a mirror scale taut band meter. The rectifier, with lightning protection switch, and meter are housed in a shielded enclosure away from the sampling transformer. No in-line meter switch is required. A separate rectifier and meter are available to allow panel mounting of the meter. Standard ranges to 80 amperes.

NAB BOOTH 613

DELTA ELECTRONICS



TELEPHONE: 703/321-9845 TWX: 710-831-0620

Unlike most other EBS Tone Decoders, the design of the Model 7506 will allow operation with the existing 1 kHz/carrier break EBS procedure.

The high stability and narrow bandwidths required by the new FCC certification procedures are easily met in the 7506 by referencing to a quartz crystal base and not depending on much less reliable phase locked loop techniques.

The Model 7506 is $3\frac{1}{2}$ inches high, rack mounted, and contains it's own power supply. In addition, Option 01 provides an audio amplifier and front-panel mounted loudspeaker. Option 02, in addition to the features of Option 01, includes a highly selective and sensitive crystal-controlled AM receiver board, for installation in the same Model 7506 cabinet.

For More Details Circle (188) on Reply Card

Tower Intensity Lights

The Flash Technology Corporation of America has announced a new FAA Type L-856 High Intensity Warning Lighting System. The new system, designated the FTB-205 ElectroFlash Beacon System, is believed to be the first designated to meet the specific needs of the skeletal tower application, offering features such as an optional remote monitor/control system for "hot" AM towers and other low frequency radiators.

The new system reduces the windage of the required tower mounted enclosures by as much as forty percent yet offers the same long life components and light output characteristics as previous FTCA ElectroFlash Systems. Experience gained in over sixty systems installations have led to significant mechanical and electrical improvements in this second-generation system.

All power and optical components are located within the same NEMA Type 4 Stainless Steel standard enclosure. Required field connections at each Beacon have been reduced to two AC line plus system ground and two low voltage control/monitor. The mechanical and electrical arrangement has been designed for easy access and maintenance.

For More Details Circle (189) on Reply Card

High-Speed Teleprinter

A new high-speed, 30 character per second teleprinter—the GE TermiNet* 30 Keyboard Send/ Receive ASR Printer with Mag Tape—is now available for low cost leasing from RCA Service Company. This printer provides terminal facilities for the exchange of communications in attended or unattended mode.

Designed to meet a variety of printer uses, this matrix impact printer assures no more wasted computer or communication line time, waiting to receive data. Operating at transmission speeds up to 1200 Baud, this TermiNet printer saves time and money in the office, on the computer and on transmission lines.

The TermiNet 30 ASR printer features include: a single cassette magnetic tape unit which stores 100,000 characters, answerback, vertical format unit (for form out (Continued on page 158)

IT'S YOUR CHOICE

Our New AAM-1 **Analog Antenna Monitor**

- FCC TYPE APPROVAL **NUMBER 3-235.**
- TRUE RATIO READINGS.
- GOOD STABILITY WITH MODULATION.
- UP TO 8 TOWERS DA-2.
- PHASE SIGN DATA ALWAYS AVAILABLE - NO EXTRA OPERATION REQUIRED.
- LOW PRICE.
- SIMPLE INTERFACE WITH REMOTE CONTROL SYSTEMS INCLUDING DUR NEW TMCS-2 DIGITAL TRANSMITTER/MONITOR REMOTE CONTROL SYSTEM.

or Our DAM-1 **Digital Antenna Monitor**

- FCC TYPE APPROVAL NUMBER 3-218.
- TRUE RIATIO READINGS.
- HIGH RESOLUTION.
- GOOD STABILITY WITH MODULATION.
- UP TO 6 TOWERS DA-2 STANDAFID, 12 TOWERS WITH EXTENSION UNIT.
- BASE CURRENT ADAPTER AVAILABLE.
- DIGITAL FIEMOTE CONTIROL SYSTEMS AVAILABLE FOR MONITOR ONLY OR FOR MONITOR AND TRANSMITTER CONTROL.

NAB BOOTH 613

DELTA ELECTRONICS

5534 PORT ROYAL ROAD P.O. BOX 1508 SPRINGFIELD, VIRGINIA 22151

TELEPHONE: 703/321-9845 TWX: 710-831-0620



The eyes of the world are upon us.

Around the world, more people now look to Electrohome for excellence in video equipment than ever before.

We manufacture solid state video monitors in monochrome and color to NTSC and PAL standards for broadcast, educational, industrial, commercial, medical, security and data applications.


The reason for such wide-spread acceptance is two-fold: a standard of quality and a record of service to our customers that have earned our products top rating around the world.

For complete information, contact Electrohome Limited at one of these offices:

Kitchener, Ontario, Canada N2G 4J6 519/744-7111 Telex 069-5449

2991 Grace Lane, Costa Mesa, California 92626 714/545-6991

9314 West 122nd Street, Palos Park, Illinois 60464 312/361-4636



ELECTROHOM

an extra degree of excellence in video equipment for every application.

Distributed in:

Austria Australia Belgium Canada Denmark Egypt Eire **Finland** Mexico

France Greece Hong Kong Israel Italy Japan Malaysia

Netherlands New Zealand Norway **Philippines** Portugal Saudi Arabia South Africa Spain

Sweden Switzerland Taiwan Thailand **United States** United Kingdom Venezuela West Germany

For More Details Circle (169) on Reply Card

Exhibitors

(Continued from page 141)

Strand Century Inc. Booth 401

Lighting units for TV studios. MMS modular memory system. Quartz color laniro units.

NEW: MMS modular memory system.

Studio Tape Exchange Booth 810

High quality reprocessed and evaluated 2" video tape. Also new and used 34" video cassettes.

Systems Marketing Corp.-Sono Mag Booth 709A

Radio automation.

NEW: DP-2, RAS-PRO, automation systems.

Tandberg Of America, Inc. **Booth**

Tandberg 10XD - 101/2 reel recorder; Tandberg 3-head cassette model TCD-330; Tandberg cassette TCR-5500.

UMC Electronics Co. Booth 712

Beaucart audio cartridge tape recorders and reproducers, Beaucart splice finders, Beau hysteresis synchronous motors.

NEW: Beaucart audio cartridge tape recorders and reproducers.

Suite: McCormick Inn

Unarco-Rohn, Division of Unarco Industries, Inc. Booth 905

Structural steel tower samples related to CATV, TV broadcast, AM & FM broadcast, two-way/mobile and home

Utility Tower Company Booth 531

Steel tower sections, base insulators and FAA (A/2) lighting kit.

Video Aids Corp. of Colorado Booth 142

New H-phase and burst phase meter; (Continued on page 156)

BROADCAST ENGINEERING

cable engineering

NCTA Convention Is Ready

CBS news correspondent Mike Wallace, legislators Sen. Vance Hartke, Cong. Torbert Macdonald, Cong. John Moss, and FCC Chairman Richard Wiley head the list of featured speakers at the National Cable Televison Association's annual convention in Dallas, Texas, April 4-7, 1976.

Among the major topics expected to receive most attention at NCTA's silver anniversary convention, "CATV '76," are pay cable TV, CATV deregulation, cable financing and marketing, future services and system operations. In addition to three major "forum" sessions featuring prominent industry and government figures, the management program includes 17 morning eye-opener panels and a special afternoon "Firing Line" session on system operations.

Three time Emmy Award Winner Mike Wallace will be the convention keynote speaker on Sunday, April 3. Wallace is co-editor of the CBS news program "60 Minutes".

The Monday, April 4 major session, "Cable Regulation: A Government Forum," will feature Cong. John Moss (D-Calif.), Chairman of the House Subcommittee on Investigations and Oversight; John Eger, Acting Director of the Office of Telecommunications Policy; John Rose, Deputy Assistant Attorney General, U.S. Department of Justice; and Mary Anne Krupsak, Lt. Governor of New York. Dean Bruch, former FCC chairman now with the law firm of Pierson, Ball and Dowd will moderate the session.

FCC Chairman Richard Wiley will be Monday's featured luncheon speaker.

Tuesday's main management session, "Forum: Perspectives on Cable Television," will include Sen. Vance Hartke (D-Ind.) ranking member of the Senate Communications Subcommittee; Torbert Macdonald (D-Mass.), Chairman of the House Communications Subcommittee; James Shepley, President, Time, Inc.; Russell Karp, President of TelePrompTer Corp., will be session moderator.

Robert L. Schmidt, President of NCTA, will be luncheon speaker on Tuesday.

Pay Cable Overview

"Pay Cable: An Overview" the featured Wednesday topic will include presentations by CATV, motion picture industry and sports representatives.

Following is a list of convention "eye-opener" (8-9:30 AM) panels.

Monday, April 5

Pole Attachment Negotiations
Tax Accounting/Property and Sales
Federal Legislation
Pay Cable: Hardware/Software
Future Cable Services

Tuesday, April 6

Franchising (New and Renewals)
Financing (Banks and other
Lenders)
Future of Pay Cable

Future of Pay Cable Regulation: How to Cope Program Services

Wednesday, April 7

Rate Increases
Privacy: Understanding the Issues
System Marketing and Pay
Marketing
Financial Controls: Management

Information and EDP

Labor Relations: EEO, OSHA, Education & Training

The Firing Line

A special Tuesday afternoon session "Firing Line: Problems of Systems Operations" will focus on the following subjects:

- Rate Increases: Implementation
- Pay Cable: Implementation
- EDP: What do you really need
- Local Origination: How to improve on losses
- Systems Operation: Installations and disconnects
- Service calls and preventive maintenance
- Statistics and Probabilities in evaluating system operation and equipment

Additional program and speaker announcements will be made in the near future. Advance registration for the convention is \$135 for members and \$185 for non-members. Further registration information is available from NCTA.

Technical Programs

Satellite Cable Interconnection, Designing Reliable Systems, Two-Way and Auxiliary Services, and an Engineering Forum are among the topics for main technical sessions at the National Cable Television Association Convention, April 4-7, 1976 at the Dallas Convention Center, Dallas, Texas.

Dr. Richard Marsten, Dean of Engineering at City University of New York and formerly of NASA, will chair a discussion entitled Satellite Cable Interconnection at the main technical session Monday, April 5. Panelists will look ahead to

Convention

satellite applications which the cable TV industry should consider for the future.

The Advanced Techniques panel on Tuesday, April 6, will feature a demonstration of fiber optics applications.

A second main technical session on Tuesday, Two-Way and Auxiliary Services, will emphasize data transmission services via CATV. The panel features a case study in banking by cable, by Bankers Trust Co., New York. Nationally recognized researcher, G. O. Shelton of GTE, will deliver a paper entitled "Transmission of High-Speed PCM Signals on CATV Systems" during the panel discussion.

A special Engineering Forum—a roundtable discussion of cable engineering problems and solutions—will be the main focus on Wednesday, April 7. NCTA's Engineering Advisory Committee chairman James Lahey, Muskegon Cable TV, will head the panel comprised of

Engineering Advisory Committee members.

According to Delmer Ports, NCTA vice president—engineering, this year's convention technical program will concentrate on day-to-day problems, but is also looking to experts from allied industries and technologies for their ideas and recommendations. "This year we are looking harder at ourselves—and harder at the outside world," Ports commented.

As in past years, selection of the convention technical papers, solicited throughout the cable industry, was made by a special subcommittee of the NCTA Engineering Advisory Committee.

Following is a list of topics for the technical program's Eye-Opener and Sunrise Sessions:

Monday, April 5:

Quality Improvements and Zero Defects (sponsored by the Society of Cable Television Engineers)

Tuesday, April 6:

Alpha-Numerics in Cable (sponsored by SCTE) Designing Reliable Systems

Wednesday, April 7:

Practical Considerations for Terrestrial Reception and Distribution (sponsored by SCTE) Pay Cable

The social highlight of the technical program comes on Monday, April 5 with the presentation of the annual awards for technical achievements. Awards will be presented during the Engineers Reception. Award winners will be announced next month.

A complete list of technical program panelists and papers is available from NCTA. Advance registration for the convention is \$135 for NCTA members and \$185 for others. Additional registration information is available from NCTA.

Social Activities

Pre-convention golf and tennis tournaments, a gala Texas barbecue, the annual banquet with entertainment by the Nashville Brass, a post convention trip to Mexico, and a full women's program featuring a Neiman-Marcus fashion show are



IF YOU'D CALLED US YESTERDAY, WHEN YOU WERE RUNNING OUT OF THESE, YOU WOULDN'T BE RUNNING OUT TO GET THEM NOW.

Because we stock the most extensive variety of video supplies (and accessories) you'll find anywhere. Because our fast, friendly, personalized service makes sure they're on their way to you fast. And because we're only a phone call away.

Send for our free catalog now. You'll find it's crammed full of everything you'll need—from simple things like gaffer tape, adapters and ready-made cables...to graphic tools, maintenance supplies...all the way up to lighting kits, intercoms and test equipment. Plus just about everything you can think of in between.

Then give us a call, whatever your needs. If we don't have it, we can tell you where to get it...and we will.



18 West 61st Street, New York 10023 (212) 586-6161 829 North Highland Ave., Hollywood CA 90038 (213) 462-0969 Call TOLL FREE 800-223-5460 except in New York State and Los Angeles Metro Area.

INTRODUCING THE BRAIN.



KSN's NEW, INTELLIGENT CHARACTER GENERATOR LETS YOU PROGRAM MOVING INFORMATION

KSN's new CG-500 Marquee Series of character generators is the breakthrough that will revolutionize electronic communication.

Controlled by a micro-processor, this exciting concept actually lets the user manipulate the moving informational scheme. The multitude of potential communication applications is almost mind-boggling. But for the Cable TV/Closed Circuit industries, the benefits are here, now.

Channel Billboarding

For TV Guide Channels and Home Box Office billboarding, the KSN CG-500 is just what the doctor ordered. Imagine the time you will save, the glorious messages you can program, the fun you will have with a character generator that

... is 128 lines long with 32 characters per line

- ... continually rotates your message
- ... automatically updates and advances to the next day whenever you want it to
- ... preserves and programs one part of the memory while a totally different message is running on the air
- ... can massage the wire, actually capture, hold and play it back at different speeds
- ... can take out segments you don't want
- ... can be fed out on a phone line (remote keyboard)
- ... can billboard several channels for very little extra cost
- ... is so intelligent, the format and information display is strictly up to you.

Find out more. Call or write. Ask us about THE BRAIN. Sensibly priced to maintain the KSN performance/price balance.



CHARACTER GENERATORS

Kansas State Network / P.O. Box 333 / Wichita, Kansas 67201

For More Details Circle (183) on Reply Card

"For some straight talk about your underground construction needs...

call me and I'll arrange a Ditch Witch demonstration on your job site!"



"Ditch Witch performance, backed up with service and parts availability — that's what makes the difference! At Ditch Witch, we'll not only tell you — we'll show you how we can fulfill your job requirements with a full line of underground equipment — trenchers, vibratory plows and multi-purpose Modularmatics. We'll show you an independent professional dealer organization, too, with a complete parts inventory for faster service.

"Call us today and see what Ditch Witch can do for you. Compare us with the competition. Then decide which equipment and dealer provides you more for your invested dollar.

"At Ditch Witch, we tell it to you straight!"

Call (800) 654-6481 Toll Free for the name of the dealer nearest you.

Ditch Witch . . . equipment from 7 - to 195-HP.

CHARLES MACHINE WORKS, INC. P.O. Box 66 Perry, Oklahoma 73077



For More Details Circle (180) on Reply Card

Convention

among the many social activities planned for NCTA's silver anniversary convention "CATV 76", April 4-7 in Dallas, Texas.

Beginning with golf, tennis and horseback riding on April 3, and ending with an optional reduced rate trip to Mexico City April 7 through 11, "CATV 76" convention week is chock full of fun and excitement.

On April 3 NCTA and the Texas CATV Association will sponsor a Cable TV Pro-Am golf tournament at beautiful Spring Park Country Club in the rolling Texas country-side. Golf pros Billy Martindale and Don January will host the event and will invite other tour players and local pros to join in the tournament fun. Registration is \$30 per person which includes greens fees, golf carts, clubhouse and locker privileges, transportation and prizes.

Also on Saturday, April 3 Australian tennis pro Warren Jacques will host a tennis clinic and round robin tournament for convention attendees. The tennis package, at \$25 per person, includes transportation, use of facilities and prizes.

For family members not playing golf or tennis, beautiful bridle trails and saddle horses are available at \$4 per hour.

On Saturday evening the Texas Assn. and NCTA have planned an authentic Texas barbecue featuring Texas style beef and beer, a Mariachi band, championship riders and a hay ride. Cost for the barbecue is \$10 per person.

Among the features of the "CATV 76" women's program are a Monday morning brunch and fashion show in the famous Zodiac Room at Neiman-Marcus. On Tuesday, April 6 a special tour of European Crossroads, the novel Dallas activity center with over 40 unique shops and five restaurants is planned. Throughout the convention a special Women's Hospitality Suite will be in operation at the Statler Hilton. This year women's program participants may attend all exhibits and technical and management sessions.

A major highlight of this year's convention is a special 4 day optional post-convention excursion to Mexico City.

PEOPLE IN THE NEWS

Looking at movement within the industry we find that Jerry M. Astor has been named director of marketing for the video products division of Akai America, Ltd.....International Video Corporation, Sunnyvale, California, has made some changes in assignments by naming Hans Koferl as marketing manager, Central Europe and general manager, IVC GmbH, and Robert W. Kuhl as manager of national accounts.

Upon resignation of George Grasso, **Donald F.**Smith has been appointed national sales manager for Commercial Electronics Inc. (CEI)....In Key Biscayne, Florida, **LaRue M.** (Bud) Courson, a 24-year veteran of the National Association of Broadcasters' staff, is their new vice president for administrative services....The appointment of **Joseph R.** Schubert to the position of director of NAEB Personnel Service which is the only personnel placement service designed especially for educational telecommunications....Myles Adler is now responsible for all Agfa-Gevaert advertising and promotion activities in the United States.

Charles F. Riley, President of Tele-Color Production, Alexandria, Virginia, has been elected as the first chairman of the Society of Broadcast Engineers chapter that was founded for the Washington, Baltimore, and Northern Virginia areas....Joining the staff of Video Concepts as director of marketing is Fred P. Wilske....Filling the new position of product marketing manager of the Watertown, Conn. Metal Stamping Plant of the Parts Division of GTE Sylvania Inc. is Thomas M. Hart....Designated as manager, marketing analysis, for GTE Lenkurt Inc. is R. Don Webster.

McMartin Industries, Inc., Omaha, Nebraska, announces the appointment of **C. Harrison Associates**, Suite 107, 6695 Peachtree Industrial Blvd., Atlanta, Georgia, as broadcast sales representative in the Southeast....The National Association of Broadcasters' Code Authority, announces the death of **Frank J. Morris** who was their west coast manager.

Phelps Dodge Communications Company, New York, N.Y., has established **Henry M. Edwards** as western manager....While on the west coast, **Wallace D. Miller** has been appointed general manager of Theta Cable in Los Angeles, and will be responsible for the overall operation of one of the country's largest cable television systems.

CCA is coming back strong with **Bill Trueman** as their new marketing Director and **Samuel Colodny** as Director of Engineering. Trueman moved from engineering with CCA into his new position, while Colodny joins CCA after a stint with AEL. Both are PE's with a deep engineering background.



FEATURES

- 100% solid state
- Exceeds NAB specifications
- Built in remote control facilities
- Economically priced
- All silicon transistors
- Premium core, metal faced hyperbolic heads
- Electronic tone cueing
- Optimum electromagnetic shielding
- Optional auxiliary trip cue
- Compact and modern design

-PREFERRED BY PROFESSIONALS-

CONTEL MANUFACTURING

A Division of

Continental Electronic Wholesale Corporation 1620 W. 32nd Place — P. O. Box 206 — Hialeah, Fla. 33012 Telephone: (305) 822-1421 — Cable: Contelco

For More Details Circle (88) on Reply Card



Here in one compact and informative 24 page booklet is all the data you need to select a Precision Audio and RF Attenuator for your application.

Reference Charts, Circuit Diagrams, Types and Uses, Current and Voltage Ratio Tables, Ratings, Etc., make this a handy and invaluable reference.

SEND FOR YOUR FREE COPY TODAY.

TECH LABS, INC.

Bergen & Edsall Blvds. Palisades Park, N.J. 07650 Tel.: (201) 944-2221

For More Details Circle (114) on Reply Card

Exhibitors

color sync generators, cross-pulse generators; party lines-editor programmer.

NEW: H-Phase/burst phase meter.

Videomax Corporation Booth 606

Expanded capability for rebuilding and refurbishing Ampex (Mark XV/X/III) and RCA video head assemblies (high band/low band).

NEW: Mark XV video head refurbishing/rebuilding.

The Video-Tape Company Booth 404

VTC 1000 quadruplex video tape; VTC U-matic videocassettes; videotape cleaning and testing services; quadruplex and videocassette tape duplication services.

NEW: VTC U-matic videocassettes, tape duplication services.

Wilkinson Electronics, Inc. Booth 617

Full line of audio equipment and a 20,000 watt transmitter.

NEW: All solid state 500 watt FM transmitter and a 2.5 kW AM transmitter.

Willi Studer America, Inc. Booth 833

The Studer A-67 recorder/reproducer.

World Video, Inc. Booth 214

A full line of professional color monitors including the 6210 Series 12" rack mount color monitor with computer type plug-in circuitry.

NEW: CDR Series 9-inch single and dual rack mount color monitors which require only 8-3/4 inches of vertical rack space.

Telecommunications Industries Ltd. Booth 205

PORTA-PATTERN© test chart systems, test slide systems; super 8mm and 16mm b&w and color

RELIABILITY **FLEXIBILITY** PERFORMANCE... ECONOMY TOO!



RELIABILITY—advanced state-of-the-art technology, I.C. op-amp circuitry and high quality components throughout, FLEXIBILITY-through multiple input preselect switches and a broad selection of optional plug-in modules to suit your individual requirements.

PERFORMANCE-with features like microphone input limiters which prevent overload. "Human Engineering" which provides maximum operator visibility, efficiency and comfort to minimize operator error. Readily available in 5, 8 or 10 channel models, mono or stereo. All sensibly priced.

THE ROBINS FAIRCHILD

30000 Series Broadcast Consoles For complete details, call Sam Jones

A Robins Industries Corporation
75 Austin Boulevard, Commack, N.Y. 11725
(516) 543-5200

For More Details Circle (128) on Reply Card

YOU CAN GET Studio Tape 3M 400 ½ HOUR **MASTER QUALITY** ea. delivered 2" VIDEO TAPE **CLEANED. EVALUATED** AND REPROCESSED

FOR ALL YOUR VIDEOTAPE NEEDS:

Call Nancy: 212-977-9330 630 9th Ave. New York, N.Y. 10036 Call Renée: (213) 466-8101 6424 Santa Monica Blvd. Hollywood, Ca. 90038

QUALITY & SERVICE AT THE LOWEST PRICES

For More Details Circle (219) on Reply Card

From 80 Years of Experience Comes the Finest AM & FM Broadcast Transmitters **Ever Manufactured!** CSI ELECTRONICS INC.



ELECTRONICS INC.

2607 River Road Cinnaminson, New Jersey, 08077 Telephone: (609) 786-1060

Visit us in NAB Booth #705, NAB March 21-24 Featuring AM and FM transmitters, 50 to 50,000 Watts

For More Details Circle (220) on Reply Card

reference films; 8x10 light box transparencies; transparency illuminator.

NEW: Spherical transparency illuminator for 8x10 test transparencies.

Teledyne Camera Systems Booth 210

CTR-3 Tri-Optical color telefilm recorder.

TeleMation, Inc. Booth 316

TVS/TAS-1000 video/audio distribution switcher, TCF-3000 color film camera, TVP-1000 video processor, 525 series broadcast and precision terminal equipment, TSG-3000 NTSC broadcast sync generator.

NEW: TCG-3000 multifont character generator.

Suite: Conrad Hilton

Television Equipment Associates Booth 203

Amplivox headsets for disk jockeys, sportscasters applications; Magnetek tape cleaner and evaluator; Matthey video delays, pulse delays, video filters; the Matthey automatic video equalizer, the I.R.T. color monitor comparator; the Link camera tube conditioner; the Link lag meter.

NEW: Matthey automatic video equalizer for NTSC to be operated upon VIR incorrect burst phase, set up, sync level, burst gain, overall gain, 2T gain, 2T pulse, bar tilt, chroma gain and chroma delay.

Telex Communications, Inc. Booth 512

Telex/Magnecord open-reel recorder/ reproducers, CS-90 sportscaster headset, TMS-100 and TMM-150 programmed music products.

NEW: Model TMM-150.

Tepco Corp.

Microwave transmitters.

Thomson-CSF Laboratories, Inc. Booth 520

FM Volumax automatic peak

controller; the AM Volumax; dual audio distribution amplifier; Audimax automatic level controller; and the Dynamic Presence equalizer. Also, a lightweight broadcast-quality, hand-held color TV camera, TTV-1515 triax color camera, the TTV-1516P portable camera, telecine equipment, Vidifont character generator systems with changeable fonts and font compose, sync and pulse equipment, image enhancer, the chroma/insert keyer, and the color correction system.

NEW: Vidifont Mark IV with font-compose camera interface; Microcam, miniature, portable, color TV camera; TTV-1516P triax portable color camera; high-performance FM Volumax, Model 4101/4111

Suite: Conrad Hilton

Exhibitors List Begins On Page 48



For More Details Circle (101) on Reply Card

March, 1976

Digital Air **Temperature**

The Announcer's Friend



- Indoor and Outdoor Sensors
- Walnut-Finish Console
- Gold Anodized Panel
- Multi-Sensor Selector
- Remote to Any Distance
- ½" Sperry 7-Segment Display
- Slaves Available

Send for Spec. Sheet, Model 309. Money Back Guarantee.

Also, a complete line of Weather Instruments, Recorders and Controllers.

(214)Texas 631-2490 Electronics, Inc. P. O. Box 7225B Dallas, Texas 75209



For More Details Circle (213) on Reply Card



For More Details Circle (125) on Reply Card

recording supply corp.

1291 RAND RD -DES PLAINES, IL 60016 312/297-0955

LEADER-, TIMING-& SPLICING TAPES

Top Quality Competitive Pricing Immediate Shipment Call or Write for our Catalog

Products

(Continued from page 147)

and vertical tabulation), adjustable pin-feed—4" to 91/2", Data-Phone+ (dial-up) capabilities, ribbon cartridge and 300-Baud originate-only integral modem.

Operating on the eight-level ASCII code, the TermiNet 30's print font has 64 upper case ASCII characters. The terminal prints 10 characters to the inch on an 80 character line with six vertical lines per inch. Printing at selectable 10, 20 or 30 cps, this impact printer is capable of handling up to a four-part form set of fan-fold or roll, sprocket-feed paper. The unique ribbon cartridge employs a Mobius loop ribbon to extend ribbon life four to five times over conventional spool-type ribbons.

*Registered trademark of General Electric Company, U.S.A. +Registered servicemark of AT&T.

For More Details Circle (194) on Reply Card

Test Generators

Tektronix announces the new 1410 Series of NTSC Sync Pulse

and Test Signal Generators offering all the advantages of modularity at prices generally associated with units of single-piece construction. To suit your specific needs, you may choose from a wide selection of sync pulse and test signal generator functions to be combined with the mainframe providing the color standard of your choice.

Should you develop additional test signal requirements in the future plug-in card construction insures a quick and easy retrofit for you. Any combination of five test signal generator modules driven by one sync pulse generator is feasible.

The Sync Pulse Modules and the Test Signal Modules plug vertically onto the 1410 Mainframe interface board. Front panel controls and switches are mounted on the module with easily removable extenders projecting through the front panels.

Available modules include three sync pulse generators, a color bars generator, a convergence pattern generator, a linearity signal generator, and a VIRS/Black burst generator.

For More Details Circle (196) on Reply Card

Take a "Q" from us! Get the smallest cart machine available Get automatic fast-forward standard Get quiet, cool operation Get the configuration to fit YOUR needs FROM GARRON ELECTRONICS 1216 KIFER ROAD, SUNNYVALE, CA 94086 (408) 736-8737 THEOREMAN (408) 736-8737 FOR More Details Circle (103) on Reply Card





For More Details Circle (103) on Reply Card

Rigged for Silent Running



Beneath the surface, Shallco attenuators quietly raise and lower signals for broadcast applications.

Request Catalog 102

Shallco

SHALLCO, INC. P. O. BOX 1089 SMITHFIELD, N. C. 27577 919/934-3135

For More Details Circle (104) on Reply Card

BROADCAST ENGINEERING

Third Generation Volumax

Earlier in this issue we covered this unit in detail, because it was tested by our audio editor. As a reminder, the new Volumax 4111 by Thomson CSF did show improvements over their older model 4111 (manufactured when the company was CBS Labs). The new unit provided the same over-modulation protection, but since a higher input level could be used for the same subjective spectral balance, a higher average modulation level was obtained in our tests.

The 4111's release and attack time is designed to provide less than 1 percent distortion at 50 Hz, with faster peaks being passed along to the following stages.

For More Details Circle (216) on Reply Card

Film Chain **Light Controls**

Beston Electronics, manufacturers of automatic light controls for large and small film chains, will show systems that are compatible with any camera-multiplexer-projector system. They will feature fast response times to changes in film density without changes in colorimetry or annoying bounce and overshoot.

For More Details Circle (217) on Reply Card

Transparency Illuminator

A new, radically-designed spherical transparency illuminator will be shown for the first time by Telecommunications Industries Limited, in booth 205 at the National Association of Broadcasters convention in Chicago, March 21-24.

According to TIL president Ed Ries, the PORTA-PATTERN Transparency Illuminator will provide completely even illumination over the entire area of an 8 x 10 transparency.

The PORTA-PATTERN Transparency Illuminator is composed of a 20" diameter sphere, the inside of which is painted with Eastman Kodak's white reflectance coating 6080 achromatic calibration standard paint, giving it totally flat illumination qualities without the use of reflectors.

The light source is a 12-volt quartz iodine lamp connected to a regulated DC power supply. This

We did it. We built a better studio. Cleveland's WJW-TV.

It is an Aderhold Construction Management Team production. Bringing together the talents and experience of architects, engineers, builders and designers. The only such experienced group across the country specializing in the complete studio. This permits budget control, dollar efficiency, and broadcasting superiority.

WJW-TV is perhaps the most revolutionary studio now existing. Acoustically superb. It incorporates innovative engineering ideas on acoustics, electronics, comfort control, and site conditions, into this beautiful structure.

Call Aderhold Construction Management Team. We'll handle the entire project from site selection to "on-air"... or any part thereof.


Aderhold Construction Co.

3384 Peachtree Rd. NE, Atlanta, Georgia 30334



For More Details Circle (105) on Reply Card

Low Cost ESE Right On Timers



ES-300: Four digit incandescent display, one hundred minute timer (99:59) with six controls: Count Up, Count Down, Min-Set, Sec-Set, Stop, Reset. \$168.00

ES-301: Identical to ES-300 except with planar, gas discharge display.

ES-302: Equivalent to ES-301 plus fast-set lever wheel programing.

ES-400: Three digit ten minute timer (9:59) with Start, Stop, Reset.

ES-510: Four digit sixty minute timer (59:59) with Start, Stop, Reset.

ES-500: Six digit, twelve hour combination clock/timer with five controls: Start, Stop, Reset, \$150.00 Fast Advance, Slow Advance.

STANDARD OPTIONS AVAILABLE: Kit; Slave; BCD Output; Remote Connector; 6' Remote Cable and Pushbutton Set; 220V A.C., 50Hz; 9" or 19" Front Panel 3½" high; 3 Wire Cord and Molded Plug. Tenths of seconds are available on all timers except the ES-500. Relay Contact Closure at Zero and/or Stop at Zero available on ES-300, 301, and 302. Crystal Timebase available for ES-500. Custom options and special orders available.

WRITE, WIRE OR CALL TODAY

5051/2 Centinela Avenue

Inglewood, California 90302

(213) 674-3021

\$185.00

\$238.00

\$ 98.00

\$125.00

Sportscaster Headset... Color, Action, Hands-free Mobility

Combine the finest omnidirectional dynamic boom mike with an equally high performance binaural headphone and you have the superior Sportscaster head² set...the Telex CS-90. For live broadcasts, from the station or on remotes, with cue and program monitoring and hands-free convenience. The audience hears every word, clearly, crisply, with crowd noise for background color and atmosphere. Circumaural ear cushions screen out noise in the immediate area so that special acoustic facilities are unnecessary. Supplied with convenient in-line, mike-muting "push-to-cough" switch. The Sportscaster headset. Color, action and hands-free mobility. For complete



For More Details Circle (107) on Reply Card

allows the color temperature and illumination level to be set and kept constant, and virtually unaffected by voltage variations. A verniertype calibrating knob is used to adjust the lamp position inside the sphere. Once set, the light condition is the same, day after day.

For More Details Circle (200) on Reply Card

Portable Camera

A hand-held electronic camera smaller and lighter than the traditional film cameras used in television newsgathering was shown for the first time to the nation's motion picture and television engineers.

Developed by Thomson-CSF Laboratories, Inc., in cooperation with the CBS Television Network, the portable camera—called Microcam because of its microminiature electronics—weighs eight pounds. A companion three-pound electronic hip pack, which can be worn around the waist, makes it possible to operate the camera in any situation, such as fast-breaking news events.



replaces cable



MATTHEY TYPE No. UN 097 FEATURES

75Ω Passive Delay Adjustable Delay without Switches ±4ns Trim by Screwdriver Adjustment **BNC Connectors** Video Performance

Delay Range 15ns min. to 665ns max. Replaces up to 437ft. of coax.

Television Equipment Associates, Inc. BILL PEGLER 516 • 628 - 8068

For More Details Circle (110) on Reply Card

SAVE AT SITLER'



G.E. & SYLVANIA STAGE - STUDIO

& PROJECTOR LAMPS

PLEASE DON'T GIVE US LAMP ORDERS AT LIST. WE'D RATHER GIVE YOU

> 42% To 48% OFF Compare Sitler's Prices:

TV Production Lamp No.	List Price	6 to 23 (42% Off)	24 to 47 (45% Off)	
FCM	16.25	9.43	8.94	8.45
FAD	13.80	8.00	7.59	7.18
FHM	17.25	10.00	9.49	8.97
DKZ	28.75	16.68	15.81	14.95
CYX	56.50	32.77	31.08	29.38
DXW	20.20	11.72	11.11	10.50
1 MT 12/2	20.00	11.60	11.00	10.40
FDB	29.50	17.11	16.23	15.34
FFT	29.00	16.82	15.95	15.08
500T 20 / 64	19.40	11.25	10.67	10.09
750T20P / SP	18.50	10.73	10.18	9.62
FDN	16.75	9.72	9.21	8.71
FDF	17.50	10.15	9.63	9.10
EGJ	34.25	19.87	18.83	17.81
DTJ	23.25	13.49	12.79	12.09
FAY	32.45	18.82	17.85	16.87
FBE	32.70	18.97	17.98	17.00
FBX	14.20	8.24	7.81	7.38
FCX	20.80	12.06	11.44	10.82
FEL	31.00	17.98	17.05	16.12
DVH / EDG	17.00	9.86	9.35	8.84
FCV	33.50	19.43	18.42	17.42
FEY	56.50	32.77	31.07	29.38
DYA	22.45	13.02	12.35	11.67
FBY	21.00	12.18	11.55	10.92

Sitler's SUPPLIES, INC.

P.O. Box 10-A Washington, Iowa 52353

For More Details Circle (109) on Reply Card



The camera's low power consumption of 20 watts enables it to operate on standard flashlight batteries in an emergency. Because of the solid-state electronic camera's size and unusually light weight, it is expected to broaden opportunities for women in broadcast journalism.

For More Details Circle (201) on Reply card

B&W Switcher

SHINTRON ANNOUNCES THE Model 361 Basic Four Switcher, a high-performance/modest-cost switcher for monochrome studios. It is a four input, black and white switcher with an A/B-C bus structure and a built-in RS-330 Genlock Sync Generator in one rack mount package. Shintron designed the Model 361 specifically for those monochrome studios unsatisfied with the limited performance of inexpensive conventional CCTV switchers.

The Model 361 Basic Four Switcher features a 4-input, 3-bus organization with total vertical interval switching by momentary-contact lighted push buttons. Possible effects are: 4 corner wipes, horizontal and vertical wipes, fade

and dissolve to effects. The effects bus is controlled by vertical interval momentary-contact lighted push button switches and gear reduction levers. The four inputs are equipped with interface for Sony, Panasonic, and BNC connectors. There are two program outputs and one preview output.

The Sync Generator genlocks to any of the four inputs or generates RS-330 sync from its internal crystal oscillator. The convenient genlock meter on the front panel indicates the sync source: genlock or internal. In addition the Model 361 automatically switches to internal sync if the genlock source fails.


For More Details Circle (202) on Reply Card

Time Lapse Video Tape Recorder

Hitachi Shibaden Corporation of America, announces the introduction of a new time lapse video tape recorder, the Hitachi SV512-S1. The new recorder includes all features needed for high quality VTR performance in a ½" EIAJ Format—designed for industrial

QUALITY TALKS FOR WNEW

New York, New York



Continental's 317C is the best measure for any 50 kW AM transmitter purchase. Performance, 125% positive modulation and reserve power capabilities are unbeatable. Today's best sound in 50 kW AM is Continental.




CONTINENTAL ELECTRONICS MFG. CO. BOX 17040 DALLAS, TEXAS 75217

For More Details Circle (111) on Reply Card

WHATEVER YOU NEED IN A MASTER CLOCK SYSTEM . . .

OYNADUIP has it!




No matter which components you may require, DynaQuip, a world leader in clock systems, can put together a package that is tailor-made for your operation. Pictured above is a typical system in use in countless broadcast stations and network centers around the world. Write or phone for descriptive literature.

a division of Firan electronics inc.

355 Iroquois Shore Road Oakville, Ontario, L6H 1M3 Canada

Telephone: (416) 844-7222 Telex: 06-982327



Why spend \$3,000 to \$4,000 on a new recorder when \$700 to \$1400 makes a new recorder out of your dependable Ampex?

Replace your old, tube type amps with Inovonics' Model 375 Tape Recording Electronics. Features solid-state circuitry, plug-in options, and exceeds recording studio specifications.

For complete data, call (408) 926-3588 or write;

aunamics.inc.

P.O. Box 61345, Sunnyvale, CA 94088

For More Details Circle (195) on Reply Card

scientific time study.

The SV512-S1 replaces the existing Hitachi SV512 with a new increased recording capacity of up to 96 hours. The recorder offers a choice of five models for different durations of recording time: 1, 12, 24, 48 and 96 hours. You can mix and match recording and playback times to suit your own requirements.

A built-in Automatic Time Switch-Over automatically converts the recorder to the 1-hour mode for continuous recording when an external triggering device is activated.

Other features of the SV512-S1 include: Pulse signal output to trigger sequential switcher: Ferrite video "T" Bar head and rotary transformer to insure stable, excellent recordings and reproduction performance; Automatic Gain Control (AGC) on both video, and audio.

For More Details Circle (203) on Reply Card


Audio Control Center

Micro-Trak Corporation of Holyoke, Massachusetts has announced

and commercial surveillance and the addition of the "D Compact" to its product line. This totally professional unit is the first in a series of System D Audio Control Centers. The D Compact is a complete audio control package incorporating a "64" Series Broadcast Audio Control Console with two Micro-Trak 740 Turntables and a professional microphone in a portable design.

> With a very stable fold up leg structure, the D Compact is arranged so that it can be used by


STOP GROUND-LOOP HUM!



\$140 F.O.B. N.Y.

NEW!

NEW!



VIDEO HUM STOP COIL HSC 1

WILL ELIMINATE HUM and other INTERFERENCE in Video Lines caused by differences in Ground

- · For Color and Black and White.
- FLAT-DC to 6.5 MHz.
- No Low-Freq. or Hi-Freq. Roll-off.
 No Differential Phase Distortion.
- · No Differential Gain Distortion.

- No Envelope Delay.
 Passive Device Failure Free-Low Price.
 Small Compact Package 4" x 4" x 2-1/4".

ELIMINATES HUM AND INTERFERENCE:

IN STUDIO

Between Buildings long runs in Buildings en Studio and Transmitter On Incoming Telco circuits
On Outgoing Telco circuits

IN FIELD

w. Remote Truck and Telco
Remote Truck and Microwa
For Intertruck Hookup For Intertruck Hookup
For VTR Units
For Monitoring Lines

Available on 10 day free trial

AUDIO-VIDEO ENGINEERING COMPANY 65 Nancy Blvd., Merrick, N.Y. 11566 Tel. (516) 546-4239

For More Details Circle (113) on Reply Card BROADCAST ENGINEERING

UNATTENDED, SELF-CONTAINED, POWER SOURCE to 300 WATTS

so reliable there are no trade-offs to consider

Continuous, unattended power 10 to 300 watts. That's TELAN. So totally reliable and weather-

proof, it'll operate in the most remote and inaccessible locations for months without even a maintenance check. Install it in an hour or two, light a match and forget it. No moving parts and it won't flame out. Uses natural gas, propane or butane fuel. TELAN Thermoelectric Generators.



110 W. Timonium Rd., Timonium, Md. 21093 Phone: 301-252-8220 Telex: 8-7780 Cable: TELISES

For More Details Circle (173) on Reply Card

itself, stand alone, or if desired, it can be set up on any available table top. When folded, it fits very nicely in the back of virtually any station wagon. With The D compact your man can be on site set up and ready to go in minutes.

All audio terminations are XLR type connectors for fast reliable hookup. The D Compact accepts inputs from three auxiliary units such as tape machines, and an additional microphone right along with its own turntables and primary microphone. You have the choice of any of Micro-Trak's "64" series audio consoles, the 6444, Broadcast Stereo, the 6454, Broadcast Mono, or the 6440 series of discotheque consoles.

For More Details Circle (204) on Reply Card

Touch Tone Detector

Frequency Devices, Inc. has announced the release of the 550 Series Touch Tone* Detectors. This new product is a P.C. mountable component which in and of itself performs all of the functions required for tone detection. There is one module for the low group and one for the high group.

The adjustment-free 550 has eliminated the need to coordinate large numbers of filtering, AGC, and level detection building blocks. It also circumvents many of the mechanical problems encountered in using larger and often inconveniently configured printed circuit card tone detector assemblies.

Rather than constraining the system mechanical design to accommodate an alien P.C. board the designer may now incorporate the detector into his own P.C. layout. The result is a significant savings in design time, assembly time, and system volume.

For More Details Circle (205) on Reply Card

Image Enhancer And Noise Reducer

Yves Faroudja Inc., a Los Altos, California based electronics firm announces the introduction of a new video product, the CRISP-MATIC Model 01-A Image Enhancer and Noise Reducer.

The CRISP-MATIC is designed to significantly improve the subjective quality and signal characteristics of television images coming Change
Sound to
Silence
with a

TABERASER

This rugged, heavy duty bulk tape eraser wipes sound from all magnetic tapes, cartridges, cassettes and magnetic film stock; handling up to 2".

It erases with minimum residual noise because the field automatically diminishes at the end of each 30-second cycle. A thermal control and blower keeps the unit below 71° C.

Available for 60Hz or 50Hz operation.

For the distributor in your area—Call or write:

TABER Manufacturing & Engineering Company

2081 Edison Ave. • San Leandro, Ca. 94577 • (415) 635-3831

For More Details Circle (115) on Reply Card

PERFECT TIMING

ESE 12 and 24 Hour Digital Clocks

THE ES 112 and ES 124 twelve and twenty-four hour, solid state, six digit clocks. Silent seven segment incandescent displays. Three easy to operate controls: Fast Advance, Slow Advance, and Hold. Built to deliver a lifetime of service. Available with the following options to provide



an even wider range of applications. BCD Output; Crystal Timebase; Remote Connector with or without Six Foot Cable and Pushbutton set; 220V AC, 50Hz; Nine or Nineteen inch Anodized Aluminum Front Panel; Slave; Three Wire Cord with Molded Plug. Also available in Kit form.

Price \$130.00

THE ES 142 and ES 144 twelve and twenty-four hour, MOS, solid state digital clock/thermometers. Display simultaneously: 6 digits of time (hours, minutes, seconds) and 3 digits of temperature (-50°F to



 $+150^{\circ}$ F) in planar, gas discharge displays .55" high. Units come equipped with Temperature Probe and six foot cord. With the exception of the Nine inch Front Panel the ES 142 and ES 144 are available with the same options as the ES 112 and ES 124. Price \$225.00



THE ES 132 and ES 134 twelve and twenty-four hour 12V D.C., MOS, solid state six digit clocks. LED display. Black anodized aluminum case. Available with same options as ES 112/124 plus A.C. operation with Crystal or Line Frequency Timebase. \$200.00




WRITE, WIRE OR CALL TODAY

505½ Centinela Avenue

Inglewood, California 90302

(213) 674-3021

There's no one system for every communications problem



We turn on voice messages when dependable voice communications are critical. That's when David Clark Company's Communications Systems offer reliable solutions.

Because your communications problems vary, so do our Intercom Systems, modules and headsets. We'll tailor a system to solve your every voice message problem. Our compatible modules provide the building blocks for custom intercom installations.

From missile sites to theaters, large construction jobs to remote oil drilling sites, TV studios to shipyards, our Intercom Systems help you hear while suppressing ambient noise.

For more information, call or write today.

from "the quiet people" at

David Glark company

370 Franklin St., Worcester, Mass. 01604

from low and median priced videotape recorders that use the "color under" principle.

The CRISP-MATIC is intended for applications such as Electronic News Gathering, tape dubbing and duplication, enhancement of large screen displays or any VTR playback where superior quality images are desired.


The CRISP-MATIC is housed in a portable case which is 43.5 cm. (17 in.) by 9 cm. (3¹/₄ in.) and can be used as a stand-alone unit or rack mounted in a standard 19-inch rack.

Operation is very simple, involving only an on/off power switch and a single knob to control the degree of picture enhancement. The unit is an "add on" device used in the playback mode of any normal (unmodified) VTR. Standard BNC connectors and a bypass switch are mounted on the rear panel.

For More Details Circle (206) on Reply Card

ENG-Remote
Compressor/Mixer
Ramko Research will introduce

COLORBARS & a VECTORSCOPE GO HAND IN HAND



- ★ The VM3 NTSC VECTORSCOPE
- ★ R/BS9 Complete NTSC SYNC GEN. (2 sets of outputs) with Genlock & COLORBARS GENERATOR
- ★ R/DB8 Driven Encoded COLORBARS GENERATOR
- ★ R/GB8 Standalone Encoded COLORBARS GENERATOR
- ★ R/CS2 NTSC SYNC GENERATOR (2 sets of outputs) with Genlock
- All units are portable and rackmountable, and include selfcontained power supply.

Ultra Audio Products

BOX 921 BEVERLY HILLS, CALIF. 90213 (213) 276-2726

For More Details Circle (181) on Reply Card

their DML-2 portable, dual mic mixers with individual limiting/compression. The DML-2M has been designed to provide a virtually error free method of mic amplification and mixing.

From the quietest whisper to the loudest shout, the simple set and

BUILD A BETTER STUDIO

Call Aderhold Construction Company. A complete construction management team of architects, builders, engineers and designers. No problem too large or too small. 404/233-5413.



Aderhold Construction Company

3384 Peachtree Rd. NE / Atlanta, Georgia 30326

For More Details Circle (118) on Reply Card



VCR CARRYING SYSTEM

The PB-3800 is a special Porta-Brace designed to accomodate the new portable color VCR units (Sony VO-3800, TEAC VT-1000). Incorporating the patented Porta-Brace cantilevered camera arm, the PB-3800 features two Cordura nylon padded cases for both the cassette deck and DXC-1600 CCU, and a heavy-duty padded waistbelt. The WB-2 is a lightweight, collapsible, two-wheeled cart designed to carry the Porta-Brace with video equipment mounted. Twelve inch semi-pneumatic wheels insure stable movement over any surface. K AND H PRODUCTS, LTD., Box 246, North Bennington, VT 05257 (802) 442-9118.

For More Details Circle (119) on Reply Card

...MORE THAN DEMODULATORS!

Diplexers • Power Combiners/
Splitters • Filters—Hi Power •
Switches • Amplifiers • Waveguide and Coaxial Transmission
Line Components • System Design.

BROADCAST CONSULTING MICROWAVE LINKS

Video, Audio, Digital Traffic

For a "hot line" to one of our staff of experienced RF experts call—(413) 568-1870....Dedicated to solving your RF problems...

Visit us at NAB Booth #932 COMARK INDUSTRIES, INC. P.O. Box 196 Westfield, Mass. 01085

For More Details Circle (120) on Reply Card

forget controls give the operator complete freedom from meter watching and knob twisting. Features virtually distortionless amplification, mixing and compression, internal tone generator for line level set, internal battery and/or optional AC supply operation, phone monitor/talkback function and XLR type mic and output connectors.

Specifications include: response from 20 Hz -20kHz ±1dB; distortion 0.1% max; 90dB gain max; balanced inputs and 600 ohm balanced outputs; 10dBm output level; 1.5 microsecond attack time; and signal to noise ratio of -65dB.

Also available is the DML-1S for stereo operation.

For More Details Circle (207) on Reply Card

Time Code Reader-Display

CMX Systems, an Orrox Company, announces a new precision reader/display designed for frame accurate editing of video tape. It reads standard SMPTE time code from any source and displays it as a digital readout visible from 40 feet in a normally lighted room. The standard SMPTE 80 bit edit code in drop or non-drop modes is displayed in hours, minutes, seconds and frames.

Real time operating speed ranges from 1/5X to 50 X. Editors working with either quadruplex or helical tape can search and pinpoint specific frames of selected scenes with ease and precision. The unit is plug compatible with any editing system.

For More Details Circle (208) on Reply Card

PUI TEC



EQUALIZERS & FILTERS

Twenty years of capable, dependable service in radio & TV stations and recording studios. U.S. and overseas. Picture is solid state Model EQP-1A3 Audio Program Equalizer.

PULSE TECHNIQUES, INC. 1411 Palisade, Teaneck, N.J. 07666. Tel. (201) 837-2575 Cable: PULTEC, TEANECK, NEW JERSEY

For More Details Circle (193) on Reply Card

OMOUND FIXED LENS ADAPTOR



THE NECESSITY ACCESSORY

Because Your TV Zoom Lens Can't Give You . . .


- SUPER WIDE ANGLES. Use lenses up to 180 degrees.
- MACRO FOCUSING for extreme closeups.
- SPECIAL EFFECTS including Anamorphic squeeze, controlled distortion, multiple, split and rotating images and many other effects.

Now with the new Comquip Adaptor use virtually any motion picture and SLR lenses on studio and portable color TV cameras . . . plus the new electronic TV news-gathering cameras . . . for far greater flexibility in studio and location production. You can even use your favorite Cine' or SLR zoom lens on it. And there's no loss of light or vignetting. Adaptor is equipped with built-in iris, focusing mount and choice of camera mount.

For further information and free spec sheet, contact

Comquip Inc. 366 S Maple Ave., Glen Rock, N.J. 07452 • (201) 444-3800

For More Details Circle (121) on Reply Card



The Super System. A refined, high-quality and ultra relliable intercom system for the demanding professional. Employing only two wires for operation, up to fifty units may be connected on line without loading or serious performance degradation. Features include: mic level limiter, flashing signal light, auxiliary audio input, adjustable side tone, and powerful two watt headphone amp.

Portable system standard with two channels; rack mount standard with three or more channels. The RTS "TW" Intercom System is comparable with carbon or dynamic mic headsets: It is completely field serviceable and packaged to provide super reliability under the toughest conditions. For more information please call or write:



7 4167 Fair Ave., No. Hollywood, Ca. 91602 213/980-0511

For More Details Circle (122) on Reply Card

Modular Tape Cart Units

The new CENTURY II tape cartridge equipment line by **Sparta** Division of Cetec Corporation will be unveiled at the 1976 NAB Convention in Chicago. The modular system of mono and stereo same-size record-playback and playback units will be available in single, dual, and triple table top mounts, and triple rack mount.

Standard features of the CEN-TURY II include both secondary

Need it in a hurry?

We offer same day shipment on stock items.

Let us serve your needs today!

We stock:

QRK, RUSSCO, TAPCO, SHURE, RAMKO, SENNHEISER, TELEX HEADPHONES, AKG, LUXO, ATLAS, SWITCHCRAFT, MMI, MICRO-TRAK, STANTON, 3M TAPE, FIDELPAC, REVOX, REK-O-KUT, AND MANY OTHERS.

Request our catalog. BROADCAST EQUIPMENT & SUPPLY CO. P.O. Box 3141 Bristol, Tennessee 37620 (615) 968-7342

For More Details Circle (123) on Reply Card

(End of Message) and tertiary cue tones...primary (Stop) cue tone defeat...audio mute on playbacks... logging signal in- and out-put...and BUILT-IN SPLICE FINDER. In conjunction with the splice finder a HIGH SPEED option is available.

It meets all proposed new NAB standards...uses peak reading record level meters with LED overload indicators in the meter face... and digital tone detect system.

For More Details Circle (209) on Reply Card

Modular Console

The new series of MAP 8422 Console Control Modules provide comprehensive switching and control facilities for multi-track recording, quad-stereo-mono mixdown, and monitoring required in today's recording and production consoles. They are available from **Modular Audio Products**, a unit of Modular Devices, Inc.

System features of the 8422 Series include: selectable Mic/High



unflanged connectors, 50 or 51.5 ohms. VSWR below 1.1 from DC to 1000 MHz.

30303 AURORA RO. CLEVELAND (SOLON) OHIO 44139 · Phone 216-248-1200 For More Details Circle (94) on Reply Card

Level inputs with programmable LED peak level indication; an internal power network for condenser mic's; switchable 70 Hz Hi Pass Filters; Channel Mute and Solo on all inputs; Quad Panning and Quad/4 Track/Stereo mode selection; Direct Track Feed; two independent Echo channels with pre-post fader selection, delay, echo and monitor send and return functions; two independent Cue channels; and self-contained Multitrack mixing amplifiers with full range rotary Submaster level controls.

For More Details Circle (210) on Reply Card

CAIRO LONDON MOSCOW

THE NOVA 5060-12 WAS THERE WITH PRESIDENT NIXON AND THE MAJOR TV NETWORKS; COVERED PRESIDENT FORO'S MISSION TO CHINA.



NOVA SOLIO STATE INVERTERS OPERATING FROM BATTERIES PROVIDE STABILIZED AC POWER TO OPERATE REMOTE BROADCAST EQUIPMENT, TV MONITORS, TAPING EQUIPMENT, AND TELEMETRY.

AVAILABLE IN 12 AND 24VDC MODELS FROM 125VA TO 1KVA.

Need one in a hurry?

CALL US COLLECT FOR SAME DAY SHIPMENT.



ELECTRIC MANUFACTURING CO.

A subsidiary of Nova Industries, Inc.

263 Hillside Avenue Nutley, N.J. 07110

(201) 661-3434

For More Details Circle (129) on Reply Card



STEP UP TO "NATURAL SOUND" AUDIO

STUDIO B



NATURAL ROOM SOUND • INTERNAL/EXTERNAL MIX SELECTION (USE WITH OR WITHOUT A CONSOLE) • REMOTE CONTROL UNIT • PEAK TYPE EQ SELECT PLUS 10 DB VARIABLE EQ GAIN • VARIABLE DECAY • BUILT-IN NATURAL DELAY • BALANCED LINE WITH 5K/600 OHM INPUT SELECT • INPUT SETTABLE FOR NOMINAL ZERO TO +18 DBM • OVERLOAD POINT AT +25 DBM PEAK • 1-3/4" ELECTRONIC RACK PANEL • XLR AUDIO & 'JONES' CONTROL CONNECTORS • VU METER • 115/230 VOLT, 50-60 HZ, 6VA.

MICMIX Audio Products, Inc.

9990 Monroe St., Suite 222, Dallas, Texas 75220

(214) 352-3811

For More Details Circle (218) on Reply Card

FM Transmitting Antenna

CCA Electronics will introduce a new FM transmitting antenna at NAB. This new antenna comes in a low power and a high power version.

The low power version will handle up to 10 kW, while the high power model will take up to 50 kW (single bay). These antennas feature a 700 kHz bandwidth with the SWR under 1.1:1. All elements are 50 ohm to assure lowest Q. Large gap form factor of the antenna eliminates feed point straps and insulators.

Its integral radome is designed to offer no increase in wind load.

For More Details Circle (211) on Reply Card

FM Educational Antennas

Phelps Dodge Communications Company will exhibit representative models of its line of FM broadcast antennas at the Convention.

In the FM educational series, Phelps Dodge offers six types. Because of the normally lower powers required in educational service, the new antennas are fabricated of 7/8 inch stainless steel tubing. The circularly polarized antenna is a 1½ turn helix and the strictly horizontal element has a "U" configuration. These antennas are complete with matching harness of RG type cables and are designed to mount on tower legs or support pipes 1¼ inch to 2¾ inch diameters. The multi-element arrays are designed for an element spacing of 10 feet.

Six models, designated Catalog Nos. ECFM-1, -2, -3, -4, -5 and -6 are available. Power rating in kilowatts varies from 0.2 to 0.5. Power gain ratings range from 0.43 to 2.99; field gain from 0.65 to 1.73; and, gain in dB from -3.66 to 4.76. FS at one mile, 1 kw, MV/M is from 90 to 239.

Incorporating the general design concepts of other Phelps Dodge Communications circularly polarized antennas, the new FM educational series is less susceptible to corona and assure phase coincidence in the centers of both vertical and horizontal components.

Also to be displayed will be two new 1,000 watt per bay circularly and horizontally polarized FM broadcast antennas designed to fill the void which currently exists between an educational series rated at 200 watts per bay and the standard antenna series rated at 5,000 watts per bay. Designated Catalog Nos. CP-1000 and HP-1000 the two new antennas are parallel fed so that a 2-bay antenna is rated at 2 kw, 3 bay at 3 kw, etc.

For More Details Circle (212) on Reply Card

NAB Exhibits Floor Plan Starts on Page 33

CHARACTER GENERATORS?

SIMPLY COMPARE

FEATURES...

No other CHARACTER GENERATOR matches the MODEL 3600 when it comes to operational features. Because television transmission standards limit the amount of information which can be displayed, you will appreciate our choice of a practical character size, legible font and full horizontal edging. For the same reason, we feel strongly about the need to move, control and emphasize message information. That is why the 3600 permits roll, crawl or sequence on any line of the display. That is also the reason for our window format feature and numerous flag functions.

Ease of operation is important in any equipment—especially if you are the operator. The 3600 provides a set of auxiliary keys for those control functions most often used. This eliminates many of the multiple-key operations so often employed by other generators. The elastic memory of the 3600 also adds greatly to its ease of operation.

EXPANDABILITY...

Most character generators tend to limit the size and features of the system to the size of the "box"; not so with the 3600. We not only left plenty of room, but we designed a system which is compatible with a host of extra features. Additional memories and independent output channels will increase the flexibility and versatility of your system. For unlimited, non-volatile information storage you may want to consider data cassette storage.

The data sources of the 3600, such as Up-Down Counter and Time/Date Generator, cannot be ignored as valuable additions to any television system. Also, don't overlook the possible need for lower case and foreign language characters—or maybe math and chemistry symbols.

To top it all off, consider the Color Background, Color Billboard and Color Flag Function. These features will greatly enhance any message display, whether it be full-screen or a simple title.

VALUE...

Many character generators have been sold on the basis of price; conversely, some on the basis of features. We welcome your comparison of our product with any other on the market because we are sure that you want to buy on the basis of value!

See Us at NAB Booth 113





For More Details Circle (214) on Reply Card



For More Details Circle (215) on Reply Card

SBE Convention Details Are On Page 12

BROADCAST engineering.

Regional advertising sales offices

Kansas City, Missouri John Cox, 1014 Wyandotte St., Kansas City, Mo. 64105, (913) 888-4664

Indianapolis, Indiana Roy Henry, 2469 E. 98th St., Indianapolis, Ind. 46280, (317) 846-7026

New York, New York Stan Osborn, 60 E. 42nd St., Room 1227, New York, N.Y. 10017, (212) 687-7240

Mountain View, California

Dennis Triola, 2680 Bayshore Frontage Rd.,
Room 102, Mountain View, Ca. 94043, (415) 961-

London W.C.2, England

John Ashcraft & Co., 12 Bear St., Leicester
Square, Tele: 930-0525

Badhoevedorp, Holland John Ashcraft & Co., John J. Lucassen, Mgr., Sloterweg 303

Tokyo, Japan International Media Representatives, Ltd., Shiba-Kotohiracho, Minato-ku, Tele: 502-0656

advertisers' index

AF Associates99	Marconi Instruments
A A A A A A A A A A A A A A A A A A A	
Accurate Sound Company131	Marti Electronics126
Aderhold Construction	Martin/Audio/Video108
Company	Memorex Corporation
	MIC-MIX Audio Products 166
Allied Broadcast Equipment130	
American Data Corporation7,49	Micro Consultants
Amperex Electro Optical Div41	Micro-Trak Corporation
Ampex Corporation30-31	Microtime, Inc
Ampro Corporation56	Minneapolis Magnetics, Inc 136
Andrew Corporation51	Moseley Associates, Inc20
Angenieux Corp. of America 89	Nagra Magnetic Recorders, Inc 80
Anixter-Mark	Rupert Neve Incorporated113
Audio Designs & Mfg., Inc	Nova Industries, Inc
Audio-Video Engineering162	Nurad Incorporated145
Auditronics	O'Connor Engineering
Belar Electronics Laboratory,	Opamp Labs, Inc
Inc	Otari
Beston Electronics, Inc118	Pacific Recorders
Bird Electronics, Inc166	Philadelphia Resins Corp 134
Broadcast Electronics, Inc10,85	Philips Audio Video Systems22-23
Broadcast Engineering Techniques .69	Potomac Instruments, Inc141
Broadcast Equipment & Supply166	Pulse Techniques166
Bryant Electronics	Quick-Set, Inc
CCA Electronics Corporation143	RCA Distributor and
CMX Systems	Special Products
CSI Electronics, Inc	RCA Electro-Optical Div65
Cablewave Systems	RTS Systems165
Canon Video	Ramko Research61
Capitol Magnetic Products79	Recording Supply Corporation158
Central Dynamics19	Recortec, Inc
Chronotron Systems, Inc62	Revox Corporation
Chyron Telesystems76	Robins/Fairchild156
David Clark Communications164	Rockwell International Cover 2
Comark Industries, Inc	
	Roh Corporation94
Communications Technology60	Ross Broadcast Products114
Comprehensive Service	Russco Electronics, Inc140
Comprehensive Service CorporationCE-2	Scully/Metrotech78
Comquip, Inc	Sennheiser Electric97
Computer Magnetics Corporation 57	Shallco, Inc
Continental Floation:	
Continental Electronic	Shintron Company, Inc
Wholesale Corp155	Sintronic Corporation102
Continental Electronics Mfg. Co 161	Sitler's Supplies, Inc160
Control Design Corporation 117	Sony Corporation of America16-17
Cooks Engineering	Sound Dynamics
Cooke Engineering128	Occupid Technology
Datavision, Inc58-59	Sound Technology
Delta Electronics146,147	Sparta Electronics Corporation 5
Ditch Witch TrenchersCE-4	Spindler & Sauppe, Inc
Dolby Laboratories, Inc 47	Spotmaster
Dynair Electronics, Inc 63	Stainless, Inc
	Ctanton Magnetics 100
Dynasciences Corporation	Stanton Magnetics123
ES Enterprises38,130,140,159,163	Strand Century18
Electrohome Ltd	Studio Tape Exchange156
Electro-Voice, Inc	Systems Marketing Corporation 139
English Electric Valve	Taber Manufacturing
North America1	
	Tandberg of America
Farinon Electric125	Tech Laboratories156
Fidelipac	Tektronix
Firan Electronics	Teledata Systems, Inc
Flash Technology Corp. of	Teledyne Energy Systems162
America	Telemation, Inc
Fujinon Optical122	Television Equipment
Garron Electronics158	Associates, Inc12,160
The Grass Valley Group3	Telex Communications, Inc 160
Harris Corporation	Tentel
Hitachi Shibaden	Tepco Corporation
Ikegami52-53	Texas Electronics, Inc
International Tapetronics	Thomson-CSF Laboratories, Inc 119
Corp	Time & Frequency Technology, Inc. 81
JVC Industries, Inc73	UMC Electronics Company13
Jamieson Film Company88	Ultra Audio Products164
Jampro Antonno Company	
Jampro Antenna Company 109	Unimedia
Jensen Tools and Alloys168	Vamco Engineering62
K&H Products, Ltd164	Varian, Eimac Division77
Kansas State NetworkCE-3	Video Aids Corp. of Colorado14,132
Kings Electronics21	Videomax Corporation9
I DD Inc	Viscount Industries
LPB Inc	Viscount Industries
Laird Telemedia167	Vital Industries, Inc Cover 4
McCurdy Radio Industries, Inc15	Ward-Beck Systems LtdCover 3
McMartin Industries, Inc 107,136	Wilkinson Electronics, Inc
Marconi Electronics, Inc	World Video92
The state of the s	

PROFESSIONAL SERVICES PROFESSIONAL SERVICES

VIR JAMES

CONSULTING RADIO ENGINEERS Applications and Field Engineering Computerized Frequency Surveys 345 Colorado Blvd Phone: (Area Code 303) 333-5562

DENVER, COLORADO 80206 Member AFCCE

RALPH E. EVANS ASSOCIATES

Consulting TeleCommunications Engineers AM-FM-TV-CATV-ITFS 3500 North Sherman Boulevard

MILWAUKEE, WISCONSIN 53216 PHONE: (414) 442-4210 Member AFCCE

SMITH and POWSTENKO

Broadcasting and Telecommunications Consultants

2000 N. Street, N.W. Washington, D. C. 20036 (202) 293-7742

Joseph & Donna Roizen VIDEO CONSULTANTS

International TV Systems Marketing/Technical Writing 800 Welch Rd., Suite 354 Palo Alto, Ca. 94304 Tel: (415)326-6103

LIGHTNING ELIMINATION ASSOCIATES **CONSULTING ENGINEERS** LIGHTNING RELATED PROTECTION

strikes - surges - transients, etc.

ROY B. CARPENTER, JR. - DIRECTOR 9102 Firestone Blvd., Downey Ca. 90241 (213) 923-1268 Cable: LEAINC

Applied Video Electronics, Inc.

STUDIO SYSTEMS DESIGN AND INSTAL LATION ENGINEERING. REFURBISHING/ MODIFYING COLOR CAMERAS AND QUADRUPLEX VIDEO TAPE RECORDERS.

Post Office Box 25 Brunswick, Ohio 44212 Phone (216) 225-4443

Oscar Leon Cuellar

Consulting Engineer 1563 South Hudson (303) 756-8456

DENVER, Colorado 80222 Member AFCCE

P. H. LEE ASSOCIATES, INC. Over 36 Years in Communications And Broadcast Engineering

AM-FM-TV Frequency Measurements

P.O. Box 1575 Thousand Oaks, Calif. 91360 (805) 492-5055 (213) 889-7769

Tahcon Inc. **TELECOMMUNICATIONS**

BROADCAST CONSULTANTS

Sales / Programing / Management / Engineering Field Services

4425 East 31st St

W. H. BRADLEY, P.E.

Consulting Radio Engineer **Engineering Applications** & Field Engineering Phone: 918-245-5444 300 West 41 Street, SAND SPRINGS, OKLAHOMA, 74063

McCLANATHAN & ASSOCIATES

Consulting Engineers

APPLICATIONS & FIELD ENGINEERING TURNKEY INSTALLATIONS—RADIO & TV DIRECTIONAL ANTENNA DESIGN

P.O. Box 750 PORTLAND, OREGON 97207 Phone: 503/246-8080

DAWKINS ESPY

Consulting Radio Engineers Applications/Field Engineering P.O. Box 3127 Olympic Station 90212 Beverly Hills, California

(213) 272-3344

Advertising rates in Classified Section are 25 cents per word, each insertion, and must be accompanied by cash to insure publication.

Each initial or abbreviation counts a full word. Minimum classified charge, \$2.00.

For ads on which replies are sent to us for forwarding (blind ads), there is an additional charge of \$3.00 per insertion, to cover department number, processing of replies, and mailing

Classified columns are not open to advertising of any products regularly produced by manufacturers unless used and no longer owned by the manufacturer or a distributor.

TRAINING

FIRST PHONE in six to twelve weeks through tape recorded lessons at home plus one week personal instruction in Boston, Philadelphia, Detroit, Atlanta, Kansas City, Seattle or Los Angeles. Our twentieth year teaching FCC license courses. Bob Johnson Radio License Preparation, 1201 Ninth, Manhattan Beach, Calif. 90266. Telephone 213-379-4461. 8-75-ti 8-75-tf

BROADCAST ENDORSEMENT and third phone preparation on cassettes. Illustration book includes current FCC-type exams. Radio License Preparation, 1201 Ninth, Manhattan Beach, Calif. 90966 8-75-tf

GET YOUR FIRST TO GET THERE FIRST! DON MARTIN SCHOOL OF COMMUNICATIONS/ Since 1937, training Broadcasters for Broadcasting! 1st Phone training using latest methods and completely equipped Transmitter studio. Call or write for details and start dates. Don Martin School, 7080 Hollywood Blvd., 5th floor, Hollywood, CA 90028. Call (213) 462-3281 or (213) 657-5886.

8-75-tf

TRAINING (CONT.)

EARN YOUR ELECTRONICS DEGREE by correspondence, G. I. Bill approved. For free brochure, write Grantham School of Engineering, Information Desk, 2000 Stoner Avenue, Los Angeles, Calif. 90025. 8-72-tf

PASS FCC EXAMS with Ameco books. Each book contains FCC questions plus simplified answers plus FCC-type exams and answers. 3rd class includes broadcast endorsement \$1.00. 2nd class \$2.25, 1st class \$1.50. Free catalog. Ameco Publishing, 275G Hillside Ave., Williston Park, N.Y. 11596. 8-72-tf

PASS FCC first and second class exams with new 21-lesson, 450-page course. Starts with basic electricity. Over 600 FCC-type, multiplechoice questions and sample exams included. No previous technical knowledge required. Commercial Radio Operator Theory Course, #15-01. Only \$5.95. Ameco Publishing, 275G Hillside Ave., Williston Park, N.Y. 11596. 8-72-tf

SERVICES

FREQUENCY MEASURING SERVICE—WE'RE #2—MONITOR REPAIRS—MOBILE UNIT—covers Northern 2/3 III., Eastern Iowa, Eastern Minn., Southern 2/3 Wis., Western Mich., and Western Ind., monthly. Radio Aids, 528 Ravine Ave., Lake Bluff, Illinois 60044, (312) 234-0953. 2-74-tf

BROADCAST CRYSTALS for AM, FM or TV transmitters. Frequency change, repair or replacement of oven types; also new vacuum types. Quality products, reasonable prices and better delivery! Don't be without a spare crystal. Repair of G.R. 1931-A/B modulation monitors and frequency change of AM and FM frequency monitors. Over 30 years in the business. Eidson Electronic Co., Box 96, Temple, Texas 76501. Phone (817) 12-74-tf 773-3901

COMMERCIAL RADIO MONITORING CO. Precision frequency measurements since 1932. Local and mobile service covering entire midwest plus. Test instruments, counters, monitors repaired and certified. Lee's Summit, Mo. 64063. (816) 524-3777. 9-74-tf

SPOTMASTER PARTS—24 hour service. Repairs and rebuilding of your Spotmaster equipment. Franchised Spotmaster repair service. 90 day warranty. COMMUNICATION MEDIAS/BROAD-CAST COMPONENT DISTRIBUTORS, P.O. Box 54, Allentown, Pa. 18105, 215-437-0607. 6-75-12t

ONE STOP FOR ALL YOUR PROFESSIONAL AUDIO REQUIREMENTS. Bottom line oriented. F.T.C. Brewer Company, P.O. Box 8057, Pensa-7-71-tf cola, Florida 32505.

HELIAX-STYROFLEX. Large stock—bargain prices—tested and certified. Write for price and stock lists. Sierra Western Electric. Box 23872, Oakland, Calif. 94623. Telephone (415) 832-3527.

BUILD YOUR OWN TV AND RADIO PRODUC-BUILD YOUR OWN TV AND RADIO PRODUCTION EQUIPMENT. Easy, inexpensive, (mostly IC). Plans or kits: Special Effects Generator, Automatic Logger, Vertical Interval Video Switcher, Solid State Lighting Board, Preset Audio-Video Board, Preset Lighting Board, Crystal Controlled Wireless Mikes with Matching receivers. Subsonic Tone Control for audio tapes, 8MM SOF Cameras and Projectors, Distribution Amplifices (Syng, Video Audio), Audio Control Boards fiers (Sync. Video, Audio), Audio Control Boards (Studio & Remote) Proc-Amp with compensation and regeneration for adapting Helical Scan VTR's to broadcast standards. PLUS specialized correspondence courses in TELEPHONE Engineering (\$39.50), and Integrated Circuit Engineering (\$49.50). Plans from \$5.95 to \$15. SUPER CATALOG plus years updateing of new devices Air Mailed \$1.00. Don Britton Enterprises, P.O. Drawer G, Waikiki, Ha. 96815.

CAMERA TUBES ... ALL TYPES EXCEPT ORTHI-CAMERA TUBES...ALL TYPES EXCEPT ORTHICONS CAN NOW BE RECONDITIONED AT AN
UNBELIEVABLE PRICE, LEAD OXIDE TYPES
\$300.00, VIDICONS FROM \$35 TO \$200.00. ALL
RECONDITIONED TUBES COME WITH 500 HOUR
WARRANTY. FOR DETAILS WRITE: RODONCO
ENGINEERING, CAMERA TUBE DIV., 4020
STAPLETON DR., BLOOMINGTON, IND. 47401.
8.75-14

WANTED

WANTED: All surplus broadcast equipment especially clean A.M. & F.M. transmitters, capacitors, 112 Clark & Potomac Phase monitors, sealed strength meters, etc. High prices. All custom duties paid. Surplus Equipment Sales at 2 Thorncliffe Pk. Dr., Unit 28, Toronto 17, Ont., Canada (416) 421-5631.

WANT TO BUY-5 or 10,000 wtt A.M. transmitter. Reply Stanley Scott, 261 So. 52nd St., Philadelphia. PA. 3-76-1t

WANTED: Pre-1926 radio equipment and tubes. August J. Link, Surcom Associates, 305 Wisconsin Ave., Oceanside, Ca. 92054, (714) 722-6162.

WANTED: WX2 or 120 series FS meter in good condition. Contact Chris Hood, 11 E. Prospect Avenue, Pittsburgh, Pa. 15205, 412-921-2943.

3-76-2t

EQUIPMENT FOR SALE

FOR SALE: Television STL System Ratheon KTR 2-7 GHZ dual link for audio and video complete with ant., trans. line, and 8' X 12' reflector. Also TR 22 High band color video tape machine. Write WXON-TV, P.O. Box 2020, Southfield, MI, 48075 or call 313-355-2901.

SPOTMASTER, FIDELIPAC, RUSSCO, ROH, ELECTRO-VOICE, OTARI, RAMKO, SCOTCH, STANTON, NORTRONICS, SHURE, SENN-HEISER, TELEX, MAGNECORD, and VIKING are all items distributed and serviced by COMMUNICATION MEDIAS/BROADCAST EQUIPMENT DISTRIBUTORS, P.O. Box 54, Allentown, Pa. 18105. 215-437-0607. "Sudden Service" our specialty.

6-75-12t

WHATEVER YOUR EQUIPMENT NEEDS—new or used—check us first. We specialize in broadcast equipment. Send \$1.00 for our complete listings. Broadcast Equipment & Supply Co., Box 3141, Bristol, Tenn. 37620.

MAGNECORD PT6-A RECORDERS. Rebuilt units and new and used Magnecord, Telex, Viking, and Spotmaster parts. Huge supply, lowest prices. REBUILT CARTRIDGE TAPE EQUIPMENT. Soptlessly clean and thoroughly tested. 30 day moneyback guarantee. ONE YEAR warranty. REPAIR AND RECONDITIONING SERVICES for cartridge equipment by factory trained technicians. Send for complete information: AUTODYNE, Box 1004, Rockville, Md. 20850, (301) 762-7626.

BROADCAST CRYSTALS for AM, FM or TV transmitters. frequency change, repair or replacement of oven types. Also new vacuum types for RCA, Gates, Collins, etc. transmitters. Quality products, reasonable prices and better delivery! Don't be without a spare crystal. Frequency change and service for AM and FM frequency monitors. Over 30 years in the business. Eidson Electronic Co., Box 96, Temple, Texas, 76501. Phone (817) 773-3901

A FEW COMPETITIVELY PRICED used Revox A77 decks available. Completely reconditioned by Revox, virtually indistinguishable from new and have the standard Revox 90 day warranty for rebuilt machines. Satisfaction guaranteed. Example, A77 with Dolby, \$675, plus shipping. Write requirements to ESSI, Box 854, Hicksville, NY, 1190, (515), 021, 225, 614 N.Y. 11802 (516) 921-2620.

STODDART RADIO interference-field intensity meters. Stoddart NM-22A, 150KHZ-32MHZ. Complete - \$2,195, less antennas - \$1,595. Stoddart NM-30A, 20-400MHZ. Complete - \$1,295. Stoddart NM-52A, 375-1000MHZ. Complete - \$1,495, less antennas - \$1,095. All are in excellent condition and calibrated prior to shipment. Surcom Associates, (213) 382-6985. 6-75-tf

MOTORS FOR SPOTMASTERS

NEW Paps hysteresis synchronous motor HSZ 20.50-4-470D as used in series 400 and 500 machines. Price \$49.00 each prepaid, while they last. 90 day warranty. Terms check with order only, no COD's. Not recommended for Tapecaster series 600 or 700.

TAPECASTER TCM, INC., Box 662 Rockville, Maryland 20851

1-72-tf

EQUIPMENT FOR SALE (CONT.)

RHODE & SCHWARTZ deviation meter model FMV BN4620 Serial 127423, \$2500.00 or swap on 1957 Thunderbird. (904) 587-5263, 968-6734.

2-76-2t

SPOTMASTER EQUIPMENT AND PARTS now in Texas from Sales Southwest, 4002 Houston Highway, Victoria, Texas 77901. 512-578-4323.

FULL LINE TUNING and phasing components available, including contractors, also large supply separate contacts for E. F. Johnson contactors. Write: Geleco Electronics, Ltd., #2 Thorncliffe Park Drive, Unit 28, Toronto 17, Canada. Phone: (416) 421-5631.

SMC 3060 AUTOMATION with 2 RS carousels with memories and 4 Mk IV Revox's, Collins 830 exciter w/stereo generator, Collins 900C1 stereo modulation monitor, Collins 26U2 stereo limiter, Gates Criterion R/P cart machine and CCA exciter with SCA generator. Must sell fast. (714) 873-5861

WICA AND VACUUM transmitting capacitors. Vacuum relays. Large stock; immediate delivery. Price lists on request. SURCOM ASSOCIATES, 305 Wisconsin Ave., Oceanside, Ca 92054, (714) 3-76-tf

EMPIRE NF105W, interference intensity meter, 4 plug-ins, \$1500.00. ROHDE-SCHARTZ FMV deviation meter, \$1000.00; JERROLD 704B, \$200.00 3-76-2t (904) 587-5263.

LOGGING SYSTEM, complete, English text with two teletypes, digital clock, encoder & decoder, prints hours, minutes, seconds and AM-PM. Nearly new \$4,800.00. Belar FM RF amplifier, new condition, \$275.00. Moseley RPL-2, \$475.00. Hewlett Packard Counter, Mod. 524, with time interval and 100 mc. plug in's, \$495.00. KSRN, Reno, Nevada 89501, 702-786-1045.

HELP WANTED

ATTENTION CHIEF ENGINEERS: We need to add five people of your caliber to our expanding staff. Are you tired of a 7 day week, 24 hour day? Would you like to get that monkey off your back? If you have 7 years experience in studio and transmitter supervision and maintenance, and would like to work 5 days a week, 7 hours a day for a good salary, send resume to Robert A. Gay, Director of Engineering, WAAY-TV, 1000 Monte Sano Blvd., Huntsville, Alabama 35801. 1-76-3t

NEW PATENTED master antenna system used NEW PATENTED master antenna system used throughout U.S. needs local supervision of installations one day per week. I have made over \$200.00 per day in supervision fees. Must be electronic troubleshooter. Protected territory. Send resume to Melvin Cohen, 1620 N. Federal Highway, Boynton Beach, Fla. 33435. Enclose 13 cent addressed envelope. Be patient for my reply.

VIDEO CIRCUIT DESIGN ENGINEER: Responsible position for person with good solid state experience and understanding of NTSC, PAL, and SECAM color circuits. Apply to V. Hallett, 418F Pine Street, Grass Valley, Calif. 95945, or call (916) 272-1971. 3-76-1t

TELEVISION BROADCASTING ENGINEER. Must have a valid FCC First Phone License. This will be renewable at expiration. Must have a minimum of 5 years experience in VHF TV transmitter operation and maintenance. RCA TT-30FL and TT-25BL background preferred. Transmitter remote control experience helpful. Box 1986, Pittsburgh, Pa. An Equal Opportunity Employer. M/F. 3-76-1t

VIDEO SALES REPRESENTATIVES: National Sales & Marketing organization seeks to expand its Video sales force. Openings available in every state. Excellent opportunity for proven Video sales personnel. Liberal commission program. Send resume to: Dept. 349, Broadcast Engineering, 1014 Wyandotte St., Kansas City, Mo. 64105.

MOVE UP from your present job in broadcast engineering. We handle all engineering jobs and openings coast to coast. Send full resume confidentially now. The AMPS Agency, 6331 Hollywood Blvd., Suite 623, Los Angeles, Calif. 90028. Tel: (213) 462-7301.

HELP WANTED (CONT.)

VIDEO ENGINEER-Working broadcast engineer WIDEO ENGINEER—Working broadcast engineer with first phone and FM experience. Strong on supervision and maintenance of portable and studio color video equipment. Must work well with staff and students in open academic atmosphere. Practical experience counts! Reply in writing to Director, Instructional Systems, Stephens College, Columbia, Mo. 65201. Include to history and references. job history and references.

CHIEF ENGINEER, FIRST CLASS FOR DI-RECTIONAL AM, FM IN MEDIUM SIZE CALI-FORNIA MARKET. MUST BE FULLY EXPERI-ENCED IN ALL PHASES OF TRANSMITTER AND ENCED IN ALL PHASES OF TRANSMITTER AND STUDIO ENGINEERING, INCLUDING AUTO-MATION. AREA EXCELLENT FOR RAISING FAMILY, ENJOYING BOATING, FISHING YEAR ROUND. PLUS SIERRA SKIING AND OCEAN BEACHES JUST TWO HOURS DISTANT. STATIONS HAVE EXCELLENT COMMUNITY IMAGE, LONG TERM EMPLOYEES, TOP FRINGE BENEFITS. BOTH HAVE TOP RATINGS IN THEIR RESPECTIVE FORMATS. E.O.E. INQUIRE DRAWER "Y", STOCKTON, CALIFORNIA 95202. NEED IS BY JUNE. NEED IS BY JUNE.

HOME BOX OFFICE, A SUBSIDIARY OF TIME, INC.—THE NATIONAL TERRESTRIAL AND SATELLITE PROGRAM DISTRIBUTOR TO THE CABLE INDUSTRY—IS LOOKING FOR AN EXPERIENCED TV & AUDIO ENGINEER WITH BACKGROUND IN MICROWAVE, CABLE & PAY TV HARDWARE. DUTIES INCLUDE SIGNAL QUALITY CONTROL & INTERFACING WITH CABLE SYSTEMS. 30% TRAVEL IN THE NORTH-FAST ANTICIPATED. SEND. RESUME TO MR EAST ANTICIPATED. SEND RESUME TO MR. GEORGE GILBERT, DIRECTOR OF NETWORK OPERATIONS, TIME/LIFE BUILDING, ROCKE-FELLER CENTER, NY, NY 10020. 3-76-11

\mathbb{A} GRASS VALLEY GROUP

We are looking for experienced engineers in the following categories:

- CIRCUIT DEVELOPMENT. Applicants should be thoroughly familiar with the latest solid state devices and techniques. BSEE and at least 5 years of experience required.
- TV SYSTEMS ENGINEERS. Applicants should be thoroughly familiar with television systems. Minimum of 5 years of TV experience required
- TV SALES ENGINEERS. 5 years of TV broadcasting experience required.
- TV FIELD SERVICE ENGINEERS. BSEE reguired. Applicants should be willing to travel in the US and abroad for a 2-year period before becoming permanently assigned to the plant in Grass Valley.

Send resume and safary requirements in confidence, to Robert L. Cobler, The Grass Valley Group, Inc., P.O. Box 1114, Grass Valley, California 95945.

Arrangements can also be made for an interview at the NAB exhibition — Chicago, March 21-24.


An equal opportunity employer

SITUATION WANTED

BROADCAST ENGINEER, eight years experience, Kansas City, Mo. 64105.

BROADCAST ENGINEER/ASSISTANT. U.S. Army Retired 20 yrs. Experience Helicopter Maintenance and Supervision. CIE graduate, 2 yrs. college on BSEE degree. 1st Class Phone license. No experience. For complete resume write AIR MAIL to Rodger D. Fetters, 321D Tindalo St., Cebu City, Philippines. 3-76-1t

AUDIO/FM ENGINEER desires part-time steady work in NYC area. Design, installation, mainte-nance. AB degree, own tools and test eqpt., First Phone, 212-795-6616.





Unmistakably Ward-Beck



Tomorrow's Technology Today.

Ward-Beck Systems Ltd., 841 Progress Avenue, Scarborough, Ontario M1H 2X4 Telephone (416) 438-6550. Telex 06-23469

Ward-Beck Systems Inc., 290 Larkin Street, Buffalo, N.Y. 14210

For More Details Circle (2) on Reply Card

VIX-114 production switcher with STAR studded features Choice of over 80

Choice of over 80 exciting patterns such as star, heart, binoculars, keyhole,

rotary clockwipe and more

- 12, 16, 20, or 24 inputs. 4 bus, 6 bus, 8 bus or more bus systems.
- All digital waveform and quad split generators.
- Digital key edging, border, shadow and outline available on all ME's.
- Vari-key. Soft, hard, shadow, or see-thru key.
- Digital quad split. Wipe or dissolve in each quadrant.
- Electronic vignette. Adjustable soft pattern edges.
- Superb linear chroma keyer. RGB or encoded.
- New digital, drift and jitter-free proc. amp on output.
- Ready to interface for computer aided operation.
- Many more state of the art and operational features described fully in series 114 brochure.

Do not fear to discover a superior product in the VIX-114 series switchers. Ask to see the demo tape for a sample of what we can do for users of switching equipment.

MORRELL BEAVERS Midwest 2644 North Seventh St. Terre Haute, Indiana 47804 Phone 812/466-3212 ROBERT McALL Northeast 34 Autumn Lane Hicksville, N. Y. 11801 Phone 516/735-0055 The VIX-114 series video switching systems are conceived and designed by the largest specialized independent video switching company in the USA. Vital Industries, Inc. is holder of US patents on digital effects and analog rotary effects. Vital VIX-114 series switchers open new vistas in production of television commercials and programs to yield maximum pleasant visual impact.

GOOD ENGINEERING IS VITAL

VITAL INDUSTRIES, INC.

MAIN OFFICE: 3700 N.E. 53rd Ave., Gainesville, Fla. 32601 • Phone 904/378-1581

GORDON PETERS Southwest P. O. Box 912 Arlington, Texas 76010 Phone 817/261-6855 Fox Hill Road Lynchburg, Va. 24503 Phone 804/384-7001 GORDON PETERS West Coast 7960 West Beverly Blvd. Los Angeles, California 90048 Phone 213/653-9438

For More Details Circle (3) on Reply Card