


Wireless World

RADIO AND ELECTRONICS



JULY 1949

2/-

Vol. LV. No. 7

IN THIS
ISSUE :

TUNABLE TELEVISION RECEIVERS

The **NAME** helps you sell
The B I C C
All Wave
ANTI-INTERFERENCE
AERIAL



BICC are world famous for their electrical and radio products. The Anti-Interference Aerial maintains this reputation.

What it does

It has been specially designed to alleviate interference caused by radiation from electrically-operated transport, vehicle ignition systems, electrical appliances using commutator motors, lighting systems, etc. A high signal level is obtained and this ensures better listening on all broadcast wave-lengths, giving maximum choice of programmes against a quiet background.

What it is

A 60-ft. polythene-protected dipole complete with insulators and matching transformer, 80-ft. coaxial screened downlead with polythene plug moulded to each end, and a receiver transformer. All the necessary components for the Aerial are included in the complete kit.



Write for Publication No.221S giving further information.

Obtainable only from recognised dealers.

£6.18.0

BRITISH INSULATED CALLENDER'S CABLES LIMITED
NORFOLK HOUSE, NORFOLK STREET, LONDON, W.C.2

Fine Limits of Accuracy



VALVE CHARACTERISTIC METER

A comprehensive instrument built into one compact and convenient case, which will test any standard receiving or small power transmitting valve on any of its normal characteristics under conditions corresponding to any desired set of D.C. electrode voltages. A patented method enables A.C. voltages of suitable magnitude to be used throughout the Tester, thus eliminating the costly regulation problems associated with D.C. testing methods.

A specially developed polarised relay protects the instrument against misuse or incorrect adjustment. This relay also affords a high measure of protection to the valve under test. Successive settings of the Main Selector Switch enable the following to be determined:—

Complete Valve Characteristics including I_a/V_g , I_a/V_a , I_s/V_g , I_s/V_a , Amplification Factor, Anode A.C. Resistance, 4 ranges of Mutual Conductance covering mA/V figures up to 25 mA/V at bias values up to -100V., together with "Good/Bad" comparison test on coloured scale against rated figures.

"Gas" test for indicating presence and magnitude of grid current, inter-electrode insulation hot and cold directly indicated in megohms, separate cathode-to-heater insulation with valve hot. Tests Rectifying and Signal Diode Valves under reservoir load conditions, and covers all the heater voltages up to 126 volts.

The AUTOMATIC COIL WINDER & ELECTRICAL EQUIPMENT CO., LTD.

WINDER HOUSE, DOUGLAS STREET, LONDON, S.W.1. Phone: VICTORIA 3404-9

Avo Precision Electrical Testing Instruments


**"It is on detail and care in design
of small points that the
modern set stands or falls"**

"Radio Times," Sept. 24, 1948

Attention to details of manufacture and assembly; revolutionary design and the provision of highly accurate specially designed jigs, ensure that in each R. & A. Reproducer the cone, voice coil centre and outer pole are inevitably and automatically aligned upon the axis of the speaker. This is why R. & A. Reproducers are free from mechanical defects. Continuous inspection at all stages is a further insurance that no defect can be present in the complete speaker.

"The Story of Co-Axial Construction" explains how our speakers are built. We will gladly send a copy to any manufacturer or overseas buyer who writes for one.

Voice coil and centering member sub-assembly.



REPRODUCERS AND AMPLIFIERS LIMITED

FREDERICK ST. WOLVERHAMPTON ENGLAND
Telephone Wolverhampton 22241 Telegrams "Audio Wolverhampton"


R&A

SPRING LOADED TERMINALS

A Positive CONNECTION WITHOUT SOLDER · SIMPLY PRESS & RELEASE


PAINTON

PAINTON & CO. LTD · KINGSTHORPE · NORTHAMPTON · ENGLAND



CRYSTAL DEVICES by *Cosmocord*

CRYSTAL PICK-UPS AND CARTRIDGES




G.P. 10 with "unbreakable" crystal. Output 1.7 volts at 1,000 c/s; range 70—8,000 c/s.

G.P. 12 high fidelity model with permanent sapphire stylus. Output 1 volt at 1,000 c/s; range 30—14,000 c/s.

G.P. 15 Microcell cartridge for microgroove or standard 78 rpm recordings.


GENERAL-PURPOSE MICROPHONES



For acoustic measurements, industrial noise measurement, disc recording technique, and P.A. systems.

Type MIC 16 (illustrated)
High fidelity model with flat response from 30 to 10,000 c/s.


Type MIC 22
General purpose model with substantially flat response from 40 to 8,000 c/s.



The MAGNETIC
TYPES G.P. 6
and G.P. 7

Good performance with exceptionally robust construction. Range 100—4,500 c/s.

DISC CUTTER HEADS



TYPE R.H. 1


Good performance and modest price make it ideal for amateur recordist.



TYPE R.H. 2


High-quality cutting head for professional use.

HEARING-AID MICROPHONES



ACOS technique ensures maximum performance within minimum practical dimensions. Seven types and sizes available. Supplied only to hearing aid manufacturers.

MINIATURE EAR-PIECES




TYPE R.E. 5

For hearing-aid use; unobtrusive, light in weight, and with "ideal" performance. Supplied only to hearing aid manufacturers.

PILLOTONE "Individual" LOUDSPEAKER

For hospital or personal use, giving quality equivalent to normal loudspeaker without disturbing others.


Sole distributors of the 'Pilotone' in the British Isles, Messrs. Philips Electrical Limited.




**MEET US AT
RADIOLYMPIA
SEPT 28 - OCT 8**

**STAND No. 7 & DEMONSTRATION
ROOM No. D10, where you can hear
sound reproduction at its best—the
ACOS way!**

H.T. AND E.H.T. RELIABILITY



Typical rectifier for use in A.C. or A.C./D.C. receivers.



Type 36EHT rectifier. Two such units only $2\frac{1}{2}$ " long by $\frac{7}{16}$ " dia. will give an output of 5.3kV.




"Westeht" E.H.T. supply unit. 5kV output from a 350-0-350 A.C. input.

WESTINGHOUSE **WESTALITE** **RECTIFIERS**

Write for details to Dept. W.W.7.

**WESTINGHOUSE BRAKE & SIGNAL
CO. LTD.**

82, York Way, King's Cross, London, N. 1



Plans for a neighbourly world

Marconi's first wireless messages did more than enable nation to speak to nation. They drew closer the world's boundaries, quickened the tempo of existence and turned distant acquaintances into next-door neighbours. Broadcasting has helped still further to increase our knowledge of our neighbours; wireless navigational aids and radar have brought greater safety and faster travel between Continents. And so Marconi's will continue to pioneer. Their engineers are busy today on developments which will make the world a closer community tomorrow.

Marconi
the greatest name in wireless

MARCONI'S WIRELESS TELEGRAPH COMPANY LTD.,
MARCONI HOUSE, CHELMSFORD, ESSEX.

DAILY DEMONSTRATIONS

of the "BARKER 148A" mounted in the "RD" BASS REFLEX CABINET in conjunction with the "RD" JUNIOR or "WILLIAMSON" AMPLIFIERS.

Full details forwarded on request.

ROGERS DEVELOPMENTS CO.,
106 Heath Street, Hampstead, N.W.3

AN ATTEMPT TO REALISE AN IDEAL

In the High Quality World, let us commend Patience, Perseverance, and Good Temper above all; but also Skill and Intelligence.

The ultimate performance of a speaker unit—especially if it is a very good one—depends as much on the intelligence of the user as on the skill of the designer.

If you are a true quality enthusiast, perseveringly pursuing an Ideal, then we know we can help you.

To readers in the North West, we demonstrate the 148A and discuss its best possible use.


J. H. BRIERLEY (Gramophones and Recordings) **LTD.,**
46 Tithebarn Street, Liverpool, 2

M^R.A.C. BARKER'S 148^A

In December 1947 we were complimented by the Wireless World on some features of the Barker 148. These were: the excellent balance at comparatively low levels; the homogeneity of high frequency response; low frequency response sensibly uniform down to 40 c/s with no major bass resonance.


Of the new 148a, with its better magnet and new cone treatment, owners and critics have remarked: the attack and transient response give the impression of contrast expansion; so wide a range of frequencies with apparent evenness of output produces an aural naturalness which has to be heard to be appreciated; it is the best baffle loaded speaker we have ever heard.

We ourselves believe it to be the most NATURAL, satisfyingly truthful and pleasant to live with sound reproducer made anywhere.



The unique constructional features, patented in many countries and exclusive to BARKER, contribute to this performance. First is the DUAL DRIVE shown on the left, and second the cone LOGARITHMIC CORRUGATIONS.

These produce a very smooth highly damped acoustic generator of exceptionally wide frequency range and remarkable clarity. They are described fully in a new leaflet obtainable at the specialists who join us in this announcement, or



from your usual dealer, or from our monomark address

BCM/AADU, LONDON, W.C.1

The 148a is being sent to many countries overseas.

EXPORT ENQUIRIES INVITED

MOST NATURAL SOUND REPRODUCER

See our
Advt.
on
page 10

ALWAYS THINK OF
GOODSELL LTD.
FOR STANDARD
AND SPECIAL
**HIGH FIDELITY
AMPLIFIERS**

WEBB'S RADIO invite you to hear the "Barker 148A" in our demonstration room, from radio or the Brierley pick-up. You will doubtless endorse our opinion that this is an outstanding loud-speaker.

(Webb's hire-purchase facilities available on all equipment.)

Stockists for: **BARKER, WEBB'S RADIO**
MORDAUNT, VOIGT, LEAK,
CHARLES, BRIERLEY, AND 14 Soho Street
ALL "HI-FI" EQUIPMENT. London, W.1

SMALL OSCILLOSCOPE AND WOBBULATOR

Specially designed for Service Engineers

Oscilloscope Type 1/B

Time-base: 10—350,000 c/s.

X.Plates: Direct or Amplified.

Y.Plates: Direct or Amplified.

Miniature Valves and $1\frac{1}{2}$ " diameter
C.R.T.

Dimensions: Height $7\frac{3}{4}$ " Width $5\frac{1}{2}$ "
Depth 11"

Wobbulator Type 1/B

Separate Power Supply: 200-250V.
50 c/s.

Output Voltage: 4V. R.M.S.

Nominal Frequency: 1.2 Mc/s.


Frequency Deviation: 0 to ± 40 Kc/s.

Dimensions: Height $2\frac{3}{4}$ " Width $5\frac{1}{2}$ "
Depth 11"

The two units clip together and are priced at


ONLY **£20**

ERSKINE LABORATORIES LTD—SCALBY, SCARBOROUGH, YORKS.



The mounting of this loudspeaker grille is achieved by the use of "Push-On" Type Spire Fixes on integral unthreaded moulded studs. Inserts eliminated; moulding costs reduced; assembly is REALLY FAST.


that's fixed that



Keeping assembly cost DOWN (and at the same time keeping assemblies safely together) can be a major production headache. Spire Speed Nuts answer that requirement. And many others as well. Acting on its own double-spring locking device, each Spire nut is speedier to put on, holds tighter when it's home. Awkward fixings and blind assemblies are tackled with equal ease by Spire. Sometimes threaded members can be eliminated altogether. Will you write for more information on Spire Speed Nuts—the fastest thing in fastenings?

Spire
Brand
SPEED NUTS

For
NON STOP
"Performance"



The RC49 . . . a new, reliable Automatic Record Changer featuring PERFORMANCE, LIGHTNESS and LOW COST

Collaro's new Model RC49 *more* than fills a long felt need . . . it brings you a reasonable priced record changer incorporating all the refinements hitherto associated only with expensive instruments . . . *plus* many new features not to be found in any other record changer.

The RC49 loads, unloads, selects, plays repeats or rejects 10" or 12" records mixed in any order, by the operation of one single control knob.

The powerful induction-type MOTOR is suitable for 100/130 and 200/250 volts A.C., and incorporates the new "Rim Drive." Beautifully simple and completely reliable, the RC49 will give years of trouble-free service.

The

COLLARO

RC49

Automatic Record Changer

COLLARO LTD.,

RIPPLE WORKS, BY-PASS ROAD, BARKING, ESSEX

Telephones : Rippleway 3333

Telegrams : "KORLLARO, BARKING"

★ Write to-day for trade terms and interesting free leaflet which fully describes the Collaro Automatic Record Changer.

MAKERS OF FINE QUALITY GRAMOPHONE COMPONENTS, INCLUDING: COLLARO GRAMOPHONE UNITS, INDUCTION MOTORS, DE LUXE MICROGRAM PORTABLE ELECTRIC GRAMOPHONES.